

## **Construction Noise and Vibration Monthly Report – November 2022**

**Solihull Metropolitan Borough Council**

<b>Non-Technical Summary</b>	<b>1</b>
<b>Abbreviations and Descriptions</b>	<b>3</b>
<b>1 Introduction</b>	<b>4</b>
1.2 Measurement Locations	7
<b>2 Summary of Results</b>	<b>9</b>
2.1 Summary of Measured Noise Levels	9
2.2 Exceedances of the LOAEL and SOAEL	13
2.3 Exceedances of Trigger Level	15
2.4 Complaints	16
<b>Appendix A Site Locations</b>	<b>17</b>
<b>Appendix B Monitoring Locations</b>	<b>27</b>
<b>Appendix C Data</b>	<b>37</b>

#### **List of tables**

Table 1: Table of Abbreviations	3
Table 2: Monitoring Locations	7
Table 3: Summary of Measured dB $L_{Aeq}$ Data over the Monitoring Period	10
Table 4: Summary of Measured PPV Data over the Monitoring Period	13
Table 5: Summary of Exceedances of LOAEL and SOAEL	14
Table 6: Summary of Total Exceedances of SOAEL	15
Table 7: Summary of Exceedances of Trigger Levels	16
Table 8: Summary of Complaints	16

# Non-Technical Summary

This Noise and Vibration Monitoring Report fulfils HS2 Limited's commitment detailed in the Environmental Minimum Requirements (EMRs), Annex 1, Code of Construction Practice, to present the results of noise and vibration monitoring carried out within the Solihull Metropolitan Borough Council (SMBC) during the month of November 2022.

Within this period monitoring was undertaken at the following worksites:

- Noise monitoring was undertaken at the Coleshill Heath Road worksite (ref.: CHR), where work activities included de-vegetation works, topsoil stripping, on-site mobilisation, filling works, excavation, Concrete pouring, formwork for walls, installation of rigid inclusions, sub-soil cutting, pile cropping works, trenchwork, ducting and backfilling works.
- Noise monitoring was undertaken at the Packington Embankment worksite (ref.: PE), where work activities included installation of parapets, topsoil stripping, digging works, remediation of topsoil, installation of duct and testing, trench works, excavation and backfilling works.
- Noise monitoring was undertaken at the Bickenhill Cutting worksite (ref.: BIC), where work activities included pile cropping, excavation, installation of ducts, backfilling works and piling works.
- Noise monitoring was undertaken at Diddington Lane Embankment (ref.: DLE), where work activities included topsoil stripping, filling piling platform and excavation works.
- Noise monitoring was undertaken in the vicinity of the Blythe Bypass Embankment Worksite (ref.: BBE), where stone backfilling were underway.
- Noise monitoring was undertaken in the vicinity of the A452 compound (ref.: A452), where plant movement and excavation works were underway.
- Noise monitoring was undertaken in the vicinity of the Park Lane Worksite (ref.: PL) where materials haulage and laydown, topsoiling of stone bund, plant movement and vegetation clearance works were underway.
- Noise and Vibration monitoring was undertaken in the vicinity of the Balsall Common Viaduct Worksite (ref.: BCV) where excavation works, and plant movement were underway.
- Noise monitoring was undertaken in the vicinity of the Carol Green Rail Underbridge Worksite (ref.: CGRU), where material movement works were underway.

- Noise and vibration monitoring were undertaken in the vicinity of the Waste Lane Overbridge and Satellite Worksite (ref.: WLOS), where diaphragm wall installation, piling works and road sweeping works were underway.

Further works were also undertaken as part of the utilities diversion between Meriden road & Diddington Lane.

The HS2 threshold levels for significant noise impacts, which are defined in Information Paper E23 (<https://www.gov.uk/government/publications/hs2-information-papers-environment>), were exceeded on one (1) occasion due to HS2 works in the Local Authority Area during November 2022.

There were no exceedances of trigger levels as defined in Section 61 consents during the reporting period at any monitoring position.

No complaints were received during the monitoring period.

# Abbreviations and Descriptions

The abbreviations, descriptions and project terminology used within this report can be found in Table 1.

Table 1: Table of Abbreviations

Acronym/Term	Definition
$L_{Aeq,T}$	See equivalent continuous sound pressure level
Ambient sound	A description of the all-encompassing sound at a given location and time which will include sound from many sources near and far. Ambient sound can be quantified in terms of the equivalent continuous sound pressure level, $L_{pAeq,T}$
Decibel(s), or dB	Between the quietest audible sound and the loudest tolerable sound there is a million to one ratio in sound pressure (measured in Pascal (Pa)). Because of this wide range, a level scale called the decibel (dB) scale, based on a logarithmic ratio, is used in sound measurement. Audibility of sound covers a range of approximately 0-140dB.
Decibel(s) A-weighted, or dB(A)	The human ear system does not respond uniformly to sound across the detectable frequency range and consequently instrumentation used to measure sound is weighted to represent the performance of the ear. This is known as the 'A weighting' and is written as 'dB(A)'.
Equivalent continuous sound pressure level, or $L_{Aeq,T}$	An index used internationally for the assessment of environmental sound impacts. It is defined as the notional unchanging level that would, over a given period of time (T), deliver the same sound energy as the actual time-varying sound over the same period. Hence fluctuating sound levels can be described in terms of an equivalent single figure value, typically expressed as a decibel level.
Exclusion of data	Measurement of noise levels can be affected by weather conditions such as prolonged periods of rain, winds speeds higher than 5m/s and snow/ice ground cover. Noise levels measured during these periods are considered not representative of normal noise conditions at the site and, for the purposes of this report, are excluded from the assessment of exceedances and calculation of typical noise levels and are also greyed out in charts. Identifiable incongruous noise and vibration events not attributable to HS2 construction noise are also excluded.
Façade	A facade noise level is the noise level 1m in front of a large reflecting surface. The effect of reflection, is to produce a slightly higher (typically +3 dB) sound level than it would be if the reflecting surface was not there.
Free-field	A free-field noise level is the noise level measured at a location where no reflective surfaces, other than the ground, lies within 3.5 metres of the microphone position.
LOAEL	Lowest Observed Adverse Effect Level - the level above which adverse effects on health and quality of life can be detected.
Peak particle velocity, or PPV	Instantaneous maximum velocity reached by a vibrating element as it oscillates about its rest position. The PPV is a simple indicator of perceptibility and risk of damage to structures due to vibration. It is usually measured in mm/s.
SOAEL	Significant Observed Adverse Effect Level - the level above which significant adverse effects on health and quality of life occur.
Sound pressure level	The parameter by which sound levels are measured in air. It is measured in decibels. The threshold of hearing has been set at 0dB, while the threshold of pain is approximately 120dB. Normal speech is approximately 60dB at a distance of 1 metre and a change of 3dB in a time varying sound signal is commonly regarded as being just detectable. A change of 10dB is subjectively twice, or half, as loud.
Vibration dose value, or VDV	An index used to evaluate human exposure to vibration in buildings. While the PPV provides information regarding the magnitude of single vibration events, the VDV provides a measure of the total vibration experienced over a specified period of time (typically 16h daytime and 8h night-time). It takes into account the magnitude, the number and the duration of vibration events and can be used to quantify exposure to continuous, impulsive, occasional and intermittent vibration. The vibration dose value is measured in $m/s^{1.75}$ .

# 1 Introduction

1.1.1 HS2 is required to undertake noise (and vibration) monitoring as necessary to comply with the requirements of the High Speed Rail (London-West Midlands) Environmental Minimum Requirements, including specifically Annex 1: Code of Construction Practice, in addition to any monitoring requirements arising from conditions imposed through consents under Section 61 of the Control of Pollution Act, 1974 or through Undertakings & Assurances given to third parties. Such monitoring may be undertaken for the following purposes:

- monitoring the impact of construction works;
- to investigate complaints, incidents and exceedance of trigger levels; or
- monitoring the effectiveness of noise and vibration control measures.

1.1.2 Monitoring data and interpretive reports are to be provided to each relevant local authority on a monthly basis and shall include a summary of the construction activities occurring, the data recorded over the monitoring period, any complaints received, any periods in exceedance of agreed trigger levels, the results of any investigations and any actions taken or mitigation measures implemented. This report provides noise data, and interpretation thereof, for monitoring carried out by HS2 within the Solihull Metropolitan District (SMBC) for the period 1<sup>st</sup> to 30<sup>th</sup> November 2022.

1.1.3 Construction sites in the local authority area where monitoring was undertaken during this period include:

- Coleshill Heath Road worksite, ref.: CHR (see Plan 5 in Appendix A), works activities included:
  - De-vegetation works.
  - Topsoil stripping.
  - On-site mobilisation.
  - Filling works.
  - Excavation.
  - Concrete poring for slab and wall.
  - Formwork for walls.

- Installation of rigid inclusions.
- Sub-soil cutting.
- Pile cropping works.
- Trenchwork.
- Ducting.
- Backfilling works.
- Packington Embankment worksite, ref.: PE (see Plan 6 in Appendix A), works activities included:
  - Installation of parapets.
  - Topsoil stripping.
  - Digging works.
  - Remediation of topsoil.
  - Installation of duct and testing.
  - Trench works.
  - Excavation.
  - Backfilling works.
- Bickenhill Cutting worksite, ref.: BIC (see Plan 6 in Appendix A), works activities included:
  - Pile cropping.
  - Excavation.
  - Installation of ducts.
  - Backfilling works.
  - Piling works.

- Diddington Lane Embankment worksite: ref.: DLE (see Plan 7 in Appendix A), works activities included:
  - Topsoil stripping.
  - Excavation works.
  - Filling piling platform.
- Blythe Bypass Embankment worksite, reference - BBE (see plan 1 in Appendix A), where work activities included:
  - Stone backfilling.
- A452 worksite, reference - A452 (see plan 2 in Appendix A), where work activities included:
  - Excavation works.
  - Plant movement.
  - Piling works.
- Park Lane worksite, reference - PL (see plan 3 in Appendix A), where work activities included:
  - Materials haulage and laydown.
  - Topsoiling of stone bund.
  - Plant movement.
  - Vegetation clearance.
- Balsall Common Viaduct worksite, reference - BCV (see plan 4 in Appendix A), where work activities included:
  - Excavation works.
  - Plant movement.
- Carol Green Rail Underbridge worksite, reference - CGRU (see plan 4 in Appendix A), where work activities included:
  - Material loading onto conveyer belt.

- Waste Lane Overbridge and Satellite worksite, reference WLOS (see plan 5 in Appendix A), where work activities included:
  - Diaphragm wall installation.
  - Piling works.
  - Road sweeping.

1.1.4 Further works were also undertaken as part of the utilities diversion between Meriden road & Diddington Lane.

1.1.5 Applicable standards, guidance, and monitoring methodology are outlined in the construction noise and vibration monitoring methodology report which can be found at the following location <https://www.gov.uk/government/collections/monitoring-the-environmental-effects-of-hs2>. Noise and vibration monitoring reports for previous months can also be found at this location.

## 1.2 Measurement Locations

1.2.1 Seventeen (17) noise and five (5) vibration monitoring installations were active in November in the SMBC area. Table 2 summarises the position of noise and vibration monitoring installations within the SMBC area in November 2022.

1.2.2 Noise monitor, ref.: DLE-N2, was installed at worksite ref.: DLE on Thursday 22<sup>nd</sup> November 2022.

1.2.3 Noise levels were not measured in November 2022 at ref: CHRU-N1-V1 due to loss of power to the battery caused by the theft of solar panels.

1.2.4 Maps showing the position of noise monitoring installations are presented in Appendix B.

Table 2: Monitoring Locations

Worksite Reference	Measurement Reference	Address
Coleshill Heath Road (CHR)	CHR-N1	Coleshill Heath Road, Coleshill Heath, Solihull
	CHRU-N1	276 Yorkminster Drive, Birmingham
	CHRU-V1	276 Yorkminster Drive, Birmingham
Pakington Embankment (PE)	PE-N1	Common Farm, Chester Road, Coleshill, Birmingham

Worksite Reference	Measurement Reference	Address
Bickenhill Cutting (BIC)	BIC-N1	Park Farm Barns, Chester Rd, Marston Green, Coventry
Diddington Lane Embankment (DLE)	DLE-N1	Hampton Hill Hounds, Nursery Cottage, Coventry Road, Bickenhill
	DLE-N2	Diddington Ln, Hampton in Arden
Blythe Bypass Embankment (BBE)	BBE-1	Patrick Farm House, Meriden Road, Hampton in Arden
A452 compound	A452-N1	Marsh House Farm, Brandocks Marsh, Solihull
	A452-V1	Final Home, Park Lane, Balsall Common
Park Lane	PL-1	Park Lane, Balsall Common, Solihull
	PL-2	The Laurel, Lavender Hall Lane, Balsall Common, Solihull
	PL-3	Holly Acre Lodge, Kenilworth Road, Solihull
	PL-V1	(east of) Final Home, Park Lane, Balsall Common, Coventry, West Midlands
Balsall Common Viaduct	BCV-1	Cherry Tree Cottage, Truggist Lane, Balsall Common, Solihull
Carol Green Rail Underbridge	CGRU-1	The Stables, Truggist Lane, Balsall Common, Solihull
	CGRU-2	Berkswell-House, Truggist Lane, Balsall Common, Solihull
Waste Lane Overbridge and Satellite	WLOS-1	19 Hodgetts Lane, Burton Green, Warwickshire
	WLOS-2	Little Beanitt Farm, Waste Lane, Balsall Common, Solihull
	WLOS-3	Dragonflies, Waste Lane, Balsall Common, Solihull
	WLOS-V1	19 Hodgetts Lane, Burton Green, Warwickshire
	WLOS-V2	Little Beanitt Farm, Waste Lane, Balsall Common, Solihull

## 2 Summary of Results

### 2.1 Summary of Measured Noise Levels

2.1.1 Table 3 presents a summary of the measured noise levels at each monitoring location over the reporting period. The  $L_{Aeq,T}$  is presented for each of the relevant time periods averaged over the calendar month, along with the highest single period  $L_{Aeq,T}$  that was found to occur within the month.

Table 3: Summary of Measured dB LAeq Data over the Monitoring Period

Worksite Reference	Measurement Reference	Site Address	Free-field or Façade Measurement	Weekday Average LAeq,T (highest day LAeq,T)					Saturday Average LAeq,T (highest day LAeq,T)					Sunday / Public Holiday Average LAeq,T (highest day LAeq,T)	
				0700 - 0800	0800 - 1800	1800 - 1900	1900 - 2200	2200 - 0700	0700 - 0800	0800 - 1300	1300 - 1400	1400 - 2200	2200 - 0700	0700 - 2200	2200 - 0700
CHR	CHR-N1	Coleshill Heath Road, Coleshill Heath, Solihull	Free-field	65.5 (67.7)	64.8 (66.4)	63.5 (65.4)	60.3 (66.3)	59.0 (67.0)	61.6 (62.6)	63.5 (63.8)	63.7 (64.3)	63.3 (67.7)	57.3 (61.8)	63.0 (68.5)	59.0 (65.8)
PE	PE-N1	Common Farm, Chester Road, Coleshill	Free-field	59.6 (63.2)	60.0 (63.3)	58.4 (62.7)	57.3 (61.2)	56.1 (63.1)	56.8 (58.7)	58.8 (62.1)	57.1 (60.2)	57.7 (60.1)	52.5 (56.4)	56.4 (59.9)	53.5 (60.8)
BIC	BIC-N1	Park Farm Barns, Chester Rd, Marston Green	Free-field	59.3 (62.4)	58.2 (60.2)	57.2 (59.5)	55.9 (60.0)	54.2 (62.0)	55.8 (58.1)	56.7 (58.2)	55.6 (58.5)	57.2 (59.3)	52.3 (56.1)	56.3 (59.1)	53.2 (59.8)
DLE	DLE-N1	Hampton Hill Hounds, Nursery Cottage, Coventry Road	Free-field	55.6 (64.8)	54.3 (59.8)	53.2 (62.5)	51.8 (60.1)	49.5 (59.6)	52.0 (54.2)	52.3 (54.6)	51.8 (56.5)	52.0 (60.1)	46.2 (53.4)	52.3 (56.1)	48.2 (55.3)
	DLE-N2	Diddington Ln, Hampton in Arden, Solihull B92 0BZ	Free-field	52.1 (55.6)	56.1 (57.1)	48.5 (54.0)	46.5 (52.7)	44.0 (54.6)	51.1 (51.1)	51.4 (51.4)	50.0 (50.0)	48.3 (50.3)	44.9 (51.0)	49.7 (51.9)	45.9 (51.6)

Worksite Reference	Measurement Reference	Site Address	Free-field or Façade Measurement	Weekday Average LAeq,T (highest day LAeq,T)					Saturday Average LAeq,T (highest day LAeq,T)					Sunday / Public Holiday Average LAeq,T (highest day LAeq,T)	
				0700 - 0800	0800 - 1800	1800 - 1900	1900 - 2200	2200 - 0700	0700 - 0800	0800 - 1300	1300 - 1400	1400 - 2200	2200 - 0700	0700 - 2200	2200 - 0700
Blythe Bypass Embankment	BBE-1	Patrick Farm House	Free-field	56.4 (58.0)	56.3 (59.5)	54.7 (57.0)	52.2 (54.4)	48.9 (56.6)	52.8 (53.6)	54.3 (55.7)	54.1 (55.0)	53.6 (59.9)	46.4 (52.0)	53.4 (56.2)	48.3 (55.0)
A452 Compound	A452-N1	Marsh House Farm	Free-field	55.0 (58.5)	58.6 (68.1)	52.1 (55.8)	49.9 (53.8)	47.0 (55.5)	52.7 (57.9)	54.8 (58.3)	50.7 (53.5)	52.5 (62.7)	45.0 (51.0)	51.2 (54.9)	46.4 (53.7)
Park Lane	PL-1	Park Lane	Free-field	55.7 (60.0)	63.5 (77.0)	51.0 (55.3)	49.4 (59.3)	46.1 (54.6)	51.4 (53.1)	55.1 (58.7)	49.8 (53.1)	51.1 (57.2)	44.5 (52.4)	49.8 (53.6)	44.7 (52.4)
	PL-2	The Laurel	Free-field	49.8 (51.7)	52.5 (61.1)	48.7 (54.9)	47.6 (53.2)	42.7 (52.4)	47.7 (50.1)	49.5 (50.7)	49.6 (54.2)	49.5 (57.6)	41.9 (50.3)	48.5 (51.8)	41.4 (48.1)
	PL-3	Holly Acre Lodge	Free-field	58.8 (61.2)	58.6 (68.0)	56.7 (59.8)	53.2 (56.8)	50.6 (71.4)	54.0 (55.2)	56.7 (58.8)	56.0 (58.6)	55.9 (59.1)	48.0 (52.9)	55.0 (58.2)	51.6 (66.4)
Balsall Common Viaduct	BCV-1	Cherry Tree Cottage	Free-field	51.6 (53.0)	59.3 (65.2)	50.8 (54.6)	49.8 (56.1)	47.0 (53.2)	48.2 (49.1)	52.1 (59.4)	48.8 (50.7)	50.4 (58.5)	42.3 (48.6)	51.5 (59.6)	46.7 (51.0)

Worksite Reference	Measurement Reference	Site Address	Free-field or Façade Measurement	Weekday Average LAeq,T (highest day LAeq,T)					Saturday Average LAeq,T (highest day LAeq,T)					Sunday / Public Holiday Average LAeq,T (highest day LAeq,T)	
				0700 - 0800	0800 - 1800	1800 - 1900	1900 - 2200	2200 - 0700	0700 - 0800	0800 - 1300	1300 - 1400	1400 - 2200	2200 - 0700	0700 - 2200	2200 - 0700
Carol Green Rail Underbridge	CGRU-1	The Stables	Free-field	51.1 (54.2)	68.7 (73.9)	49.8 (53.7)	48.9 (57.4)	47.2 (55.6)	46.8 (48.3)	52.7 (62.8)	47.8 (49.1)	48.6 (55.9)	47.6 (55.6)	50.1 (57.4)	47.1 (54.0)
	CGRU-2	Berkswell-House	Free-field	54.3 (57.0)	60.3 (63.6)	54.0 (56.0)	53.2 (58.8)	51.3 (57.7)	49.7 (52.3)	57.3 (61.0)	51.8 (54.4)	52.4 (57.7)	46.6 (54.6)	55.4 (58.0)	52.0 (56.5)
Waste Lane Overbridge and Satellite WP062	WLOS-1	19 Hodgetts Lane	Façade	47.7 (52.0)	62.1 (67.5)	50.5 (64.6)	45.5 (57.7)	40.4 (53.1)	46.2 (48.1)	60.2 (65.6)	43.0 (44.5)	46.3 (63.8)	37.4 (46.8)	43.2 (50.2)	37.6 (44.8)
	WLOS-2	Waste Lane (East)	Free field	49.6 (53.8)	53.1 (72.6)	47.5 (53.0)	45.0 (52.4)	41.5 (54.3)	46.0 (46.4)	50.5 (51.8)	47.7 (48.4)	47.0 (50.8)	41.1 (49.5)	47.5 (57.5)	40.3 (48.0)
	WLOS-3	Waste Lane (West)	Free field	60.0 (64.2)	60.2 (63.0)	57.4 (60.8)	52.9 (60.4)	48.0 (59.8)	55.1 (55.6)	59.6 (60.5)	59.1 (60.4)	57.6 (59.7)	49.1 (55.0)	57.3 (62.1)	49.2 (56.6)

2.1.2 Table 4 presents a summary of the measured vibration levels at the monitoring location over the reporting period. The highest PPV measured during the monitoring along any axis is presented in the table.

Table 4: Summary of Measured PPV Data over the Monitoring Period

Worksite Reference	Measurement Reference	Monitor Address	Highest PPV measured in any axis, mm/s
A452 compound	A542-V1	Final Home, Park Lane, Balsall Common	2.69 (X-axis)
PL	PL-V1	(east of) Final Home, Park Lane, Balsall Common, Coventry, West Midlands	25.05 (X-axis)
WLOS	WLOS-V1	19 Hodgetts Lane, Burton Green, Warwickshire, CV8 1PH	6.03 (X-axis)
	WLOS-V2	Little Beanitt Farm, Waste Lane, Berkswell, Balsall Common, Solihull, CV7 7GH	8.96 (X-axis)

2.1.3 Appendix C presents graphs of the noise and vibration monitoring data over the month for each of the measurement locations. Noise data presented consists of the hourly  $L_{Aeq}$  values and, where relevant, the  $L_{Aeq,T}$  values (where the time period T has been taken to be the averaging period as specified in Table 1 of HS2 Information Paper E23). Vibration data presented consist of hourly PPV values. The full data set for the monitoring equipment can be found at the following location:

<https://data.gov.uk/dataset/24542ae7-dd44-444f-b259-871c4cc43b5e/environmental-monitoring-data>.

## 2.2 Exceedances of the LOAEL and SOAEL

2.2.1 The lowest observed adverse effect level (LOAEL) is defined in the Planning Practice Guidance – Noise (PPG) as the level above which "noise starts to cause small changes in behaviour and/or attitude, e.g. turning up volume of television; speaking more loudly; where there is no alternative ventilation, having to close windows for some of the time because of the noise. Potential for some reported sleep disturbance. Affects the acoustic character of the area such that there is a perceived change in the quality of life".

2.2.2 The significant observed adverse effect level (SOAEL) is defined in the 'Planning Practice Guidance – Noise' as the level above which "noise causes a material change in behaviour and/or attitude, e.g. avoiding certain activities during periods of intrusion; where there is no alternative ventilation, having to keep windows closed

most of the time because of the noise. Potential for sleep disturbance resulting in difficulty in getting to sleep, premature awakening and difficulty in getting back to sleep. Quality of life diminished due to change in acoustic character of the area."

2.2.3 HS2 Phase One Information Paper E23: Control of Construction Noise and Vibration sets out the LOAELs and SOAELs for construction noise.

2.2.4 Where reported construction noise levels exceed the LOAEL and SOAEL, relevant periods will be identified. Summary statistics to evaluate ongoing qualification for noise insulation and temporary rehousing are also presented where relevant.

2.2.5 Table 5 presents a summary of recorded exceedances of the LOAEL and SOAEL at each measurement location over the reporting period, including the number of exceedances during each time period.

Table 5: Summary of Exceedances of LOAEL and SOAEL

Worksite Reference	Measurement Reference	Site Address	Day (Weekday, Saturday, Sunday, Night)	Time period	Number of exceedances of LOAEL	Number of exceedances of SOAEL
Coleshill Heath Road (CHR)	CHR-N1	Coleshill Heath Road	All Days	All Periods	No exceedance	No exceedance
Pakington Embankment (PE)	PE-N1	Common Farm	All Days	All Periods	No exceedance	No exceedance
Bickenhill Cutting (BIC)	BIC-N1	Park Farm Barns	All Days	All Periods	No exceedance	No exceedance
Diddington Lane Embankment (DLE)	DLE-N1	Hampton Hill Hounds	All Days	All Periods	No exceedance	No exceedance
	DLE-N2	Diddington Ln, Hampton in Arden	Weekday	0800-1800	1	No exceedance
Blythe Bypass Embankment	BBE-1*	Patrick Farm House	All Days	All Periods	No exceedance	No exceedance
A452 Compound	A452-N1	Marsh House Farm	Weekday	0800-1800	1	No exceedance
Park Lane	PL-1*	Park Lane	Weekday	0800-1800	5	No exceedance
	PL-2*	The Laurel	All Days	All Periods	No exceedance	No exceedance
	PL-3*	Holly Acre Lodge	Weekday	0800-1800	1	No exceedance

Worksite Reference	Measurement Reference	Site Address	Day (Weekday, Saturday, Sunday, Night)	Time period	Number of exceedances of LOAEL	Number of exceedances of SOAEL
Balsall Common Viaduct	BCV-1*	Cherry Tree Cottage	All Days	All Periods	No exceedance	No exceedance
Carol Green Rail Underbridge	CGRU-1*	The Stables	All Days	All Periods	No exceedance	No exceedance
	CGRU-2*	Berkswell-House	All Days	All Periods	No exceedance	No exceedance
Waste Lane Overbridge and Satellite	WLOS-1*	19 Hodgetts Lane	All Days	All Periods	No exceedance	No exceedance
	WLOS-2	Waste Lane (East)	Weekday	0800-1800	1	1
	WLOS-3*	Waste Lane (West)	All Days	All Periods	No exceedance	No exceedance

\*A distance correction has been applied when calculating exceedances of the LOAEL and SOAEL.

2.2.6 Nine (9) exceedances of the LOAEL were recorded during weekday core working hours at the monitoring locations ref.: DLE-N2, A452-N1, PL-1, PL-3 and ref.: WLOS-2 during November 2022.

2.2.7 For the purpose of assessing eligibility for noise insulation or temporary rehousing, multiple exceedances of the SOAEL in a 24-hour period would be counted as a single exceedance during that day. Over the reporting period, the overall number of SOAEL exceedances at each measurement location is shown in Table 6 and may be lower than the total sum of individual exceedances reported in Table 5 for each location.

Table 6: Summary of Total Exceedances of SOAEL

Worksite Reference	Measurement Reference	Monitor Address	Total of SOAEL exceedances in the month
WLOS	WLOS-2	Waste Lane (East)	1

2.2.8 One (1) 24-hour periods that experienced an exceedance of the SOAEL was/were recorded due to HS2 construction works during November 2022.

## 2.3 Exceedances of Trigger Level

2.3.1 Table 7 provides a summary of exceedances of the S61 trigger noise levels determined to be due to HS2 related construction noise measured during the reporting period, along with the findings of any investigation.

Table 7: Summary of Exceedances of Trigger Levels

Complaint Reference Number (if applicable)	Worksite Reference	Date and Time Period	Identified Source	Results of Investigation (including noise monitoring results)	Actions Taken
-	-	-	-	-	-

## 2.4 Complaints


2.4.1 Table 8 provides a summary of complaint information related to noise and vibration received during the reporting period, along with the findings of any investigation.

Table 8: Summary of Complaints


Complaint Reference Number	Worksite Reference	Description of Complaint	Results of Investigation	Actions Taken
-	-	-	-	-

# Appendix A Site Locations

# Worksite Identification Plan - Overview




# Worksite Identification Plan - 1




**Legend**

- Active Worksites

# Worksite Identification Plan - 2



# Worksite Identification Plan - 3




# Worksite Identification Plan - 4




OFFICIAL

# Worksite Identification Plan - 5




OFFICIAL

# Worksite Identification Plan - 6



OFFICIAL

# Worksite Identification Plan - 7



OFFICIAL


# Worksite Identification Plan - 8



OFFICIAL


# Appendix B Monitoring Locations

# Noise and Vibration Monitoring Plan - 1




OFFICIAL

# Noise and Vibration Monitoring Plan - 2




# Noise and Vibration Monitoring Plan - 3



OFFICIAL

# Noise and Vibration Monitoring Plan - 4




# Noise and Vibration Monitoring Plan - 5



OFFICIAL

# Noise and Vibration Monitoring Plan - 6



OFFICIAL

# Noise and Vibration Monitoring Plan - 7



# Noise and Vibration Monitoring Plan - 8



OFFICIAL

# Noise and Vibration Monitoring Plan - 9




OFFICIAL



# Appendix C Data

## Noise




The following graphs show the hourly measured ambient noise level  $L_{Aeq,1h}$  and, where relevant, the averaged noise level  $L_{Aeq,T}$  values, where the time period T is as specified in Table 1 of HS2 Information Paper E23. Periods with adversely weather affected noise levels are greyed out and have been excluded from the calculation of the  $L_{Aeq,T}$  values in Table 3 of the main report.

### Worksite: CHR - Monitoring Ref: CHR-N1







## Worksite: PE - Monitoring Ref: PE-N1







OFFICIAL




**Worksite: BIC - Monitoring Ref: BIC-N1**










**Worksite: DLE - Monitoring Ref: DLE-N1**









## Worksite: DLE - Monitoring Ref: DLE-N2





Note: Monitor installed at 12:00 on Thursday 22<sup>nd</sup> November 2022.




## Worksite: BBE – Monitoring Ref: BBE-1







OFFICIAL





**Worksite: A452 Compound - Monitoring Ref: A452-N1**













**Worksite: PL - Monitoring Ref: PL-1**








## Worksite: PL – Monitoring Ref: PL-2







OFFICIAL





### Worksite: PL - Monitoring Ref: PL-3














### Worksite: BCV – Monitoring Ref: BCV-1









## Worksite: CGRU- Monitoring Ref: CGRU-1






**Worksite: CGRU- Monitoring Ref: CGRU-2**











### Worksite: WLOS - Monitoring Ref: WLOS-1






## Worksite: WLOS - Monitoring Ref: WLOS-2





## Worksite: WLOS – Monitoring Ref: WLOS-3




Note: Missing data throughout the week was due to loss of power supply to the monitor.



Note: Missing data from 00:00 on Monday 7<sup>th</sup> November till 11:00 on Wednesday 9<sup>th</sup> November was due to loss of power supply to the monitor.



Note: Missing data throughout the week was due to loss of power supply to the monitor.





Note: Missing data throughout the week was due to loss of power supply to the monitor.

OFFICIAL

## Vibration


The following graphs show the hourly measured peak particle velocity PPV recorded during the monitoring period. The graphs show the highest PPV of the three orthogonal axes x, y and z. Where high values of PPV were caused by local interference with the vibration monitor, which are not representative of HS2 construction works, these values have been greyed out in the following charts and have been excluded to calculate values in Table 4 of the main report.

### Worksite: A452 compound – Monitoring Ref: A452-V1




Note: Missing data from 12:00 on Saturday 12<sup>th</sup> November till the end of the month was due to loss of power to the monitor.


## Worksite: PL – Monitoring Ref: PL-V1





Note: High vibration levels measured at 09:00 on Wednesday 2<sup>nd</sup> November was due to topsoiling and hydroseeding works undertaken in vicinity of the monitor.





Note: High vibration levels measured between 12:00 to 14:00 on Friday 11<sup>th</sup> November was due to topsoiling and hydroseeding works undertaken in vicinity of the monitor.




Note: High vibration levels measured at 09:00 on Monday 14<sup>th</sup> November was due to topsoiling and hydroseeding works undertaken in vicinity of the monitor.




## Worksite: WLOS – Monitoring Ref: WLOS-V1




Note: High vibration levels measured at 12:00 on Wednesday 9<sup>th</sup> November was due to ground works undertaken in vicinity of the monitor.





Note: High vibration levels measured at 10:00 on Wednesday 16<sup>th</sup> November was due to ground works undertaken in vicinity of the monitor.




Note: High vibration levels measured at 09:00 on Tuesday 9<sup>th</sup> November was due to ground works undertaken in vicinity of the monitor.



### Worksite: WLOS - Monitoring Ref: WLOS-V2





Note: High vibration levels measured at 08:00 on Tuesday 15<sup>th</sup> November was due mobilising piling works in vicinity of the monitor.

