

**PROLONGATION – LIST OF DUTY SUSPENSIONS EXPIRING 31  
DECEMBER 2011**

<u>CN code</u>	<u>Goods</u>	<u>Automatically prolonged?</u>
ex 0711 59 00 11	Mushrooms, excluding mushrooms of the genera <i>Agaricus</i> , <i>Calocybe</i> , <i>Clitocybe</i> , <i>Lepista</i> , <i>Leucoagaricus</i> , <i>Leucopaxillus</i> , <i>Lyophyllum</i> and <i>Tricholoma</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry(1)	<b>YES</b>
ex 1517 90 99 10	Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % arachidonic acid or 35 % or more but not more than 50 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO)	<b>YES</b>
ex 2009 80 79 87	Frozen boysenberry juice concentrate with a Brix value of 61 or more, but not more than 65	
ex 2009 80 99 93	Untreated frozen coconut water, not put up for retail sale	<b>YES</b>
ex 2811 22 00 20	Microspheres of amorphous silicon of a particle size of 5 µm (± 1 µm), for use in the manufacture of cosmetic products(1)	
ex 2811 22 00 30	Balls of porous white silica of a particle size of more than 1 µm for use in the manufacture of cosmetic products(1)	<b>YES</b>
2819 10 00	Chromium trioxide	<b>YES</b>
ex 2827 39 85 20	Antimony pentachloride of a purity by weight of 99 % or more	
ex 2837 20 00 10	Tetrasodium hexacyanoferrate (II)	<b>YES</b>
ex 2843 29 00 10	Silver oxide, nitrate- and carbonate-free, with a silver content of at least 99.99 % by weight of the metal content, for the manufacture of silver oxide batteries(1)	<b>YES</b>
ex 2845 90 90 10	Helium-3	<b>YES</b>
ex 2845 90 90 30	Carbon monoxide <sup>13</sup> C	
ex 2903 39 90 70	1,1,1,2 Tetrafluoroethane, certified odourless containing a maximum : — 600 ppm by weight of 1,1,2,2-Tetrafluoroethane, — 2 ppm by weight of pentafluoroethane, — 2 ppm by weight of chlorodifluoromethane, — 2 ppm by weight of	<b>YES</b>

	chloropentafluoroethane, — 2 ppm by weight of dichlorodifluoromethane For use in the manufacture of pharmaceutical grade propellant for medical metred dose inhalers(1)	
ex 2903 39 90 80	Hexafluoropropene	<b>YES</b>
ex 2903 59 80 30	Octafluorocyclopentene	<b>YES</b>
ex 2909 19 90 50	3-Ethoxy-perfluoro-2-methylhexane	<b>YES</b>
ex 2912 49 00 20	4-Hydroxybenzaldehyde	
ex 2916 39 00 45	2-Chlorobenzoic acid	<b>YES</b>
ex 2918 29 00 30	Octadecyl-3-(3,5-di- <i>tert</i> -butyl-4- hydroxyphenyl)propionate	<b>YES</b>
2920 90 40	Triethyl phosphite	<b>YES</b>
ex 2921 51 19 40	<i>p</i> -Phenylenediamine	<b>YES</b>
ex 2922 19 85 70	D-(-)-threo-2-amino-1-( <i>p</i> - nitrophenyl)propane-1,3-diol	<b>YES</b>
ex 2922 29 00 35	2-Amino-4,6-dinitrophenol sodium salt, containing at least 20 % water	
ex 2922 39 00 70	<i>p</i> -[(2- Chloroethyl)ethylamino]benzaldehyde	<b>YES</b>
ex 2923 90 00 35	Tetrabutylammonium fluoride trihydrate	
ex 2924 19 00 60	<i>N,N</i> -Dimethylacrylamide	<b>YES</b>
ex 2926 90 95 55	Methyl-2-cyano-2-phenylbutyrate	
ex 2926 90 95 61	<i>m</i> -(1-Cyanoethyl)benzoic acid	<b>YES</b>
ex 2928 00 90 15	1,1'-(Hydroxyimino)bis-(2-propanol)	
ex 2929 10 00 80	1,3-Bis(isocyanatomethyl)benzene	<b>YES</b>
ex 2930 90 99 30	Glutathione	<b>YES</b>
ex 2930 90 99 78	4-Mercaptomethyl-3,6-dithia-1,8- octanedithiol	<b>YES</b>
ex 2930 90 99 89	Potassium- or sodium-salt of O-ethyl-, O- isopropyl-, O-butyl-, O-isobutyl- or O- pentyl-dithiocarbonates	<b>YES</b>
ex 2931 00 99 91	Trimethylsilane	<b>YES</b>
ex 2932 29 85 60	6'-(Dibutylamino)-3'-methyl-2'- (phenylamino)-spiro[isobenzofuran- 1(3 <i>H</i> ),9'-[9 <i>H</i> ]xanthen]-3-one	<b>YES</b>
ex 2932 29 85 71	6'-(Diethylamino)-3'-methyl-2'- (phenylamino)-spiro[isobenzofuran- 1(3 <i>H</i> ),9'-[9 <i>H</i> ]xanthen]-3-one	<b>YES</b>
ex 2932 29 85 72	2'-[Bis(phenylmethyl)amino]-6'- (diethylamino)-spiro[isobenzofuran- 1(3 <i>H</i> ),9'-[9 <i>H</i> ]xanthen]-3-one	<b>YES</b>
ex 2932 99 00 70	1,3:2,4- <i>bis</i> -O-Benzylidene- <i>D</i> -glucitol	<b>YES</b>
ex 2932 99 00 75	3-(3,4-Methylenedioxyphenyl)-2- methylpropanal	<b>YES</b>
ex 2932 99 00 80	1,3:2,4- <i>bis</i> -O-(4-Methylbenzylidene)- <i>D</i> - glucitol	<b>YES</b>
ex 2933 21 00 50	1-Bromo-3-chloro-5,5-dimethylhydantoin	<b>YES</b>

ex 2933 21 00 60	DL- <i>p</i> -Hydroxyphenylhydantoin	<b>YES</b>
ex 2933 21 00 70	$\alpha$ -(4-Methoxybenzoyl)- $\alpha$ -(1-benzyl-5-ethoxy-3-hydantoinyl)-2-chloro-5-dodecyloxycarbonylacetanilide	<b>YES</b>
ex 2933 39 99 50	<i>N</i> -Fluoro-2,6-dichloropyridinium tetrafluoroborate	
ex 2933 52 00 10	Malonylurea (barbituric acid)	<b>YES</b>
ex 2933 59 95 35	4-Amino-2,6-dichloropyrimidine	
ex 2933 99 80 69	[(3 <i>R</i> )-4-(4-chlorobenzyl)-7-fluoro-5-(methylsulphonyl)-1,2,3,4-tetrahydrocyclopenta[ <i>b</i> ]indole-3-yl]acetic acid	
ex 2933 99 80 81	1,2,3-Benzotriazole	<b>YES</b>
ex 2934 99 90 75	(4 <i>R-cis</i> )-1,1-Dimethylethyl-6-[2[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1 <i>H</i> -pyrrol-1-yl]ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate	<b>YES</b>
ex 2934 99 90 76 ex 3204 20 00 10	2,5-Thiophenediylbis(5- <i>tert</i> -butyl-1,3-benzoxazole)	<b>YES</b>
ex 2934 99 90 77	Potassium 5-methyl-1,3,4-oxadiazole-2-carboxylate	<b>YES</b>
ex 2935 00 90 76	4-Toluenesulphonyl urea	
ex 2935 00 90 89	3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)- <i>N,N</i> -dimethyl-1,2,4-triazol-1-sulphonamide	<b>YES</b>
ex 3204 13 00 10	C.I. Basic Red 1 dye	<b>YES</b>
ex 3208 20 10 40	Poly(1 <i>H</i> ,1 <i>H</i> -heptafluorobutyl methacrylate) dissolved in a mixture of methyl perfluorobutyl ether and methyl perfluoroisobutyl ether	
ex 3208 90 19 60	Copolymer of hydroxystyrene with one or more of the following: — styrene — alkoxy styrene — alkylacrylates dissolved in ethyl lactate	<b>YES</b>
ex 3707 10 00 35 ex 3707 90 90 70	Sensitising emulsion or preparation containing one or more of: — acrylate polymers, — methacrylate polymers, — derivatives of styrene polymers, containing by weight not more than 7 % of photosensitive acid precursors, dissolved in an organic solvent containing at least 2-methoxy-1-methylethyl acetate	<b>YES</b>

ex 3707 10 00 40	Sensitising emulsion, containing: — not more than 10 % by weight of naphthoquinonediazide esters, — 2 % or more but not more than 20 % by weight of copolymers of hydroxystyrene — not more than 7 % by weight of epoxy-containing derivatives dissolved in 1-ethoxy-2-propyl acetate and/or ethyl lactate	<b>YES</b>
ex 3811 90 00 20	Corrosion inhibitor, containing reaction products of fatty acids and tall oil with formaldehyde and (Z)-N-9-octadecenyl-1,3-propanediamine	
ex 3815 90 90 71	Catalyst, containing N-(2-hydroxypropylammonium)diazabicyclo (2,2,2) octane-2-ethyl hexanoate, dissolved in ethane-1,2-diol	<b>YES</b>
ex 3815 90 90 89	Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a polyacrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile(1)	<b>YES</b>
ex 3824 90 97 13	Preparations containing not less than 92 % but not more than 96.5 % by weight of 1,3:2,4-bis-O-(4-methylbenzylidene)-D-glucitol and also containing carboxylic acid derivatives and an alkyl sulphate	<b>YES</b>
ex 3824 90 97 14	Calcium phosphonate phenate, dissolved in mineral oil	<b>YES</b>
ex 3824 90 97 18	4-Methylmandelic acid, crude	
ex 3824 90 97 22	Preparations containing not less than 47 % by weight of 1,3:2,4-bis-O-benzylidene-D-glucitol	
ex 3902 90 90 93	Synthetic poly-alpha-olefin having a viscosity of at least $38 \times 10^{-6} \text{m}^2 \text{s}^{-1}$ (38 centistokes) at 100°C measured using the ASTM D 445 method	<b>YES</b>
ex 3902 90 90 98	Synthetic poly-alpha-olefin with a viscosity at 100° Celsius (measured according to method ASTM D 445) ranging from 3 centistokes to 9 centistokes and obtained by polymerization of a mixture of dodecene and tetradecene, containing a maximum of 40 % of tetradecene	<b>YES</b>
ex 3903 19 00 30	Crystalline polystyrene with a melting point of 268 °C or more but not more than 272 °C and a setting point of 232 °C	<b>YES</b>

	or more but not more than 242 °C, whether or not containing additives and filling material	
ex 3907 99 90 50	Semi-crystalline polycyclohexylenedimethylene terephthalate polymer resin, containing by weight 10 % or more but not more than 40 % of glass fibre, in the form of granules or pellets	
ex 3910 00 00 40	Biocompatible silicones for the manufacture of long term surgical implants(1)	<b>YES</b>
ex 3911 90 99 86	Copolymer of methyl vinyl ether and maleic acid anhydride	<b>YES</b>
ex 3913 90 00 94	Granules containing by weight: — 35 % or more but less than 75 % of a high amylose extruded biopolymer produced from corn starch, — 5 % or more but less than 16 % polyvinyl alcohol, — 10 % or more but less than 46 % of polyol plasticisers, — 0.25 % or more but less than 3 % of stearic acid, — whether or not containing 30 % ( $\pm$ 10 %) of biodegradable polyester resin but never to a level that exceeds the amount of the high amylose biopolymer	<b>YES</b>
ex 3913 90 00 96	Powder consisting of 90 % ( $\pm$ 5 %) by weight of a high amylose extruded biopolymer produced from corn starch, 10 % ( $\pm$ 5 %) by weight of a synthetic polymer and 0.5 % ( $\pm$ 0.25 %) of stearic acid	<b>YES</b>
ex 3919 10 80 30	Double-sided, self-adhesive modified epoxy resin foil, put up in rolls, 10 to 20 cm wide, 10 to 210 m long and with a total thickness of 10 to 50 $\mu$ m, not for retail sale	<b>YES</b>
ex 3919 10 80 40 ex 3919 90 00 43	Black poly(vinyl chloride) film: — with a gloss of more than 30 degrees according to ASTM D2457, — whether or not covered on one side with a protective poly(ethylene terephthalate) film, and on the other side with a pressure sensitive adhesive with channels and a release liner	<b>YES</b>

ex 3920 10 89 40	Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0.8 mm or more but not more than 1.2 mm	<b>YES</b>
ex 3920 59 90 10	Non-cellular and non-laminated sheet of modified copolymer of acrylonitrile-methyl acrylate with a thickness of 1.0 mm or more but not more than 1.3 mm, put up in rolls	<b>YES</b>
ex 3920 62 19 14 ex 3920 62 19 16	Poly(ethylene terephthalate) film, of a thickness of 20 µm or more but not more than 150 µm, coated on one side with silicone, for use in the manufacture of window film(1)	
ex 3920 99 28 50	Thermoplastic polyurethane film, of a thickness of 250 µm or more but not more than 350 µm, covered on one side with a removable protective film	<b>YES</b>
ex 5004 00 10 10	Silk yarn (other than yarn spun from silk waste) not put up for retail sale, unbleached, scoured or bleached, entirely of silk	<b>YES</b>
ex 5004 00 90 10	Yarn spun entirely from silk, not put up for retail sale	
ex 5402 47 00 10	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex or more but not more than 1 800 decitex, consisting of 110 filaments or more but not more than 120 filaments, each having a core of poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not more than 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings(1)	<b>YES</b>
ex 5907 00 00 10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter of not more than 150 µm	<b>YES</b>
ex 7019 39 00 50	Non-woven product of non-textile glass fibre, for the manufacture of air filters(1)	<b>YES</b>
ex 7201 10 11 10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm	<b>YES</b>
ex 7201 10 30 10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than	<b>YES</b>

	150 mm, containing by weight not more than 1 % of silicon	
ex 7326 20 80 20	Metal fleece, consisting of a mass of stainless steel wires of diameters ranging from 0.022 mm to 0.070 mm, compacted by sintering and rolling	<b>YES</b>
ex 7607 11 90 10	Plain aluminium foil with the following parameters: — an aluminium content of 99.98 % or more — a thickness of 0.070 mm or more but not more than 0.115 mm — with a cubic texture of a kind used for high voltage etching(1)	<b>YES</b>
ex 8407 90 10 10	Four-stroke petrol engines of a cylinder capacity of not more than 250 cm <sup>3</sup> for use in the manufacture of lawnmowers of sub-heading 8433 11, mowers with motor of subheading 8433 20 10, rotovators of sub-heading 8432 29 50, garden shredders of sub-heading 8436 80 90 or scarifiers of subheading 8432 29 10(1)	<b>YES</b>
ex 8413 91 00 20	Manganese-silicon-bronze swash plates with a copper content of 58 % or more but not more than 63 % by weight for incorporation into fluid pumps for air conditioners of motor vehicles	
ex 8414 90 00 50	Cross-flow fan, of 97.4 mm ( $\pm$ 0.2 mm) diameter and 645 mm ( $\pm$ 1 mm) or 873 mm (+0.5/-1 mm) height made from anti-static, anti-bacterial and heat-resistant, glass fiber reinforced plastic with a minimum temperature resistance of 70°C, for use in the manufacture of indoor air conditioning units(1)	
ex 8415 90 00 20	Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles(1)	<b>YES</b>
ex 8481 80 99 50	Service valve, consisting a combination of a two way valve on the liquid line and a three way valve on the gas line with: — a minimum enclosing pressure of 30 kgf/cm <sup>2</sup> , — a minimum withstanding pressure of 45 kgf/cm <sup>2</sup> , for use in the manufacture of outdoor air conditioning units(1)	<b>YES</b>
ex 8481 80 99 60	Four way valve, consisting of: — a core plunger,	<b>YES</b>

	<ul style="list-style-type: none"> <li>— a sealing plunger,</li> <li>— a 220 V-240 V AC 50/60 Hz solenoid coil,</li> <li>— a working pressure up to 4.3 Mpa,</li> <li>— a housing</li> </ul> for directing the flow of the refrigerant, for use in the manufacture of outdoor air conditioning units(1)	
ex 8501 10 93 20	Single phased 50 Hz, AC motor driven by permanent single capacitor and having a power output of less than 37 W, for use in the manufacture of indoor split air conditioning units(1)	
ex 8501 31 00 30	DC motor, brushless, with a three-phase winding, an external diameter of 85 mm or more, but not more than 115 mm, a nominal torque of 2.23 Nm ( $\pm$ 1.0 Nm), of an output of more than 120 W but not more than 520 W, calculated with 1550 RPM ( $\pm$ 350 RPM) at a supply voltage of 12 V equipped with electronic circuit with sensors using the Hall effect, for use with an electric power steering control module (power steering motor)(1)	<b>YES</b>
ex 8503 00 99 33	Stator for brushless motor of electrical power steering with a roundness tolerance of 50 $\mu$ m	<b>YES</b>
ex 8503 00 99 34	Rotor for brushless motor of electrical power steering with a roundness tolerance of 50 $\mu$ m	<b>YES</b>
ex 8504 90 18 40	Trans coil for boosting DC voltage and isolating high and low voltages for use in the manufacture of products falling within subheading 8504 31 80(1)	
ex 8507 80 30 40	Rectangular lithium-ion-accumulator, with <ul style="list-style-type: none"> <li>— a length of 80 mm or more, but not more than 1000 mm,</li> <li>— a width of 25 mm or more, but not more than 150 mm,</li> <li>— a height of 100 mm or more, but not more than 500 mm,</li> <li>— a weight of 0,5 kg or more, but not more than 30 kg,</li> <li>— a capacity of 20 Ah or more, but not more than 1000 Ah,</li> </ul> for use in the manufacture of rechargeable power-supply units for incorporation into goods of heading No 8903(1)	<b>YES</b>



ex 8522 90 80 81	Laser optical pick up unit for the reproduction of optical signals from CD or DVD and the recording of optical signal on DVD, comprising at least — a laser diode, — a laser driver integrated circuit, — a photo detector integrated circuit, — a front monitor integrated circuit and an actuator, for use in the manufacture of products falling within heading No 8521(1)	<b>YES</b>
ex 8522 90 80 97 ex 8529 90 65 50	Tuner transforming high-frequency signals into mid-frequency signals, for use in the manufacture of products falling under n° 8521 and n° 8528(1)	<b>YES</b>
ex 8525 80 19 40	Assembly for cameras used in computer notebooks of dimensions of not more than 15 x 25 x 25 mm, comprising an image sensor, an objective and a colour processor, having an image resolution of not more than 1600 x 1200 pixel, whether or not fitted with cable and/or housing, whether or not mounted on a base and containing a LED chip(1)	<b>YES</b>
ex 8529 90 65 60	Tuner transforming high frequency signals to mid frequency signals for use in the manufacture of satellite or terrestrial TV receivers for set-top boxes(1)	<b>YES</b>
ex 8529 90 65 70	Unit driver consisting of an electronic integrated circuit and a flexible printed circuit, for use in the manufacture of LCD modules(1)	<b>YES</b>
ex 8539 39 00 20	Cold cathode (CCFL) or External Electrode (EEFL) fluorescent lamps, of a diameter of not more than 5 mm and with a length of more than 120 mm but not more than 1570 mm	<b>YES</b>
ex 8540 11 00 91	Colour cathode-ray tube with a slot mask, equipped with an electron gun and a deflection yoke and with a screen width/height ratio of 4/3 and a diagonal measurement of the screen of not more than 42 cm	
ex 8540 11 00 92	Full square curved screen colour cathode-ray tube, equipped with an electron gun and a deflection yoke and with a screen width/height ratio of 4/3 and a diagonal measurement of the	

	screen of 68 cm ( $\pm 2$ mm)	
ex 8540 11 00 93	Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 79 cm or more	<b>YES</b>
ex 8540 20 80 91	Photomultiplier consisting of a photocathode tube with 9 or 10 diodes, for light of a wavelength of 160 nm or more but not more than 930 nm, of a diameter of not more than 14 mm and a height of not more than 94 mm	<b>YES</b>
ex 8540 91 00 92	Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 69 cm or less	
ex 8708 99 97 20	Metal housing caps for incorporation into balancing-arms or spherical bearings used in the suspension systems for the front wheels of motor vehicles(1)	<b>YES</b>
ex 9001 90 00 70	Polyethylene terephthalate film with a thickness of less than 300 $\mu\text{m}$ according to ASTM D2103, having on one side prisms of acrylic resin with a prism angle of 90° and a prism pitch of 50 $\mu\text{m}$	<b>YES</b>
ex 9107 00 00 20	Mechanical timer for use in the manufacture of no-frost refrigerators(1)	