Document issued without commitment or prejudice

### SHIP OR VESSEL IN SERVICE NAME: FORMER RFA DILIGENCE R06

Dated: August 2020



Picture for illustration only

### Contents

### Section 1

Hull and Structure
Deck Gear
Machinery and Systems
Documentation
Stability and Ballasting

### Section 2

Tank Contents Statement – to be forwarded

### Section 3

Inventory of Potential Hazardous Material on Board – to be forwarded

### Note

Nil equipment is in date for testing. MoD may conduct trials affecting structure without compromising towing or safety.

## General particulars

Date and Place of Build		28 JANUARY 1980, at Oresundsvartet 31 JANUARY 1981
		1 7014440
Date ceased operational	May 2015	
service		
Type of Vessel	Forward Re	pair Ship (FRS)
	Official Num	ber 399182
Summary of condition	Sound for to	wing, not in running condition
Displacements & Weights	Gross Regis	ster – 8048
in Tonnes	Net Registe	r – 2414
	Light Ship (I	nclining Exp. 2014) – 6267
Estimated metal weight	5000Te <sup>1</sup>	<sup>1</sup> Based on ex-RFA FORT GEORGE Light Disp Vs DSA
Estimated metal %	80% <sup>1</sup>	Reported Metal Recovery- Provided without prejudice
Draughts	Max/Min - F	wd 6.964/4.5m, Aft 6.964/4.5m
	(Currently F	wd 6.7m, Aft 6.2m)
Length	Overall – 11	1.49m
Beam	Extreme – 2	0.99m
OA height Mast-head to	43.2m	
keel		
Last programmed Docking	Special Surv	vey Assigned 09 DECEMBER 2014
Repair and refit periods	Last Refit Co	ompleted 10 MARCH 2015

## Hull and Structure

Propellers	NiAL Bronze, dia 4.0 mtrs. Weight of Boss 6120 Kg, Weight of Blade
	1070 Kg (4 bladed KaMeWa)
Shaft & Gland	Shafting: Length 14.9 mtrs, dia 0.436 mtrs, Weight 14600Kg
	Stern Tube Liners: White Metal
	Stern gland : Simplex
Rudder	Rudder: Half Spade Rudder, Weight 9400Kg, Area 12.3 sq Mtrs
	Rudder Pintle: Length 1.1 mtrs, dia 0.36 mtrs, weight 800 Kg
	Rudder Stock: Length 2.943 mtrs, dia 0.36 mtrs, weight 2100Kg
	Liner: SIS5204-15
Stabilisers	Passive Flume tank
Logs	NAVIKNOT 600SD Combined Satellite, EM & Doppler Log System
Sonar	Echosounder – Skipper GDS101
Keels	Port & Starboard bilge keels
Hull valves	Closed
Hull condition	Materially sound at last inspection.
Paint coatings	Hempels Hempaguard X7 Applied NOVEMBER 2014 – Good at last
condition	docking
UW hull:	
Upper hull &	Good
superstructure:	Good
Accommodation	Intact and partially furnished.

## Deck Gear

Anchors	4 in number – Stockless Flipper Delta, Fabricated Steel of rolled steel St. 52-3. Weight 5000Kg
Chain Cable	Ship uses Anchor wires in normal operation— 4 in number (6x36, 32mm dia) 2 x 1500m, 2 x 1125m. Nil in date for test.

	Disposar Ship. 1 of hier Ref 12 DETGET(CE) Suites Summary
Towing	Emergency towing arrangement:
	2 in number 200Te Smit brackets fwd
	1 in number 100Te Smit bracket aft
Bollards/Bits	30 sets double bollards
	11 in number Panama chocks
	5 sets mooring rollers
Cordage	Nil beyond mooring ropes
Davits	2 in number Noreq NPD-11300
Boats	2 in number NOREQ-LBT850C – 80 person capacity each
SOLAS	2 in number Scania diesel engines
	Type DS140.2A
	Variant AO4MV
	8 cylinder, 4 stroke, turbo charged.
	Generator Manufacturer:- NEBB (BBC)
	Type MC 546 C
	Serial No. Port F 3127-2, Stbd F 3127-1
	Each 340A 260 kVA 220kw 3ph

## Machinery and System

Boilers	N/A
Main Engines	Diesel Electric Propulsion.
	5 in number NOHAB 16 cyl F216V-C900, 2650kw, 900 rpm
	1 in number Caterpillar C32, 994kW, 1800 rpm,
	1 in number Caterpillar 3512, 1628kW, 1800 rpm
	4 in number NEBB QGW560 HB8 1100 kw, 885 rpm, 6000V.
	Propulsion motors.
Generators	N/A
Auxiliaries and Pumps	Electrically driven. Fully maintained prior to laid-up status now
	essential equipment turned by hand on weekly basis.
Electrical	Laid up in "Dead" condition. Compartments de-humidified or
	individual cabinets etc protected with desiccant.
Steering Gear	Port and starboard hydraulic rotary vane units.
	Manufacturer: Allweiler AG
	Type: 2ESA210 Screw Spindle, Rotary, Positive Displacement
Hydraulically operated	Passenger/ store lift.
lifts	Manufacturer: Dansk Siemens Aktieselskab, Blegdamsvej 124,
	Kebenhavn 0, Tria 64 64. (Malmo Sweden)
Electronic & Sensors	DP System – Kongsberg Simrad with Tautwire, DPS700 (twin GPS)
	& DGNSS. Systems laid-up and not maintained.
GMDSS	Provided under contract – likely to be removed.
	Primary system: Sailor RT-4722
	MF/HF: Sailor HC-4500
Batteries	Removed
Fire-Fighting	Main systems isolated and disarmed. PPE destored.
Sanitary	Model / Type: Hamworthy Super Trident ST-10
	Serial No.: 47647-05 (US Coast Guard Cert No. 159.015/23 /0)
	Tank flushed and pumped empty

## Documentation

Certification	LRS Class – Expired, out of Class.
Drawings - Main	Onboard – not complete.
Operating Manuals	Onboard – not complete

= ==F =	3 to 1 to	
Historical	Removed	

# Stability, Ballasting and Tank Contents

Tanks, oils and Ballasting Summary	Ballasted in normal sea-going condition With 1909.8 liquids remaining of which the bulk is fresh water ballast (one tank contains treated sea water). Oily residuals remain in some tanks and pipework.
Stability Summary	Ship is stable, a final opinion will be issued by MoD at point of sale – note that ship condition, including stability will then become the sole responsibility of the new owner.