

APPENDIX 1. General Documents (Onshore)

Document Ref.	Document Title	Appendix Page No.
PCCS-00-TC-AA-6627-00001	INTERFACE SCHEDULE	2
PCCS-00-TC-AA-6627-00002	INTERFACE RESPONSIBILITY SPECIFICATION	8
PCCS-00-TC-EA-7770-63001	ELECTRICAL STANDARD GRAPHIC SYMBOLS	32
PCCS-00-TC-IN-0901-00001	PAS / ESD / F&G ARCHITECTURE/ BLOCK DIAGRAM	33
PCCS-00-TC-MP-4024-00001	SITE MASTER PLAN (ONSHORE)	34
PCCS-00-TC-MP-4024-00002	OVERALL PLOT PLAN	35
PCCS-00-TC-PX-2365-00002-	PIPING AND INSTRUMENTATION DIAGRAM PIPING	36
001	LEGEND AND SYMBOLS	
PCCS-00-TC-PX-2365-00003-	PIPING AND INSTRUMENTATION DIAGRAM EQUIPMENT	37
001	LEGEND AND SYMBOLS	
PCCS-00-TC-PX-2365-00004-	PIPING AND INSTRUMENTATION DIAGRAM EQUIPMENT	38
001	TITLE LABELS	
PCCS-00-TC-PX-2365-00005-	PIPING AND INSTRUMENTATION DIAGRAM	39
001	INSTRUMENTATION LEGEND AND SYMBOLS-1	
PCCS-00-TC-PX-2365-00006-	PIPING AND INSTRUMENTATION DIAGRAM	40
001	INSTRUMENTATION LEGEND AND SYMBOLS-2	
PCCS-00-TC-PX-2365-00007-	PIPING AND INSTRUMENTATION DIAGRAM SAMPLE	41
001	CONNECTIONS LEGENDS AND SYMBOLS	
PCCS-00-TC-PX-2365-00008-	PIPING AND INSTRUMENTATION DIAGRAM - KKS	42
001	IDENTIFICATION SYSTEM	
PCCS-00-TC-PX-2366-00001- 001	PROCESS FLOW DIAGRAM LEGEND AND SYMBOLS	43

PETERHEAD CCS (ONSHORE) SHELL U.K. LTD PETERHEAD, SCOTLAND



ENGINEER REFERENCE									R	ev.	Page	
Project	Unit	No	Doc.	Туре	Co	ode	Seria	al No	V	1 of 8		
									K01		1 01 6	
CLIENT REFERENCE					-							
Project Code		Area/Fac	ility Code	Origi	nator	Disc	pline	Doc Type		Sequer	ntial No	
PCCS		0	0	Т	С	Α	Α	66	27	000	001	

INTERFACE SCHEDULE

Rev	Date	STATUS	WRITTEN BY	CHECKED BY	APPROVED BY							
nev.	DD/MM/YY	31/103	(name & sign)	(name & sign)	(name & sign)							
	DOCUMENT REVISIONS											

										K01		CLIENT PROJECT LOCATION		PETERHEA	ELL U.K. LTD AD CCS (ONSHORE) IEAD, SCOTLAND		DOC. NO.: CLIENT REF.: PCCS-00-TC-AA-6627-00001 REV: K01				
L	INE INFORMATION				INTERCONNECTED LII	NES		FLOWRATE L	NE SIZE (mm)	MECHANICAL I OPERATING CONDITIONS	NTERFACE SCHEDU DES COND			INTERFACI	E POINT LOCATION						
TP NO BL NO	TIE-IN NO	SERVICE	ORG X	LINE NO	P&ID ORG Y	LINE NO	P&ID	PHASE DESIGN FLOW EXISTII RATE LINE (kg/h)		PRESS TEMP (barg) (°C)	PRESS (barg)	TEMP (°C)	Easting	Northing	Elevation I	KEY DWG	REFERENCE DWGS/DOCUMENTS	INTERFACE POINT TYPE	TYPE OF CONNECTION	TIE-IN CLASSIFICATION	NOTES
P - 1001 - M	TP - 0001 - M TP - 0002 - M	Fuel Gas Fuel Gas	SSE SSE	13EKG60 BR010 13EKG60 BR010	PS EPC PS EPC	13EKG84 BR001 13EKG84 BR001	PCCS-01-TC-PX-2365-00002-001 PCCS-01-TC-PX-2365-00002-001	V 200 V 200	200 200	30 5 / 15.6 30 5 / 15.6	39 39	250 250	865488	1254531 1258062	9609			3a 3b	BF BW	5 5	
TP - 1003 - M	TP - 0003 - M	Ammonia	SSE	HRSG-13	PS EPC PS EPC	13QCJ17 BR001	PCCS-01-TC-PX-2365-00003-001	- V	200	0.1 95	9	150	896697	1257248	28645			3a	BF	5	Tie-in point to HRSG-13. DP & DT to be confirmed by vendor. No existing line number. Deleted and replaced by TP-2008-C to cover structural interface between 13RLJ10 package (SCR catalyst and
TP - 1005 - M	TP - 0005 - M	Flue Gas	SSE	13HNE10 BR001	CCP EPC	BL001	PCCS-01-TC-PX-2365-00003-001	V -	6100	0.0 / 0.04 100	0.05/-0.015	120	907600	1266300	17650			Note 7	Note 7	6	ammonia injection units) and HRSG structure. CCP Flue gas tie-in. Flue gas duct under CCP scope. Deleted
P - 1007 - M P - 1008 - M	TP - 0007 - M TP - 0008 - M	Flue Gas Flue Gas	SSE SSE	13HNE10 BR001 13HNE10 BR001	CCP EPC CCP EPC	FT 1001 A-D TE 1001	PCCS-01-TC-PX-2365-00003-001 PCCS-01-TC-PX-2365-00003-001	V 6200 V 6200		0.0 / 0.04 100 0.0 / 0.04 100	0.05/-0.015 0.05/-0.015	120 120	NA NA	NA NA		EPC Contractor EPC Contractor		Instrument Tie in Instrument Tie in	Instrument Tie in Instrument Tie in	6	Instrument Tie-in CCP BL-002 Instrument Tie-in CCP BL-002
P - 1009 - M	TP - 0009 - M	Condensate	SSE	CONDENSER 2A	PS EPC	See Remarks	PCCS-01-TC-PX-2365-00005-001	L -	By ST Vendor	-0.98 46.8	12	265	EPC	EPC	EPC By	y ST Vendor		By ST Vendor	By ST Vendor	0	Condensate extract pump min.flow to existing main condensers - Turbine Vendor Supply. No existing line number. Turbine Vendor to confirm location of tie-in.
P - 1010 - M	TP - 0010 - M	Hot Reheat	SSE	See Remarks	PS EPC	See Remarks	PCCS-01-TC-PX-2365-00005-001	V	By ST Vendor	-0.98 46.8	0.367	120 (See Notes)	EPC	EPC	EPC By	y ST Vendor		By ST Vendor	By ST Vendor	6	IP Bypass Outlet to Condenser 2A; Piping from bypass valve to existing LP steam exaust ducting is supplied by the Turbine Vendor. Assumed as saturation temperature +10°C margin. No existing line number
P - 1011 - M	TP - 0011 - M	LP Steam	SSE	See Remarks	PS EPC	See Remarks	PCCS-01-TC-PX-2365-00005-001	V Note	By ST Vendor	-0.98 46.8	0.367	120 (See Notes)	EPC	EPC	EPC By	y ST Vendor		By ST Vendor	By ST Vendor		LP Bypass Outlet to Condenser 2B; Piping from bypass valve to existing LP steam exaust ducting is supplied by the Turbine Vendor. Assumed as saturation temperature +10°C margin. No existing line number
P - 1012 - M	TP - 0012 - M	Condensate	SSE	CONDENSER 2B	PS EPC	See Remarks	PCCS-01-TC-PX-2365-00005-001	L -	By ST Vendor	-0.98 46.8	12	265	EPC	EPC	EPC By	y ST Vendor		3a	BF		Condensate extract pump min.flow to existing main condensers - Turbine Vendor Supply. No existing line
TP - 1013 - M TP - 1014 - M	TP - 0013 - M TP - 0014 - M	Condensate Condensate	SSE SSE	CONDENSER 2B CONDENSER 2A		20LCA40 BR001 20LCA30 BR001 (See Remarks)	PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001	L -	50 250	-0.98 Ambient -0.98 40	5 11 (+FV)	66 160	EPC 960020	EPC 1481972	9636	EPC Contractor		3a 3b	BF BW	6 6	New line. Tie-in to existing condenser 2B. No existing line number LP condensate from CCP-BL-004. No existing line number
TP - 1015 - M TP - 1016 - M TP - 1017 - M	TP - 0015 - M TP - 0016 - M TP - 0017 - M	Condensate Condensate Condensate	SSE SSE SSE	See Remarks See Remarks See Remarks	PS EPC PS EPC PS EPC PS EPC	20LCA31 BR001 20LCA32 BR001 20LCA32 BR002	PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001	L 350 L 350		-0.7 24 -0.7 24 -0.7 24	35 (+FV) 35 (+FV) 35 (+FV)	66 66 66	969150 972750 EPC		7323 7323 EPC By E	EPC Contractor		3a 3a By EPC Contractor	BF BF By EPC Contractor		Downstream of MOV. No existing line number Downstream of MOV. No existing line number Pump 20LCB10 AP020 vent line Tie-in. No existing line number
P - 1018 - M	TP - 0018 - M	Condensate	SSE	See Remarks	PS EPC	20LCA35 BR001	PCCS-01-TC-PX-2365-00005-001	L 250	250	24 24	35 (+FV)	66	961539	1499000	15526	21 O Contractor		3b	BW	6	Tie-in upstream of branch to valve WC/49; Downstream of FIC 20LCA35 CF001. No existing line number
TP - 1019 - M TP - 1020 - M TP - 1021 - M	TP - 0019 - M TP - 0020 - M TP - 0021 - M	Condensate Condensate Condensate	SSE SSE SSE	See Remarks See Remarks See Remarks	PS EPC PS EPC	20LCA36 BR001 20LCA35 BR002 20LCA35 BR002	PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001	L Note L 250	250	24 24 24 24 24 24	35 (+FV) 35 (+FV) 35 (+FV)	66 66	EPC 956539 950501	1499000	EPC By 15526 15526	y ST Vendor		By ST Vendor 3b	By ST Vendor BW	6	Branch upstream of existing RO going to Vent steam condenser. No existing line number Tie-in downstream of existing RO. No existing line number Tie-in upstream of branch to valve WC/12. No existing line number
P - 1021 - M P - 1022 - M P - 1023 - M	TP - 0021 - M TP - 0022 - M TP - 0023 - M	Water Condensate	SSE SSE	See Remarks See Remarks	PS EPC PS EPC PS EPC	20LCA35 BR002 20LCA40 BR001 20LCA38 BR001	PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001	L Note L Note	5 50	Atm. Ambient 24 24	5 35 35	66 66	EPC 994781	EPC 1460785	EPC By E 13807	EPC Contractor		By EPC Contractor 3b	By EPC Contractor BW	6	Tie-in dowstream of valve RFW/1A; upstream of branch to RFW/1B. No existing line number Tie-in downstream of branch containing valve WC/73. No existing line number
P - 1024 - M P - 1025 - M	TP - 0024 - M TP - 0025 - M	Condensate Phosphate	SSE SSE	See Remarks 10QCD10.1	PS EPC PS EPC	20LCA31 BR002 20QCD30 BR001	PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00006-001	L 50	50 15	-0.7 24 25 Ambient	35 35	66 66	EPC EPC	EPC EPC	EPC By E	EPC Contractor		3a 3b	By EPC Contractor By EPC Contractor		Pump 20LCB10 AP010 vent line Tie-in. No existing line number
P - 1026 - M P - 1027 - M P - 1028 - M	TP - 0026 - M TP - 0027 - M TP - 0028 - M	Phosphate Chemical Injection Chemical Injection	SSE SSE SSE	10LCA20 BR611 10QCA10.1 10LCA20 BR601	PS EPC PS EPC PS EPC PS EPC	10LCA20 BR611 20QCA30 BR001 10LCA20 BR601	PCCS-01-TC-PX-2365-00006-001 PCCS-01-TC-PX-2365-00006-001 PCCS-01-TC-PX-2365-00006-001	L 15 L 15 L 15	15 15 15	25 Ambient 25 Ambient 25 Ambient	35 35 35	66 66 66	EPC EPC EPC	EPC EPC EPC	EPC By E	EPC Contractor EPC Contractor EPC Contractor		3b 3b 3b	By EPC Contractor By EPC Contractor By EPC Contractor	6 6 6	
P - 1029 - M P - 1030 - M	TP - 0029 - M TP - 0030 - M	Condensate Condensate	SSE SSE	10LCA20 BR001 10LCA20 BR001	PS EPC PS EPC	Line Capped Line Capped	PCCS-01-TC-PX-2365-00006-001 PCCS-01-TC-PX-2365-00006-001	L 250 L 250	- -	25 46.8 25 46.8	35 35	66 66	914355 914355	1294640 1291943	19688 19721			3b 3b	BW BW	6 6	To end cap that is used to separate the line to HRSG-13
P - 1031 - M P - 1032 - M P - 1033 - M	TP - 0031 - M TP - 0032 - M TP - 0033 - M	LP Steam LP Steam LP Steam	SSE SSE SSE	10LBG15 BR001 13LBA85 BR002 13LBA85 BR002	PS EPC PS EPC PS EPC PS EPC	13LBG40 BR001 13LBA40 BR001 13LBA41 BR001	PCCS-01-TC-PX-2365-00007-001 PCCS-01-TC-PX-2365-00008-001 PCCS-01-TC-PX-2365-00008-001	V 250 V 350 V 250	250 350	3.2 240 4.1 236.7 0 Ambient	12 12 12	265 265 265	964610 939805 945999	1250773 1383500 1384400	34667 25320 21494			3b 3b	BW BW BW	6 6	Line decommissioned
P - 1034 - M P - 1035 - M	TP - 0034 - M TP - 0035 - M	Cold Reheat Cold Reheat	SSE SSE	13LBC45 BR001 13LBC45 BR001	PS EPC PS EPC	10LBC46 BR001 20LBC47 BR001	PCCS-01-TC-PX-2365-00009-001 PCCS-01-TC-PX-2365-00009-001	V 550 V 550	550	23.2 362 23.2 362	50 50	410 410	926260 926249	1289479 1285104	18324 18575			3b 3b	BW BW	6	
P - 1036 - M P - 1037 - M P - 1038 - M	TP - 0036 - M TP - 0037 - M TP - 0038 - M	Hot Reheat Hot Reheat	SSE SSE SSE	13LBB45 BR001 13LBB46 BR001 13LBB55 BR001	PS EPC PS EPC PS EPC	Line Capped Line Capped 13LBB45 BR001	PCCS-01-TC-PX-2365-00010-001 PCCS-01-TC-PX-2365-00010-001 PCCS-01-TC-PX-2365-00010-001	V 645 x V 645 x V 645 x	8 -	21.83 512 21.83 512 21.83 512	50 50	545 545 545	909740 909740 909740	1358805	18330 18321 21420			3b 3b	BW BW RW	6	Tie-in where the existing line has been capped Tie-in where the existing line has been capped
P - 1038 - M P - 1039 - M P - 1040 - M	TP - 0038 - M TP - 0039 - M TP - 0040 - M	Hot Reheat Hot Reheat HP Steam	SSE SSE SSE	13LBB55 BR001 13LBB55 BR001 13LBA15 BR001	PS EPC PS EPC PS EPC	13LBB45 BR001 Line Capped 13LBA50 BR001	PCCS-01-TC-PX-2365-00010-001 PCCS-01-TC-PX-2365-00010-001 PCCS-01-TC-PX-2365-00011-001	V 645 x 2	8 -	21.83 512 21.83 512 76.22/104.5 530/525	50 50 165	545 545 545	909740 914295 919600	1356535 1356535 1282500	21420 30567 16257			3b 3b 3b	BW BW	6 6	Existing line renamed to 13LBB47 BR001
P - 1041 - M P - 1042 - M	TP - 0041 - M TP - 0042 - M	HP Steam Demin Water	SSE SSE	13LBA15 BR001 See Remarks	PS EPC PS EPC	Line Capped 00GHC86 BR001	PCCS-01-TC-PX-2365-00011-001 PCCS-01-TC-PX-2365-00013-001	V 325 x 2 V 325 x 2 L Note	50	76.22 / 104.5 530 / 525 7 Ambient	165 9	545 50	923500 EPC	1290368 EPC	16189 EPC By E	EPC Contractor		3b By EPC Contractor	BW By EPC Contractor	6	Tie-in where the existing line has been capped. Existing line renamed to 10LBA51 BR001 Tie-in to existing line from RFW tanks to Common Services line. No existing line number
P - 1043 - M P - 1044 - M P - 1045 - M	TP - 0043 - M TP - 0044 - M TP - 0045 - M	Cooling water Cooling water Cooling water	SSE SSE SSE	CCW CLR A CCW CLR A CCW CLR B	PS EPC PS EPC	See Remarks See Remarks See Remarks	PCCS-01-TC-PX-2365-00013-001 PCCS-01-TC-PX-2365-00013-001 PCCS-01-TC-PX-2365-00013-001	L Note L Note L Note	By ST Vendor	5 20 5 20 5 20	6.9 6.9 6.9	30 30 30	EPC EPC EPC	EPC EPC	EPC By	y ST Vendor y ST Vendor v ST Vendor		By ST Vendor By ST Vendor By ST Vendor	By ST Vendor By ST Vendor By ST Vendor	6 6	CCW CLR A to CCW package. Steam Turbine Vendor Scope. No existing line number CCW package to CCW CLR A. Steam Turbine Vendor Scope. No existing line number CCW CLR B to CCW package. Steam Turbine Vendor Scope. No existing line number
P - 1046 - M P - 1047 - M	TP - 0043 - M TP - 0046 - M TP - 0047 - M	Cooling water Cooling water	SSE		PS EPC PS EPC	See Remarks	PCCS-01-TC-PX-2365-00013-001	L Note		5 20	6.9	30	EPC	L1 0	· ·	y ST Vendor		By ST Vendor	By ST Vendor	6	CCW package to CCW CLR B. Steam Turbine Vendor Scope. No existing line number Deleted
P - 1048 - M P - 1049 - M	TP - 0048 - M																				Deleted Deleted Deleted
P - 1050 - M P - 1051 - M P - 1052 - M	TP - 0050 - M TP - 0051 - M TP - 0052 - M	Demin Water Demin Water	SSE SSE	10GHC10 BR001 See Remarks	PS EPC PS EPC	00GHC10 BR001 00GHC87 BR001	PCCS-01-TC-PX-2365-00021-001 PCCS-01-TC-PX-2365-00022-001	L 50 L Note	50	7 10 7 Ambient	10	50 50	EPC 903665	EPC 1449153	EPC By E 26533	EPC Contractor		By EPC Contractor By EPC Contractor		6	Deleted Tie-in downstream of valve 2/WD/2. No existing line number
P - 1053 - M P - 1054 - M	TP - 0053 - M TP - 0054 - M	Potable Water Potable Water	SSE SSE	10GKB10 BR001 See Remarks	PS EPC PS EPC	13GKB10 BR001 00GKB86 BR001	PCCS-01-TC-PX-2365-00023-001 PCCS-01-TC-PX-2365-00024-001	L 80 L 80	80 80	7 Ambient 6 Ambient	10 7	50 50	EPC EPC	EPC EPC	EPC By E	EPC Contractor EPC Contractor		By EPC Contractor By EPC Contractor By EPC Contractor	By EPC Contractor	6	Tie-in to VP21 on the existing Towns water ring main. No existing line number
P - 1055 - M P - 1056 - M P - 1057 - M	TP - 0055 - M TP - 0056 - M TP - 0057 - M	Condensate Condensate Condensate	SSE SSE SSE	See Remarks See Remarks See Remarks	PS EPC PS EPC PS EPC PS EPC	00QLC70 BR001 00QLC71 BR001 00QLC72 BR001	PCCS-01-TC-PX-2365-00028-001 PCCS-01-TC-PX-2365-00028-001 PCCS-01-TC-PX-2365-00028-001	L 50 L Note L Note	50 50 50 50	5 160 5 160 5 160	19 (+FV) 7 (+FV) 7 (+FV)	230 230 230	EPC EPC EPC	EPC EPC	EPC By E	EPC Contractor EPC Contractor EPC Contractor		By EPC Contractor By EPC Contractor By EPC Contractor	By EPC Contractor By EPC Contractor By EPC Contractor		Tie-in to existing PRS condensate returns line. No existing line number Tie-in to existing HRSG Heating and Ventilation line. No existing line number Tie-in to existing Admin and Control block heating and ventilation. No existing line number
P - 1058 - M P - 1059 - M	TP - 0058 - M TP - 0059 - M	Demin Water Auxiliary Steam	SSE	See Remarks See Remarks	PS EPC	00GHC55 BR001 00LBG55 BR003	PCCS-01-TC-PX-2365-00027-001 PCCS-01-TC-PX-2365-00031-001	L Note V 150	80	6.0 / 7.8 Ambient 17 230	9	50 250	EPC 934500	EPC 1381857	28071	EPC Contractor		By EPC Contractor 3b	By EPC Contractor BW	6 5	Tie-in to line from existing RFW tanks to common services. No existing line number Auxiliary steam line tie-in to existing line to PRS. No existing line number
P - 1060 - M P - 1061 - M P - 1062 - M	TP - 0060 - M TP - 0061 - M TP - 0062 - M	Gland sealing steam Auxiliary Steam Condensate	SSE SSE SSF	10LBG22 BR001 10LBG22 BR001 See Remarks	PS EPC PS EPC PS EPC PS EPC	00LBG58 BR001 00LBG55 BR005 00QLC68 BR001	PCCS-01-TC-PX-2365-00031-001 PCCS-01-TC-PX-2365-00031-001 PCCS-01-TC-PX-2365-00031-001	V 150 V 150 L Note		17 230 17 230	19 19	250 250 250	936400 875250 EPC	1418671 1393000 EPC	22334 18000 EPC By E	EPC Contractor		3b 3b By EPC Contractor	BW BW By EPC Contractor	6 5	Tie-in to existing line from Auxiliary steam ring main
P - 1063 - M	TP - 0063 - M	Fuel Gas	SSE	3"-P-4003-3A1	PS EPC	00EKG66 BR001	PCCS-01-TC-PX-2365-00032-001	V 80	80	27 15	39 (See Notes)	85 (See Notes)	EPC	EPC	, and the second	EPC Contractor		By EPC Contractor	By EPC Contractor		Tie-in to existing Fuel gas line to new Auxiliary Boiler fuel gas skids. Design conditions for existing line to be determined by EPC contractor
P - 1064 - M P - 1065 - M	TP - 0064 - M TP - 0065 - M																				Deleted Deleted Auxiliary CW system tie-in. Upstream of valves 10PCB11 AA001 and 10PCB12 AA001. No existing line
P - 1066 - M	TP - 0066 - M	Cooling water	SSE	See Remarks	PS EPC	00PAB20 BR002	PCCS-01-TC-PX-2365-00025-001	L 600	600	3.15 5 / 15	5	85	1102936	1268496	2877			3a	BF	6	number Deleted
P - 1068 - M P - 1069 - M	TP - 0068 - M	Cooling water			PS EPC	FT 00PAB21 CF101	PCCS-01-TC-PX-2365-00025-001 PCCS-01-TC-PX-2365-00025-001	L Note		3.15 5/15	5	85	1100874		4706			Strap on instrument	<u> </u>		Deleted Tie-in to install strap-on flowmeter
P - 1070 - M P - 1071 - M P - 1072 - M	TP - 0070 - M TP - 0071 - M TP - 0072 - M	Cooling water Cooling water		00PAB21 BR003 See Remarks	PS EPC PS EPC	FT 00PAB21 CF102 00PAB21 BR001	PCCS-01-TC-PX-2365-00025-001	L Note L 1800		3.15 5 / 15 3.15 5 / 15	5	85 85	1108392 1110009		4706 4706 -			Strap on instrument 3b	Strap on instrument BW	6	Tie-in to install strap-on flowmeter Tie-in is downstream of the pump 3/4 Y-Tee and the crossover valve. No existing line number Deleted
P - 1073 - M	TP - 0073 - M	Cooling water	SSE	00PAB26 BR001	PS EPC	Line Capped	PCCS-01-TC-PX-2365-00025-001	L 400		1 5/15	5	85	973864	1463757	9300			3b	BW		End-cap connection. Upstream of General Services Water Coolers 2A and 2B. No existing line number
P - 1074 - M P - 1075 - M P - 1076 - M	TP - 0074 - M TP - 0075 - M TP - 0076 - M	Cooling water Cooling water Cooling water	SSE SSE SSF	00PAB26 BR001 00PAB23 BR001 00PAB24 BR001	PS EPC PS EPC PS EPC	00PAB26 BR001 Line Capped Line Capped	PCCS-01-TC-PX-2365-00025-001 PCCS-01-TC-PX-2365-00025-001 PCCS-01-TC-PX-2365-00025-001	L 400 L Note L 400	-	3.15 5/15 1 5/15 1 5/15	5 5 5	85 85 85	971639 957639 945814	1449284 1458580 1458580	9300 9300 9300			3b 3b 3b	BW BW	6	Tie-in point downstream of existing valves 16A and B. No existing line number Tie-in upstream of General Services Water Coolers 2A and 2B. No existing line number Tie-in downstream of General Services Water Coolers 2A and 2B. No existing line number
P - 1077 - M P - 1078 - M	TP - 0077 - M TP - 0078 - M	Cooling water			PS EPC	00PAB20 BR002	PCCS-01-TC-PX-2365-00025-001	L Note		3.15 5/15	5	85	111000	1267114	4706			3b	BW		Tie-in upstream of existing valve 2/CW/3. No existing line number
P - 1079 - M P - 1080 - M P - 1081 - M	TP - 0079 - M TP - 0080 - M TP - 0081 - M																				Deleted Deleted Deleted
P - 1082 - M P - 1083 - M	TP - 0082 - M TP - 0083 - M																				Deleted Deleted
P - 1084 - M	TP - 0084 - M	Raw water	SSE	See Remarks	PS EPC	Line Capped	PCCS-01-TC-PX-2365-00005-001	L Note		Atm. Ambient	5	66	948750	1486733	9710			3b	BW	ъ.	Tie-in upstream of condensates dump Tie-in downstream of RFW tanks A/B. No existing line number Tie-in upstream of condensates dump
P - 1085 - M	TP - 0085 - M	Raw water	SSE	See Remarks See Remarks	PS EPC PS EPC	Line Capped Line Capped	PCCS-01-TC-PX-2365-00005-001 PCCS-01-TC-PX-2365-00005-001	L Note		25 Ambient 25 Ambient	35	66	949811 949965	1490616 1486733	9710 9710			3b	BW	6	Tie-in downstream of RFW tanks A/B. No existing line number Tie-in upstream of condensates dump
P - 1086 - M	TP - 0086 - M	Raw water Raw water	SSE	See Remarks See Remarks	PS EPC PS EPC	Line Capped Line Capped	PCCS-01-TC-PX-2365-00005-001	L Note		Atm. Ambient	5	66	949965	1486733	9710			3b	BW	6	Tie-in downstream of RFW tanks A/B. No existing line number Tie-in upstream of condensates dump Tie-in downstream of RFW tanks A/B. No existing line number
P - 1088 - M P - 1089 - M	TP - 0088 - M TP - 0089 - M	Demin Water Condensate	SSE	See Remarks HP Drains Receiver	PS EPC	00GHC58 BR001 See Remarks	PCCS-01-TC-PX-2365-00027-001 PCCS-01-TC-PX-2365-00005-001	L Note	5 50 By ST Vendor	2 Ambient -1 Ambient	9 50 / -1	50 405	EPC EPC	EPC EPC		EPC Contractor EPC Contractor		By EPC Contractor By EPC Contractor	By EPC Contractor By EPC Contractor	6	Tie-in downstream of RFW tanks A/B. No existing line number Pump min flow line to Demin Common Services. No existing line number Cold reheat drain line to condenser. Turbine vendor scope. No existing Line
P - 1090 - M P - 1091 - M	TP - 0090 - M TP - 0091 - M TP - 0092 - M	Steam LP Steam	SSE SSF	13LBA80 BR001	PCCS-01-TC-PX-2365-00015-001 PS EPC PCCS-01-TC-PX-2365-00007-001 PS EPC	13LBG40 BR001 13LBG42 BR002	PCCS-01-TC-PX-2365-00015-001 PCCS-01-TC-PX-2365-00007-001	V 350	350	4.1 236.7	12	250	949300		18645	EPC Contractor		3b	BW	6	Deleted
P - 1092 - M P - 1093 - M P - 1094 - M	TP - 0092 - M TP - 0093 - M TP - 0094 - M	LP Steam LP Steam Condensate	SSE SSE SSE	13LBG15 BR001 13LBG15 BR001 13LCL30 BR430	PCCS-01-TC-PX-2365-00007-001 PS EPC PCCS-01-TC-PX-2365-00007-001 PS EPC PCCS-01-TC-PX-2365-00038-001 PS EPC	13LBG42 BR002 13LBG42 BR001 13LCL30 BR990	PCCS-01-TC-PX-2365-00007-001 PCCS-01-TC-PX-2365-00007-001 PCCS-01-TC-PX-2365-00038-001	V 350 V 50 M 250	50 50 250	3.2 250 3.2 250 5 420	12 12 7	265 265 465	EPC 963633 EPC	1250273 EPC	34244	EPC Contractor EPC Contractor		3b 3b 3b	BW BW	6 6	
P - 1095 - M P - 1096 - M	TP - 0095 - M TP - 0096 - M	Condensate Condensate	SSE SSE	13LCL30 BR430 13LCL30 BR431	PCCS-01-TC-PX-2365-00038-001 PS EPC PCCS-01-TC-PX-2365-00038-001 PS EPC	13LCL31 BR430 13LCL30 BR991	PCCS-01-TC-PX-2365-00038-001 PCCS-01-TC-PX-2365-00038-001	M 25 M 25	25 25	5 420 5 420	7 7 -	465 465	EPC EPC	EPC EPC	EPC By E	EPC Contractor EPC Contractor		3b	BW BW	6	
P - 1097 - M P - 1098 - M P - 1099 - M	TP - 0097 - M TP - 0098 - M TP - 0099 - M	Condensate Condensate Condensate	SSE SSE SSE	13LCL30 BR431 13LCL50 BR417 13LCL50 BR417	PCCS-01-TC-PX-2365-00038-001 PS EPC PCCS-01-TC-PX-2365-00038-001 PS EPC PCCS-01-TC-PX-2365-00038-001 PS EPC	13LCL31 BR431 10LCL31 BR417 13LCL50 BR997	PCCS-01-TC-PX-2365-00038-001 PCCS-01-TC-PX-2365-00038-001 PCCS-01-TC-PX-2365-00038-001	M 25 M 25 M 25	25 25 25	5 420 5 420 5 420	7 7	465 465 465	EPC EPC EPC	EPC EPC EPC	EPC By E EPC By E	EPC Contractor EPC Contractor EPC Contractor		3b 3b 3b	BW BW BW	6 6 6	
P - 1100 - M P - 1101 - M	TP - 0100 - M TP - 0101 - M	Condensate Condensate	SSE SSE	10LCL20 BR002 10LCL20 BR002	PCCS-01-TC-PX-2365-00034-001 PS EPC PCCS-01-TC-PX-2365-00034-001 PS EPC	10LCL20 BR101 10LCL20 BR102	PCCS-01-TC-PX-2365-00034-001 PCCS-01-TC-PX-2365-00034-001		150	2 100 2 100	6 (+FV) 6 (+FV)	150 150	907650 907650	1295710 1295120	17472 17399			3b 3b	BW BW	6	EPC Contractor to determine if pipework is suitable for upstream conditions. EPC Contractor to determine if pipework is suitable for upstream conditions.
P - 1102 - M P - 1103 - M P - 1104 - M	TP - 0102 - M TP - 0103 - M TP - 0104 - M	Condensate Condensate Condensate	SSE SSE SSE	1020220 211001		13LCL20 BR002 10LCM03 BR991 13LCM03 BR431	PCCS-01-TC-PX-2365-00034-001 PCCS-01-TC-PX-2365-00040-001 PCCS-01-TC-PX-2365-00040-001	L 125 M 25 M 25	25	4 100 0 520 0 520	6 (+FV) 30 30	150 545 545	907650 EPC EPC	1294595 EPC EPC	,	EPC Contractor		3b 3b 3b	BW BW BW	6 6 6	EPC Contractor to determine if pipework is suitable for upstream conditions.
P - 1105 - M P - 1106 - M	TP - 0105 - M TP - 0106 - M	Condensate Condensate	SSE SSE	10LCM03 BR432 10LCM03 BR432	PCCS-01-TC-PX-2365-00040-001 PS EPC PCCS-01-TC-PX-2365-00040-001 PS EPC	10LCM03 BR992 13LCM03 BR432	PCCS-01-TC-PX-2365-00040-001 PCCS-01-TC-PX-2365-00040-001	M 80 M 80	80 80	0 520 0 520	30 30	545 545	EPC EPC	EPC EPC	EPC By E EPC By E	EPC Contractor EPC Contractor		3b 3b	BW BW	6	
P - 1107 - M P - 1108 - M P - 1109 - M	TP - 0107 - M TP - 0108 - M TP - 0109 - M	Condensate Condensate Condensate	SSE SSE SSE	10LCM03 BR465	PCCS-01-TC-PX-2365-00040-001 PS EPC PCCS-01-TC-PX-2365-00040-001 PS EPC PCCS-01-TC-PX-2365-00040-001 PS EPC	10LCM03 BR995 13LCM03 BR465 10LCM03 BR996	PCCS-01-TC-PX-2365-00040-001 PCCS-01-TC-PX-2365-00040-001 PCCS-01-TC-PX-2365-00040-001	M 25 M 25 M 25	25 25 25	0 380 0 380 0 380	7 7 7	400 400 400	EPC EPC EPC	EPC EPC EPC	EPC By E	EPC Contractor EPC Contractor EPC Contractor		3b 3b 3h	BW BW BW	6 6 6	
P - 1110 - M P - 1111 - M	TP - 0110 - M TP - 0111 - M	Condensate LP Bypass	SSE SSE	10LCM03 BR466 13MAN62 BR001	PCCS-01-TC-PX-2365-00040-001 PS EPC PCCS-01-TC-PX-2365-00014-001 PS EPC	13LCM03 BR466 Line Capped	PCCS-01-TC-PX-2365-00040-001 PCCS-01-TC-PX-2365-00014-001	M 25 V 50	25	0 380 -0.98 46.8	7 7	400 250	EPC EPC EPC	EPC	EPC By E	PC Contractor PC Contractor		3b 3b	BW BW	6	
P - 1112 - M P - 1113 - M P - 1114 - M	TP - 0112 - M TP - 0113 - M TP - 0114 - M	LP Bypass IP Bypass IP Bypass	SSE SSE SSE	13MAN63 BR002 13MAN52 BR001	PCCS-01-TC-PX-2365-00014-001 PS EPC	Line Capped Line Capped Line Capped	PCCS-01-TC-PX-2365-00014-001 PCCS-01-TC-PX-2365-00014-001 PCCS-01-TC-PX-2365-00014-001	L 25 V 800 L 150		0 Ambient -0.98 46.8 -0.98 46.8	35 28 Note 7	66 545 Note 7	EPC 967218 966814	EPC 1467043 1467486	EPC By E 15303 14444	EPC Contractor		3b 3b	BW BW BW	6 6	
P - 1115 - M P - 1116 - M	TP - 0115 - M TP - 0116 - M	LP Bypass IP Bypass		MAG10 Condenser 2A 13MAN53 BR001	PCCS-01-TC-PX-2365-00014-001 PS EPC PCCS-01-TC-PX-2365-00014-001 PS EPC	Line Capped Line Capped	PCCS-01-TC-PX-2365-00014-001 PCCS-01-TC-PX-2365-00014-001	V 25 L 25		-0.98 46.8 -0.98 46.8 0 Ambient	Note 7 Note 7 Note 7	Note 7 Note 7 Note 7	EPC 966814	EPC 1467246	EPC By E	EPC Contractor		3b 3b	BW BW BW	6	
P - 1117 - M P - 1118 - M P - 1119 - M	TP - 0117 - M TP - 0118 - M TP - 0119 - M	LP Bypass IP Bypass Condensate	SSE SSE SSE	13LBA43 BR001 13LBB56 BR001	PCCS-01-TC-PX-2365-00008-001 PS EPC PCCS-01-TC-PX-2365-00010-001 PS EPC PCCS-01-TC-PX-2365-00038-001 PS EPC	Line Capped Line Capped 13LCL31 BR418	PCCS-01-TC-PX-2365-00008-001 PCCS-01-TC-PX-2365-00010-001 PCCS-01-TC-PX-2365-00038-001	V 350 V 80 M 25	-	0 Ambient 0 Ambient	12 50	250 545 465	944229 EPC EPC		21015 EPC By E	EPC Contractor		3b 3b	BW BW BW	6	Line 13LBA85/86 decommissioned. Line 13LBB47 BR001 up to valve 13LBB56 AA001 decomissioned.
P - 1120 - M P - 1121 - M	TP - 0119 - M TP - 0120 - M TP - 0121 - M	Condensate Condensate Condensate	SSE SSE	13LCL50 BR418 13HNE10 BR001	PCCS-01-TC-PX-2365-00038-001 PS EPC PCCS-01-TC-PX-2365-00003-001 PS EPC	13LCL50 BR998 QT 13HNE85 CQ101	PCCS-01-TC-PX-2365-00038-001 PCCS-01-TC-PX-2365-00003-001	M 25 M Note	25 S N/A	0 400 0 400 0.0 / 0.04 100	7 7 0.05/-0.015	465 465 120	EPC EPC	EPC EPC	EPC By E EPC By E	EPC Contractor EPC Contractor EPC Contractor		3b 3b Instrument Tie in	BW BW Instrument Tie in	6 6 6	Instrument tie-in
P - 1122 - M P - 1123 - M	TP - 0122 - M TP - 0123 - M	Condensate Condensate	SSE SSE	13HNE10 BR001 13LBA86 AA404	PCCS-01-TC-PX-2365-00003-001 PS EPC PCCS-01-TC-PX-2365-00008-001 PS EPC	QT 13HNE85 CQ102 Line Capped	PCCS-01-TC-PX-2365-00003-001 PCCS-01-TC-PX-2365-00008-001	M Note M 25	6 N/A -	0.0 / 0.04 100 0 100	0.05/-0.015 Note 7	120 Note 7	EPC EPC	EPC	EPC By E	EPC Contractor EPC Contractor		Instrument Tie in 3b	Instrument Tie in BW	6 6	Instrument tie-in Line decommissioned.
2 - 1124 - M 2 - 1125 - M 2 - 1126 - M	TP - 0124 - M TP - 0125 - M TP - 0126 - M	Condensate Condensate Condensate	SSE SSE SSE		PCCS-01-TC-PX-2365-00008-001 PS EPC PCCS-01-TC-PX-2365-00010-001 PS EPC PCCS-01-TC-PX-2365-00010-001 PS EPC	Line Capped Line Capped Line Capped	PCCS-01-TC-PX-2365-00008-001 PCCS-01-TC-PX-2365-00010-001 PCCS-01-TC-PX-2365-00010-001	M 25 M 25 M 25		0 100 0 100 0 100	Note 7 Note 7 Note 7	Note 7 Note 7 Note 7	EPC EPC EPC	EPC EPC EPC	EPC By E	EPC Contractor EPC Contractor EPC Contractor		3b 3b 3b	BW BW BW	6 6 6	Line decommissioned. Line decommissioned. Line decommissioned.
- 1127 - M	TP - 0127 - M			EPC	EPC PS EPC	EPC EPC	PCCS-01-TC-PX-2365-00010-001	L EPC	EPC	EPC EPC	EPC	EPC	EPC	EPC	EPC By E			3b	BW	·	Recycle line for treated water back to Power Station.

													K01		CLIEN PROJEC LOCATIO	г:	PETER	SHELL U.K. LTD HEAD CCS (ONSF ERHEAD, SCOTLA					DOC CLIENT	
LI	LINE INFORMATION INTERCONNECTED LINES								FLOWRATE	LINE	SIZE (mm)	OPERAT CONDITION	ING		DESIGN CONDITIONS INTERFACE POINT LOCATION									
TP NO BL NO	TIE-IN NO	SERVICE	ORG X	LINE NO	P&ID	ORG Y	LINE NO	P&ID	PHASE DESIGN FLOW RATE (kg/h)	EXISTING LINE	NEW LINE	PRESS (barg)	TEMP (°C)	PRESS (barg)	TEMP (°C)	Easting	Northing	Elevation	KEY DWG	REFERENCE DWGS/DOCUMENTS	INTERFACE POINT TYPE	TYPE OF CONNECTION	TIE-IN CLASSIFICAT	NOTES R
TP - 1200 - M 001		Flue Gas	PS EPC	01	PCCS-01-TC-PX-2365-00003-001	CCP EPC	02	PCCS-02-TC-PX-2365-00001-001	V 2,556,00	6100x6100	6100x6100	0.0	100	0.05/-0.015 (Note 12)	-5 / 120	907600	1266300	17650			4a	BF	6	
TP - 1201 - M 002														,										Deleted
TP - 1202 - M 003				20LBA43 BR001		CCP EPC	02-SLP-4001		V 219,456		900	2.2	141	-1/5	-5 / 160	960660	1489660	14040			2	BW	6	
TP - 1203 - M 004 TP - 1204 - M 005		LP Condensate Flue Gas	PS EPC	20LCA30 BR001	PCCS-01-TC-PX-2365-00005-001 PCCS-02-TC-PX-2365-00002-001	CCP EPC	02-SCL-4022	PCCS-02-TC-PX-2365-00101-001	L 180,665 V 2,356,72	200	200 10400v5200	-0.8	40 75	-1 / 11 0.085	-5 / 160 -5 / 120	823600	1476980 1436300	10450 26750			2 4b	BW	6	Elua gas to main stock
TP - 1204 - M			PS FPC	001 BG55 BR006	PCCS-01-TC-PX-2365-00002-001	CCP EPC	02 02-SMP-4001	PCCS-02-TC-PX-2365-00108-001	V 2,336,72	1040003200	10400x3200	20.5	237	-1 / 27	-57 120 270	828250	1345590	9570			40	RW	6	Flue gas to main stack
TP - 1206 - M 007		Demin Water		00GHC87 BR001		CCP EPC	02-WDM-4001	PCCS-02-TC-PX-2365-00107-001	L 50,000		150	7.0	10	0/9	-5 / 85	827700	1348590	9480			2	BW	6	Continuous consumption
P - 1207 - M 008		Towns Water	PS EPC	00GKB86 BR001	PCCS-01-TC-PX-2365-00024-001	CCP EPC	02-WDR-4001	PCCS-02-TC-PX-2365-00079-001	L 25,471		80	4.0	10	0/7	-5 / 85	751000	1341300	8900			1	BF	6	BL at the underground/above ground transition. Above ground to below ground BL interface. New line 00GKB86 BR001 is an 80mm U/G line which ties into the Towns Water ring main at VP21 (see TP-0054) and feeds into new CCP line 80-02-WDR local to the new towns water break tank (T-4001) 80mm lines have not been modelled.
TP - 1208 - M 009		MP Condensate	PS EPC	00QLC69 BR001	PCCS-01-TC-PX-2365-00027-001	CCP EPC	02-SCM-4001	PCCS-02-TC-PX-2365-00108-001	L 4,950	150	150	15.0	200	-1 / 27	250	EPC	EPC	EPC	By EPC Contractor		Note 14	BW	6	
TP - 1209 - M 010		Sea Water	PS EPC	00PAB21 BR001	PCCS-01-TC-PX-2365-00025-001	CCP EPC	02-WSS-4001	PCCS-02-TC-PX-2365-00073-001	L 20,272,80	3 1700	1700	3.3	5 / 15 (Note 11)	0/9	-5 / 85	767810	1241260	12460			1	BF	2	
TP - 1210 - M 011		Sea Water	PS EPC	00PAB22 BR001	PCCS-01-TC-PX-2365-00025-001	CCP EPC	02-WSR-4005	PCCS-02-TC-PX-2365-00074-001	L 20,272,80	3 1700	1700	1.8	17.5 / 27.5 (Note 11)	0/9	-5 / 85	989965	1641837	4000			1	BF	2	BL-011 elevation is +10.7m AOD. Stated pressure is the normal pressure, for rated flow the BL-011 pressure is 1 barg.
TP - 1211 - M 012		Treated water																						
ΓP - 1212 - M 013		CO2	CCP EPC		PCCS-02-TC-PX-2365-00064-001	PL EPC	02-PRO-3066		V 137,050	250	250	120.0	25	0 / 143	-5 / <mark>100</mark> (Note 10)	767655	1631625	16135			2	N/A	6	Battery Limit to CO2 pipeline contractor. Minimum metal design temperature -79 C.
TP - 1212 - M 014		Treated water	CCP EPC	By EPC Contractor	By EPC Contractor	PS EPC	By EPC Contractor	By EPC Contractor	L 754,000 (Note 9)	-	Note 6	EPC	Ambient	EPC	EPC	EPC	EPC	EPC	By EPC Contractor	By EPC Contractor		BF	6	Recycle line for treated water back to Power Station.
				_																				

PCCS-00-TC-AA-6627-00002 - INTERFACE RESPONSIBILITY SPECIFICATION

NOTES:
A - GENERAL: EPC CONTRACTOR TO RECONFIRM AND FINALISE FLOWRATES AND LINE SIZES DURING DETAILED DESIGN.
B - GENERAL: TIE-IN TYPE AND CLASSIFICATION TO BE CONFIRMED DURING DETAILED ENGINEERING BY COMPANY AND THE EPC CONTRACTOR BASED ON PLANT AVAILABILITY FOR SHUTDOWN DURING PROJECT SCHEDULE.
C - EPC CONTRACTOR TO UTILIZE THIS SCHEDULE AND ENHANCE IT FURTHER INTEGRATING ADDITIONAL DETAILS AND TIE-INS AS NECESSARY TO INCLUDE THE FULL EPC SCOPE INCLUDING ANY DEMOLITION AND ISOLATION.

4 - DELETED 6 - AS LISTED: EXISTING LINE SIZE TO BE CONFIRMED DURING EPC PHASE.
7- AS LISTED: DESIGN CONDITIONS OF EXISTING LINES TO BE CONFIRMED DURING EPC PHASE.

10 - AS LISTED: TBC BY COMPRESSOR VENDOR IN EPC.
11 - AS LISTED: WINTER/SUMMER CONDITIONS.
12 - AS LISTED: DESIGN CONDITIONS OF DUCTING TO BE CONFIRMED AFTER BOOSTER FAN (CCP) VENDOR INFORMATION RECEIVED.
13 - BATTERY LIMIT DESIGN FLOW RATE: FLOW SHOWN IS MAXIMUM VALUE QUOTED IN H&MB.
14 - DELETED

			LEGEND	
PPS EPC	Power Station EPC Contractor		TYPE OF CONNECTION:	TIE-IN CLASSIFICATION :
CCP EPC	Carbon Capture Plant EPC Contractor	HT-	HOT TAP	1. NO SHUTDOWN NECESSARY TO MAKE
		DB-	DRILLED BRANCH	TIE-IN
		CF-	COLD CUT	2. PRE-ARRANGED SHUTDOWN OF SPECIFIC
		BW-	BUTT WELD	SYSTEM NECESSARY TO MAKE TIE-IN
		BF-	BOLT TO EXISTING FLANGE	3. HOT TAP
		BB-	BOLT BLIND TO EXISTING FLANGE	4. DURING PARTIAL SHUTDOWN
		SC-	SCREWED CONNECTION	5. DURING UNIT SHUTDOWN.
		FC-	FIT COUPLING	6. DURING MULTI-UNIT SHUTDOWN.
		HC-	HUB CONNECTOR	SEE NOTE B
		SEE NO	TE <mark>B</mark>	

CLIENT: SHELL U.K. LTD
PROJECT: PETERHEAD CCS (ONSHORE)

LOCATION: PETERHEAD, SCOTLAND

DOC. NO.: CLIENT REF.: REV:

PCCS-00-TC-AA-6627-00001 K01

	ELECTRICAL INTERFACE SCHEDULE INTERFACE POINT LOCATION													
TP NO	ORGANISATION X	ORGANISATION Y	DESCRIPTION	INTERFACE POINT LOCATION (EQUIPMENT)	INTERFACE POINT TYPE	REFERENCE DWGS/DOCUMENTS	NOTES	REV						
TP - 3001 - E	PS EPC	SSE	Power Station Earthing Tie-Ins	Location of new booster fans Location of Ammonia Storage		PCCS-01-TC-EA-8809-00001 OVERALL EARTHING LAYOUT DRAWING (POWER STATION)	Earthing tie in points for the Power Station are shown on PCCS-01-TC-EA-8809-00001.							
TP - 3002 - E	CCP EPC	SSE		Perimeter of the Carbon Capture plant shown on the drawing	GA	PCCS-02-TC-EA-8809-00001 OVERALL EARTHING LAYOUT DRAWING (CCCC)	Earthing tie in points for the Carbon Capture Plant are shown on PCCS-02-TC-EA-8809-00001.							
TP - 3003 - E	PS EPC	SSE	Modification of Existing HV Switchgear	Locations shown on the drawing	РВ	PCCS-01-TC-EA-2384-00002 UNIT 20 ONE LINE DIAGRAM	Power station contractor is responsible for modification of existing HV Switchgear and connecting new loads as shown on the one line diagram and HV demolition schedule.							
TP - 3004 - E	PS EPC	SSE	Modification of Existing LV Switchgear	Locations shown on the drawing	PB	PCCS-01-TC-EA-2384-00002 UNIT 20 ONE LINE DIAGRAM	Power station contractor is responsible for modification of existing LV Switchgear and connecting new loads as shown LV demolition schedule.							
TP - 3005 - E	CCP EPC	National Grid/SSE	132kV Import Connection	National Grid Substation		PCCS-02-TC-EA-2580-00001 HV AND LV PROTECTION AND METERING DIAGRAM SHEET 22	National grid substation Import cable connection							
TP - 3006 - E	PS EPC	National Grid/SSE	275kV Import Connection	National Grid Substation		PCCS-01-TC-EA-2580-00001 UNIT 20 PROTECTION AND METERING DIAGRAM	National grid substation Import cable connection							
TP - 3007 - E	CCP EPC	SSE	Power Supplies for the Ammonia Storage	GT13 PCC	РВ		New equipment in Ammonia storage area to be supplied from existing LV switchgear.							
TP - 3008 - E	CCP EPC	National Grid/SSE	132kV Protection and Metering Cabinets	National Grid Substation		PCCS-02-TC-EA-2580-00001 HV AND LV PROTECTION AND METERING DIAGRAM SHEET 22	National grid substation replacement of existing protection and metering cabinets and cables.							

CLIENT: SHELL U.K. LTD PROJECT: PETERHEAD CCS (ONSHORE) LOCATION: PETERHEAD, SCOTLAND

DOC. NO.: **CLIENT REF.:** REV:

PCCS-00-TC-AA-6627-00001 K01

	ELECTRICAL INTERFACE SCHEDULE													
TP NO	ORGANISATION X	ORGANISATION Y	DESCRIPTION	INTERFACE POINT LOCATION (EQUIPMENT)	INTERFACE POINT TYPE	REFERENCE DWGS/DOCUMENTS	NOTES	REV						
TP - 3009 - E	PS EPC	National Grid/SSE	275kV Protection and Metering Cabinets	National Grid Substation	PA	PCCS-01-TC-EA-2580-00001 UNIT 20 PROTECTION AND METERING DIAGRAM	National grid substation replacement of existing protection and metering cabinets and cables.							
TP - 3010 - E	PS EPC	SSE	GT13 Electrical Modification and Upgrade Work	GT13 PCC	РВ	Siemens System Study Report	Power supplies required. Siemens are responsible for modifying and updating the existing electrical protection, metering and control systems on GT13 to allow it to operate independent to GT11 and GT12 with the latest operating software and protection relays.							
TP - 3011 - E	PL EPC	CCP	Electrical equipment in the Pigging Compound installed in Compression area	Compression Area (see the plot plan)	PC	Plot Plan Overall CCCC Project Area Plan PCCS-00-TC-MP-4024-00002	Power supplies required. The Offshore pipeline design includes the installation of equipment on shore in the compression area. The pigging compound which is being designed by JP Kenny during the FEED will be supplied from the substation ESS-300, which is in the scope of the CCP EPC contractor.							
TP - 3012 - E	PL EPC	ССР	Electrical equipment in the Nitrogen Package installed in Compression area	Compression Area (see the plot plan)	PC	Plot Plan Overall CCCC Project Area Plan PCCS-00-TC-MP-4024-00002	Connection to main earth sytem by the OS EPC. The Offshore pipeline design includes the installation of equipment on shore in the compression area. The nitrogen package which is being designed by JP Kenny during the FEED will be supplied from the substation ESS-300, which is in the scope of the CCP EPC contractor.							
TP - 3013 - E	PL EPC	ССР	Electrical equipment in the Pigging Compound installed in Compression area	Compression Area (see the plot plan)	GB	Plot Plan Overall CCCC Project Area Plan PCCS-00-TC-MP-4024-00002	The Offshore pipeline design includes the installation of equipment on shore in the compression area. The pigging compound which is being designed by JP Kenny during the FEED will be supplied from the substation ESS-300, which is in the scope of the CCP EPC contractor.							
TP - 3014 - E	PL EPC	ССР	Electrical equipment in the Nitrogen Package installed in Compression area	Compression Area (see the plot plan)	GB	Plot Plan Overall CCCC Project Area Plan PCCS-00-TC-MP-4024-00002	Connection to main earth sytem by the OS EPC. The Offshore pipeline design includes the installation of equipment on shore in the compression area. The nitrogen package which is being designed by JP Kenny during the FEED will be supplied from the substation ESS-300, which is in the scope of the CCP EPC contractor.							

REFERENCE DOCUMENTS:
PCCS-00-TC-AA-6627-00002 - INTERFACE RESPONSIBILITY SPECIFICATION

LEGEND								
PPS EPC	Power Station EPC Contractor							
CCP EPC	Carbon Capture Plant EPC Contractor							
PL EPC	Pipe Line EPC Contractor							

												CLIENT: PROJECT: LOCATION:	SHELL U.K. LTD PETERHEAD CCS (ONSHORI PETERHEAD, SCOTLAND	DOC. NO.: CLIENT REF.: REV:	PCCS-00-TC-AA-662	7-00001 K01
								C&I IN	ITERFACE SCHEDULE			•				
	FROM LOCATION TO LOCATION INTERFACE												REFERENCE			
TP NO	DESCRIPTION	ORG X	FIELD BUILDING	ROOM	CABINET	CABLE MARK	ORG Y	FIELD	BUILDING	ROOM	CABINET	POINT TYPE	DRAWINGS/DOCUMENTS	NOTES		REV
TP - 4001 - I	Fibre Optic Cable connection	CCP EPC	CCS Control Building	Equipment Room	FO Patch Panel	00-ICSSFO-0001	PS EPC		PPS Control Building	Control Room	FO Patch Panel	cs	PCCS-00-TC-IN-0901-00001	6-core, single-mode, a data	moured, fibre-optic cable for exchange of	
TP - 4002 - I	Hard-wired cable connection	CCP EPC	CCS Control Building	PS Control Room	Safety Console	00-ICSSD-0002	PS EPC		PPS Control Building	Control Room	Safety Console	cs	PCCS-00-TC-IN-0901-00001	20-pair, 1.5 mm ² , armo	ured cable for shutdown and status signals	
TP - 4003 - I	BT leased line	CCP EPC	CCS Control Building	Equipment Room	Interface Panel	00-ICSSD-0003	Shell		St Fergus Control Building	Control Room	Interface Cabinet	cs	PCCS-00-TC-IN-0901-00001	Modbus serial connect to St Fergus control ro	ion via BT leased line from CCS control roor om.	n
TP - 4004 - I	BT leased line	CCP EPC	CCS Control Building	Equipment Room	Interface Panel	00-ICSSD-0004	Shell		Shell Tullos Office Building	Control Room	Interface Cabinet	cs	PCCS-00-TC-IN-0901-00001	Modbus serial connect to Shell Tullos Office.	ion via BT leased line from CCS control roor	n
TP - 4005 - I	Broadband link	CCP EPC	CCS Control Building	Communication Room	Broad band Interface Cabinet	00-ICSSD-0005	Shell		Goldeney Control Room	Control Room	Broad band Interface Cabinet	CS	PCCS-00-TC-IN-0901-00001		cabinet incorporating communication module between CCS control room and Goldeneye	
TP - 4006 - I	Hard-wired cable connection	CCP EPC	CCS Control Building	Equipment Room	Safety cabinet	00-ICSSD-0006	PL EPC		Pig Launcher Receiver Package	Field	JB : 01-JBED-4010	CS	PCCS-00-TC-IN-0901-00001	10-pair, 1.5 mm2, arm	oured cable for shutdown and status signals	
TP - 4007 - I	Hard-wired cable connection	CCP EPC	CCS Control Building	Equipment Room	Safety cabinet	00-ICSSD-0007	PL EPC		Pig Launcher Receiver Package	Field	JB : 01-JBEA-4009	CS	PCCS-00-TC-IN-0901-00001	10-pair, 0.75 mm2, arr	noured cable for shutdown and status signal	S
TP - 4008 - I	Hard-wired cable connection	CCP EPC	CCS Control Building	Equipment Room	Control cabinet	00-ICSSD-0008	PL EPC		Pig Launcher Receiver Package	Field	JB : 01-JBPA-4007	CS	PCCS-00-TC-IN-0901-00001	10-pair, 0.75 mm2, arr signals.	noured cable for control and indication	
TP - 4009 - I	Hard-wired cable connection	CCP EPC	CCS Control Building	Equipment Room	Control cabinet	00-ICSSD-0009	PL EPC		Pig Launcher Receiver Package	Field	JB : 01-JBPD-4008	CS	PCCS-00-TC-IN-0901-00001	10-pair, 0.75 mm2, arr signals.	noured cable for control and indication	

REFERENCE DOCUMENTS:
PCCS-00-TC-AA-6627-00002 - INTERFACE RESPONSIBILITY SPECIFICATION

LEGEND								
PPS EPC	Power Station EPC Contractor							
CCP EPC	Carbon Capture Plant EPC Contractor							
PL EPC	Pipe Line EPC Contractor							



Peterhead CCS Project

Doc Title: Interface Responsibility Specification

Doc No. **PCCS-00-TC-AA-6627-00002**

Revision: **K01**

KEYWORDS

Goldeneye, CO₂, Carbon Capture and Storage, Interface.



Table of Contents

1.		Introduction	1
2.		Scope of Document	1
3.		General	1
4.		Mechanical (Piping and Ducting)	1
	4.1.	Piping – Interface Point Type "1"	2
	4.2.	Piping – Interface Point Type "2"	3
	4.3.	Piping – Interface Point Type "3a"	5
	4.4.	Piping – Interface Point Type "3b"	6
	4.5.	Ducting – Interface Point Type "4a"	7
	4.6.	Ducting – Interface Point Type "4b"	9
5.		Electrical	10
	5.1. 5.1.1. 5.1.2. 5.1.3.	Power Distribution Interface Point Type "PA" Interface Point Type "PB" Interface Point Type "PC"	10 10 11 12
	5.2. 5.2.1. 5.2.2.	Grounding System Interface Point Type "GA" Interface Point Type "GB"	13 13 13
	5.3. 5.3.1.	Telecommunication Systems Interface Point Type "CA"	14 14
6.		Control Systems	16
	6.1. 6.1.1.	Control Systems Interface Point Type "CS"	16 16
7.		Civil, Structural and Arquitectural	17
	7.1. 7.1.1. 7.1.2. 7.1.3.	Underground Gravity Interface Points Underground Gravity Lines – Interface Point Type "G1" Underground Gravity Lines – Interface Point Type "G2" Underground Pressure Lines – Interface Point Type "P1"	17 17 18 19
8.		References - Bibliography	20
9.		Glossary of Terms	21
Т	able d	of Figures	
Fi	gure 5-	1:Interface Point at nearest flange/valve	2
Fi	gure 5-	2:Welded Joint	3
	_	3: Piping - I/P at flange at geographical boundary between Packages	5
	_	4: Piping - I/P at weld at geographical boundary between Packages	6
FΪ	gure 5-	5: Ducting - I/P at flange at geographical boundary between Packages	7



Figure 5-6: Ducting - I/P at flange at geographical boundary between Packages	9
Figure 5-7: Power Distribution - Interface Point Type "PA"	10
Figure 5-8: Power Distribution - Interface Point Type "PB"	11
Figure 5-9: Power Distribution - Interface Point Type "PB"	12
Figure 5-10: Underground Gravity Lines – Interface Point Type "G1"	17
Figure 5-11: Underground Gravity Lines – Interface Point Type "G2"	18
Figure 5-12: Underground Pressure Lines – Interface Point Type "P1" Plan View	19
List of Tables	
Table 5-1: Piping - Interface Point Type "1"	2
Table 5-2: Piping - Interface Point Type "2"	4
Table 5-3: Piping - Interface Point Type "3a"	5
Table 5-4: Piping - Interface Point Type "3b"	6
Table 5-5: Ducting - Interface Point Type "4a"	8
Table 5-6: Ducting - Interface Point Type "4b"	9
Table 5-7: Power Distribution - Interface Point Type "PA"	10
Table 5-8: Power Distribution - Interface Point Type "PB"	11
Table 5-9: Power Distribution - Interface Point Type "PB"	12
Table 5-10: Grounding Systems - Interface Point Type "GA"	13
Table 5-11: Grounding Systems - Interface Point Type "GB"	13
Table 5-12: Telecommunication Systems - Interface Point Type "CA"	14
Table 5-13: Control System - Interface Point Type "CS"	16
Table 5-14: Underground Gravity Lines – Interface Point Type "G1"	17
Table 5-15: Underground Gravity Lines – Interface Point Type "G2"	18
Table 5-16: Underground Pressure Lines – Interface Point Type "P1"	19



1. Introduction

The Peterhead CCS Project would be the world's first commercial scale demonstration of CO₂ capture, transport and offshore geological storage from a (post combustion) gas-fired power station. Carbon Capture technology will be fitted to an existing gas-fired power station at Peterhead in North East Scotland, UK, at a site with sufficient space for the construction of the post combustion CO₂ capture plant and the compression and conditioning plant. Approximately one million tonnes of CO₂ will be captured from the flue gas produced by the Peterhead Power Station and stored each year in a depleted Goldeneye reservoir currently operated by Shell. After capture, the CO₂ will be routed to compression, also located at the Peterhead Power Station site, where it will be compressed, cooled and conditioned for water and oxygen removal to meet a suitable transportation and storage specification. Following post-compression cooling the resulting dense phase CO₂ stream will be transported direct offshore via a new offshore pipeline which will tie-in subsea to the existing Goldeneye pipeline. The CO₂ will be permanently stored in an area centered on the depleted Goldeneye gas field.

2. Scope of Document

This document will cover the distribution of responsibilities for the various interfaces and tie-ins for the modifications to the existing SSE Power Generation Plant and the new onshore facilities for carbon capture, compressions and conditioning before it is transported offshore.

3. General

The purpose of this document is to describe the split of works between Packages for each interface point type for piping, control and instrumentations and electrical disciplines. This document clarifies as necessary the split of works during construction, pre-commissioning and commissioning.

4. Mechanical (Piping and Ducting)

The following Interface Point types for aboveground piping are hereby described:

- Type 1
- Type 2
- Type 3a
- Type 3b
- Type 4a
- Type 4b

1

Revision: K01



4.1. Piping - Interface Point Type "1"




Figure 5-1: Interface Point at nearest flange/valve

Table 5-1: Piping - Interface Point Type "1"

PHASE	ITEM	ORG X	ORG Y	REMARKS
Design	Piping upstream of geographical battery limit	X		ORG-X to coordinate and share stress information with ORG-Y
	Piping and flange from geographical battery limit to first isolation valve (where IP is located)		X	ORG-Y to provide isometric drawings to ORG-X to allow purchasing of material
	Piping, flange and valve downstream of IP		X	
Procurement	Piping upstream of geographical battery limit	X		
	Piping and flange from geographical battery limit to first isolation valve (including final gasket on IP)	X		
	Piping, flange, valve, bolts, nuts, spectacle blind (or spacer and slip blind) downstream of IP		X	
Construction	Erection and hydrotest of piping upstream of IP	X		For utilities, block valve is given by ORG-Y to ORG-X for installation
				Including supply, removal and disposal of water
	Erection and hydrotest of piping downstream of IP		X	Including supply, removal and disposal of water

Doc. no.: PCCS-00-TC-AA-6627-00002, Interface Responsibility Specification




PHASE	ITEM	ORG X	ORG Y	REMARKS
Pre-commissioning	Pre-commissioning (air blowing or water flushing, etc.) of piping upstream of IP	X		Including the installation of final gasket on IP and tightening of valve and flange at IP.
	Pre-commissioning (air blowing or water flushing, etc.) of piping downstream of IP		X	
Commissioning	Commissioning (tightness test, nitrogen purging, etc.) of piping upstream of IP	X		
	Commissioning (tightness test, nitrogen purging, etc.) of piping downstream of IP		X	

NOTE 1: In above matrix, ORG-Y is defined as the Contractor with isolation valve in its own scope of work, while ORG-X is the other Contractor.

NOTE 2: In above matrix, the term "upstream" refers to ORG-X, while "downstream" refers to ORG-Y.

NOTE 3: Each Contractor shall be responsible for painting, insulation and heat tracing up to the interface point.

4.2. Piping – Interface Point Type "2"



packages

Figure 5-2: Welded Joint



Table 5-2: Piping - Interface Point Type "2"

PHASE	ITEM	ORG X	ORG Y	REMARKS
Design	Piping upstream of geographical battery limit	X		ORG-X to coordinate and share stress information with ORG-Y
	Piping downstream of geographical battery limit		X	
Procurement	Piping upstream of geographical battery limit	X		
	Piping downstream of geographical battery limit		X	
Construction	Erection of piping upstream of geographical battery limit	X		
	Erection and hydrotest downstream of IP up to first valve or flange		X	ORG-Y to test his portion to allow ORG-X to make the overall test including supply, removal and disposal of water
	Welding of piping at geographical battery limit	X		After ORG-Y has hydrotested his piping and removed the test cap (or flange and blind)
	Hydrotest of piping upstream and downstream of IP up to first valve or flange		X	Including supply, removal and disposal of water
Pre-commissioning	Pre-commissioning (Air blowing or water flushing, etc.) of piping upstream and downstream of IP up to first valve or flange	X	X	ORG-Y to carry out the final reinstatement (after pre-commissioning) of its own piping downstream of IP
	Pre-commissioning (Air blowing or water flushing, etc.) of piping downstream of first valve or flange		X	
Commissioning	Commissioning (tightness test, nitrogen purging, etc.) of piping upstream and downstream of IP up to first valve	X	X	ORG-Y to check and fix eventual leaks of its own piping downstream of IP
	Commissioning (tightness test, nitrogen purging, etc.) of piping downstream of first valve		X	

NOTE 1: In above matrix, ORG-Y is defined as the Contractor with <u>closest</u> isolation valve in its own scope of work, while ORG-X is the other Contractor.

NOTE 2: In above matrix, the term "upstream" refers to ORG-X, while "downstream" refers to ORG-Y.

NOTE 3: Each Contractor shall be responsible for painting, insulation and heat tracing up to the interface point.



4.3. Piping – Interface Point Type "3a"




Figure 5-3: Piping - I/P at flange at geographical boundary between Packages

Table 5-3: Piping - Interface Point Type "3a"

PHASE	ITEM	ORG X	ORG Y	REMARKS
Design	Piping and flange upstream of IP	X		ORG-X to coordinate and share stress information with ORG-Y
	Piping and flange downstream of IP		X	
Procurement	Piping and flange (including spectacle blind or spacer and slip blind) upstream of IP	X		
	Piping and flange (including bolts, nuts and final gasket) downstream of IP		X	
Construction	Erection and hydrotest upstream of IP	X		Including supply, removal and disposal of water
	Erection and hydrotest downstream of IP		X	Including supply, removal and disposal of water
Pre-commissioning	Pre-commissioning (air blowing or water flushing, etc.) of piping upstream of IP	X		
	Pre-commissioning (air blowing or water flushing, etc.) of piping downstream of IP		X	Including final reinstatement of flange at IP
Commissioning	Commissioning (tightness test, nitrogen purging, etc.) of piping upstream and downstream of IP up to first valve	X	X	ORG-Y to check and fix eventual leaks of its own piping downstream of IP

Doc. no.: PCCS-00-TC-AA-6627-00002, Interface Responsibility Specification



PHASE	ITEM	ORG X	ORG Y	REMARKS
	Commissioning (tightness test, nitrogen purging, etc.) of piping downstream of first valve		X	

NOTE 1: In above matrix, ORG-Y is defined as the Contractor with <u>closest</u> isolation valve in its own scope of work, while ORG-X is the other Contractor.

NOTE 2: In above matrix, the term "upstream" refers to ORG-X, while "downstream" refers to ORG-Y.

NOTE 3: Each Contractor shall be responsible for painting, insulation and heat tracing up to the interface point

4.4. Piping – Interface Point Type "3b"




Figure 5-4: Piping - I/P at weld at geographical boundary between Packages

Table 5-4: Piping - Interface Point Type "3b"

PHASE	ITEM	ORG X	ORG Y	REMARKS
Design	Piping upstream of IP	X		ORG-X to coordinate and share stress information with ORG-Y
	Piping downstream of IP		X	
Procurement	Piping upstream of IP	X		
	Piping downstream of IP		X	
Construction	Erection upstream of IP	X		
	Erection and hydrotest downstream of IP up to first valve or flange		X	ORG-Y to test his portion to allow ORG-X to make the overall test, including supply, removal and disposal of water
	Welding of piping at geographical battery limit	X		After ORG-Y has hydrotested his piping and removed the test cap (or flange or

Doc. no.: PCCS-00-TC-AA-6627-00002, Interface Responsibility Specification

Revision: K01



PHASE	ITEM	ORG X	ORG Y	REMARKS
				blind)
	Hydrotest of piping upstream and downstream of IP up to first valve or flange		X	Including supply, removal and disposal of water
Pre-commissioning	Pre-commissioning (air blowing or water flushing, etc.) of piping upstream and downstream of IP up to first valve or flange	X	X	ORG-Y to carry out the final reinstatement (after pre-commissioning) of its own piping downstream of IP
	Pre-commissioning (air blowing or water flushing, etc.) of piping downstream of first valve or flange		X	
Commissioning	Commissioning (tightness test, nitrogen purging, etc.) of piping upstream and downstream of IP up to first valve	X	X	ORG-Y to check and fix eventual leaks of its own piping downstream of IP
	Commissioning (tightness test, nitrogen purging, etc.) of piping downstream of first valve		X	

NOTE 1: In above matrix, ORG-Y is defined as the Contractor with <u>closest</u> isolation valve in its own scope of work, while ORG-X is the other Contractor.

NOTE 2: In above matrix, the term "upstream" refers to ORG-X, while "downstream" refers to ORG-Y.

NOTE 3: Each Contractor shall be responsible for painting, insulation and heat tracing up to the interface point

4.5. Ducting - Interface Point Type "4a"




Figure 5-5: Ducting - I/P at flange at geographical boundary between Packages



Table 5-5: Ducting - Interface Point Type "4a"

PHASE	ITEM	ORG X	ORG Y	REMARKS
Design	Ducting, flange and expansion joint upstream of IP	X		ORG-X to coordinate and share stress information with ORG-Y
	Ducting and flange downstream of IP		X	
Procurement	Ducting, flange and expansion joint upstream of IP	X		
	Ducting and flange (including bolts, nuts and final gasket) downstream of IP		X	
Construction	Erection and tightness test upstream of IP	X		
	Erection and tightness test downstream of IP		X	
Pre-commissioning	Pre-commissioning (air blowing or water flushing, etc.) of ducting upstream of IP	X		
	Pre-commissioning (air blowing or water flushing, etc.) of ducting downstream of IP		X	Including final reinstatement of flange at IP
Commissioning	Commissioning (tightness test, nitrogen purging, etc.) of ducting upstream and downstream of IP	X	X	ORG-Y to check and fix eventual leaks of its own ducting downstream of IP
	Commissioning (tightness test, nitrogen purging, etc.) of ducting downstream		X	

NOTE 1: In above matrix, the term "upstream" refers to ORG-X, while "downstream" refers to ORG-Y.

NOTE 2: Each Contractor shall be responsible for painting and insulation up to the interface point



4.6. Ducting - Interface Point Type "4b"




Figure 5-6: Ducting - I/P at flange at geographical boundary between Packages

Table 5-6: Ducting - Interface Point Type "4b"

PHASE	ITEM	ORG X	SSE	REMARKS
Design	Ducting, flange and expansion joint upstream of IP	X		ORG-X to coordinate and share stress information with ORG-Y
	Ducting and flange downstream of IP		X	Existing boiler duct within stack
Procurement	Ducting, flange (including bolts, nuts and final gasket) and expansion joint upstream of IP	X		
	Ducting and flange downstream of IP		X	Existing boiler duct within stack
Construction	Erection and tightness test upstream of IP	X		
	Erection and tightness test downstream of IP	X		
Pre-commissioning	Pre-commissioning (air blowing or water flushing, etc.) of ducting upstream of IP	X		
	Pre-commissioning (air blowing or water flushing, etc.) of ducting downstream of IP	X		Including final reinstatement of flange at IP
Commissioning	Commissioning (tightness test, nitrogen purging, etc.) of ducting upstream and downstream of IP	X		
	Commissioning (tightness test,	X		



PHASE	ITEM	ORG X	SSE	REMARKS
	nitrogen purging, etc.) of ducti downstream of IP	ng		

NOTE 1: In above matrix, ORG-Y is defined as SSE, while ORG-X is the CCP EPC.

NOTE 2: In above matrix, the term "upstream" refers to ORG-X, while "downstream" refers to ORG-Y.

NOTE 3: Org X shall be responsible for painting and insulation.

5. Electrical

The following Interface Point types are hereby described:

- Power Distribution Type PA, PB
- Grounding System Type GA
- Telecommunication Systems Type CA

5.1. Power Distribution

5.1.1.Interface Point Type "PA"




Figure 5-1: Power Distribution - Interface Point Type "PA"

Table 5-1: Power Distribution - Interface Point Type "PA"

PHASE	ITEM	ORG X	NATIONAL GRID	REMARKS
Design	Cable routing up to IP.	X		
	Cables, terminals and accessories up to IP.	X		
Procurement	Cables, terminals and accessories up to IP.	X		Including termination kits.
Construction	Cable trenching and cable rack up to IP.	X		Including trench backfilling after cables laying and testing is completed.
	Cables (both power and control)	X		Including cables continuity test.

Doc. no.: PCCS-00-TC-AA-6627-00002, Interface Responsibility Specification



PHASE	ITEM	ORG X	NATIONAL GRID	REMARKS
	laying in trenches or on rack up to IP.			
	Cables termination and physical connection to equipment.	X		ORG X shall be responsible for terminating at both ends.
Testing	Equipment (transformers, switchgear, etc.) and cables.	X	X	ORG-X will lead and coordinate the test phase.

5.1.2. Interface Point Type "PB"




Figure 5-2: Power Distribution - Interface Point Type "PB"

Table 5-2: Power Distribution - Interface Point Type "PB"

PHASE	ITEM	ORG X (PS EPC)	ORG Y (SSE)	REMARKS
Design	Cable routing in its plant area	X		
	Cables, terminals and accessories up to IP.	X		
	Modifications to switchgear	X		
Procurement	Cables, terminals and accessories up to IP.	X		Including termination kits.
	Equipment upstream of IP, i.e. modification to switchgear.	X		
Construction	Cable trenching / racking in its plant area	X		Including backfilling after cable laying is completed.
	Cable laying in trenches / on	X		Including cables continuity test.

Doc. no.: PCCS-00-TC-AA-6627-00002, Interface Responsibility Specification

Revision: K01

PHASE	ITEM	ORG X (PS EPC)	ORG Y (SSE)	REMARKS
	racking up to IP. Cables termination and physical connection to equipment.	X		ORG X shall be responsible for terminating at both ends.
Testing	Equipment (transformers, switchgear, etc.) and cables.	X	X	ORG-X will lead and coordinate the test phase.

NOTE 1: In above matrix, ORG-X is defined as the Power Station EPC Contractor with electrical equipment, while ORG-Y is SSE.

NOTE 2: In above matrix, the term "downstream" refers to ORG-X, while "upstream" refers to ORG-Y.




Figure 5-3: Power Distribution - Interface Point Type "PB"

Table 5-3: Power Distribution - Interface Point Type "PB"

PHASE	ITEM	ORG X (OS EPC)	ORG Y (CCP EPC)	REMARKS
Design	Cable routing in its plant area		X	Cable routes to the substation to be designed by ORG Y.
	Cables, terminals and accessories up to IP.	X		
	Design of switchgear		X	Design of all switchgear by ORG Y
Procurement	Cables, terminals and accessories up to IP.	X		
	Equipment upstream of IP, i.e.		X	Supply of switchgear by ORG Y

Doc. no.: PCCS-00-TC-AA-6627-00002, Interface Responsibility Specification



PHASE	ITEM	ORG X	ORG Y	REMARKS
		(OS EPC)	(CCP EPC)	
	modification to switchgear.			
Construction	Cable trenching / racking in its plant area		X	
	Cable laying in trenches / on racking up to IP.	X		Including cables continuity test.
	Cables termination and physical connection to equipment.	X		ORG X shall be responsible for terminating at both ends.
Testing	Equipment (transformers, switchgear, etc,) and cables.	X	X	ORG-X will lead and coordinate the test phase.

NOTE 1: In above matrix, ORG-X is defined as the Offshore EPC Contractor with electrical equipment, while ORG-Y is the on shore Carbon Capture Plant EPC contractor.

NOTE 2: In above matrix, the term "downstream" refers to ORG-X, while "upstream" refers to ORG-Y.

5.2. Grounding System

5.2.1. Interface Point Type "GA"

Table 5-4: Grounding Systems - Interface Point Type "GA"

PHASE	ITEM	ORG-X	ORG-Y (SSE)	REMARKS
Design	Earthing grid	X		Including analysis of overall system to meet appropriate standards.
Procurement	Earthing grid	X		
Construction	Earthing grid	X		Including connection to existing main earthing system.
Testing	Earthing grid	X		

5.2.2. Interface Point Type "GB"

Table 5-5: Grounding Systems - Interface Point Type "GB"

PHASE	ITEM	ORG-X (OS EPC)	ORG-Y (CCP EPC)	REMARKS
Design	Earthing grid	X		For the equipment they will be supplying and

Doc. no.: PCCS-00-TC-AA-6627-00002, Interface Responsibility Specification

Revision: K01



PHASE	ITEM	ORG-X (OS EPC)	ORG-Y (CCP EPC)	REMARKS
				installing only
Procurement	Earthing grid	X		Materials to the point of interface and to connect on to the main grid designed by ORG Y.
Construction	Earthing grid	X		Including connection to existing main earthing system.
Testing	Earthing grid	X		

5.3. Telecommunication Systems

5.3.1. Interface Point Type "CA"

Table 5-6: Telecommunication Systems - Interface Point Type "CA"

PHASE	ITEM	ORG X	ORG Y	REMARKS
Design	Each Contractor shall provide power supply and the Telecom Power Distribution Panels (PDP) within their Battery Limits.	X		
	Contractor shall be responsible for Design of: - Power cable for the supply of Telecom UPS - Telecom UPS - Power cable from UPS to the Telecom Power Distribution Panels (PDP). - Telecom Power Distribution Panels (PDP).	X		
	Telecom UPS and PDP sizing requirements for design shall be provided by ORG-Y		X	
Procurement	Contractor shall be responsible for procurement of: - Power cable for the supply of Telecom UPS - Telecom UPS - Power cable from UPS to the	X		
	Telecom Power Distribution			



PHASE	ITEM	ORG X	ORG Y	REMARKS
	Panels (PDP). - Telecom Power Distribution Panels (PDP).			
Construction	Contractor shall be responsible for installation of: - Power cable for the supply of Telecom UPS - Telecom UPS - Power cable from UPS to the Telecom Power Distribution Panels (PDP). - Telecom Power Distribution Power Distribution Panels (PDP).	X		

NOTE 1: In above table, ORG-X is either the Power Station or Carbon Capture Plant EPC Contractor, ORG-Y is either SSE, Shell or the Power Station EPC Contractor.



6. Control Systems

6.1. Control Systems

6.1.1. Interface Point Type "CS"

Table 5-1: Control System - Interface Point Type "CS"

PHASE	ITEM	ORG X	ORG Y	REMARKS
Design	Each Contractor shall be responsible for the cable routing within its battery limit.	X	X	
	One Contractor shall be responsible for the interconnecting cabling between battery limits	X		
	Each Contractor shall be responsible for the control system design within its battery limits.	X	X	
Procurement	Each Contractor shall be responsible for the control system and cabling procurement within its battery limits.	X	X	
	One Contractor shall be responsible for the interconnecting cabling procurement between battery limits.	X		
Construction	Each Contractor shall be responsible for the civil works (cable trench or cable racking) within its battery limit.	X	X	
	Each Contractor shall be responsible for the control system installation within its battery limits.	X	X	
	One Contractor is responsible for laying the Data Signals Hard Wired/Fibre Optic/Serial Link from the Carbon Capture Control Room to the Power	X		



PHASE	ITEM	ORG X	ORG Y	REMARKS
	Station Control Room.			
Testing	Control System	X	X	ORG-X will lead and coordinate the test phase.

7. Civil, Structural and Arquitectural

7.1. Underground Gravity Interface Points

7.1.1. Underground Gravity Lines – Interface Point Type "G1"




Figure 5-1: Underground Gravity Lines – Interface Point Type "G1"

Table 5-1: Underground Gravity Lines – Interface Point Type "G1"

PHASE	ITEM	EPC-X	REMARKS
Design	Piping up to IP	X	
Procurement	Piping up to IP	X	
Construction	Erection of piping up to IP	X	Including the encasing of pipe in pit Including any required test on piping before pit- to-pit test
	Pit-to-pit test of piping	X	Including supply, removal and disposal of water
Pre-	Manual cleaning of pit at	X	
Commissioning	NA		



7.1.2. Underground Gravity Lines – Interface Point Type "G2"




Figure 5-2: Underground Gravity Lines – Interface Point Type "G2"

Table 5-2: Underground Gravity Lines – Interface Point Type "G2"

PHASE	ITEM	EPC-X	REMARKS
Design	Piping up to IP including pit		
Procurement	Piping up to IP	X	Including materials for pit
	Erection of piping up to IP	X	Including construction of pit
	Pit-to-pit test of piping up to IP	X	Including supply, removal and disposal of water
Construction	Erection of piping up to IP including pit		Including the sealing of EPC-A pipe in pit Including any required
	Pit-to-pit test of piping up to IP		Including supply, removal and disposal of water
Pre-commissioning	Manual cleaning of pit at IP		
Commissioning	NA		



7.1.3. Underground Pressure Lines – Interface Point Type "P1"




Figure 5-3: Underground Pressure Lines – Interface Point Type "P1" Plan View

Table 5-3: Underground Pressure Lines – Interface Point Type "P1"

PHASE	ITEM	EPC-X	REMARKS
Design	Piping from IP	X	
Procurement	Piping up to IP	X	Including supply of
	Isolated existing pipeline	X	Including temporary by-pass if required
	Erection and hydrotest up to IP	X	Including the supply, removal and disposal of
	Trench backfilling up to IP	X	Including trench
Pre-commissioning	Water flushing of piping upstream and downstream of IP up to first valve or flanged	X	Including the supply, removal and disposal of
Commissioning	Removal of any temporary works, by-passes, etc.	X	



References - Bibliography

PCCS-00-TC-AA-6627-00001

Interface Schedule



Glossary of Terms

Term	Definition
CCP	Carbon Capture Plant
CCS	Carbon Capture and Storage
EPC	Engineering, Procurement and Construction
IP	Intermediate Pressure
ORG	Organisation
PDP	Power Distribution Panels
UPS	Uninterruptable Power Supply

