

Normal, completed test failures with one or more Fail or PRS type RfR within 'Tyres' grouping

2007/08

RfR ID	Component	RfR Description	Apr-07	May-07	Jun-07	Jul-07	Aug-07	Sep-07	Oct-07	Nov-07	Dec-07	Jan-08	Feb-08	Mar-08	Total	% Tests Failing for one or more incidences of RfR
8374	Tyre(s) type	One tyre is of a different nominal size or aspect ratio to any other on the same axle.	3474	3705	3534	3591	3480	3474	3769	3401	2378	3622	3677	3630	41735	0.2%
8376	Tyre(s) type	One tyre is of a different nominal size or aspect ratio to any other on the same axle.	384	422	419	435	434	405	465	402	268	420	423	433	4910	0.0%
8378	Tyre(s) type	one tyre is of a different type of structure from another tyre on the same axle	59	72	62	81	57	57	74	51	40	64	54	72	743	0.0%
8380	Tyre(s) type	a 3- or 4-wheeled vehicle fitted with single wheels and a cross-ply or bias-belted tyre fitted on rear axle and radial-ply tyre on front axle.	2	3	4	6	5	3	4			4	2	4	37	0.0%
8382	Tyre(s) type	a 3- or 4-wheeled vehicle fitted with single wheels and a cross-ply tyre fitted on rear axle and a bias-belted tyre on front axle.				1	1	1	2			1		2	8	0.0%
8383	Tyre(s) type	Special lightweight or space saving wheels and tyres fitted as a road wheel	178	187	184	193	169	178	230	196	159	228	244	241	2387	0.0%
8384	Tyre(s) condition	a tyre has a cut the length of which is at least 25 mm or 10% of section width, whichever is greater, deep enough to reach the ply or cords	11845	13031	12293	12411	12497	12472	13210	10792	6964	10396	11691	13947	141549	0.6%
8385	Tyre(s) condition	a tyre has any of its ply or cords exposed	10182	11194	11087	11622	11527	11777	12619	10682	6775	10682	10473	12123	130743	0.5%
8386	Tyre(s) condition	a re-cut tyre fitted to a vehicle not permitted to be so equipped	50	56	60	50	47	43	55	47	33	38	34	38	551	0.0%
8387	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	5078	5228	4847	4786	4653	4519	4559	3933	2458	4078	4673	5233	54045	0.2%
8388	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	5324	5586	5184	5095	5041	4958	5028	4236	3000	4932	5395	6218	59997	0.2%
8389	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	2479	2725	2631	2564	2629	2542	2720	2173	1378	2068	2521	2813	29243	0.1%
8390	Tyre(s) condition	a tyre incorrectly seated on the wheel rim	127	128	136	117	139	129	124	133	78	115	127	138	1491	0.0%
8391	Tyre(s) condition	a tyre not fitted in compliance with the manufacturers sidewall instruction, e.g. as asymmetric with a sidewall marked 'outer' fitted with the marking to the inner side of the wheel	2854	3111	3060	3202	3012	3025	3420	2897	1994	3024	3135	3451	36185	0.1%
8392	Tyre(s) condition	Tyres on twin wheels making wall contact due to under-inflation or incorrect fitment.	32	28	17	22	25	20	27	21	15	21	16	23	267	0.0%
8393	Tyre(s) condition	A tyre fouling a part of the vehicle	1009	1031	979	971	1034	1006	1109	1018	523	796	894	849	11219	0.0%
8394	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	86410	96152	93336	97091	92562	93148	101925	88820	60966	97777	96184	105866	1110237	4.5%
8395	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	129	134	167	108	108	129	142	122	80	108	115	129	1471	0.0%
8396	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	18	37	26	25	24	42	44	37	25	50	45	44	417	0.0%
8397	Tyre(s) valve stem	a seriously damaged or misaligned valve stem which could cause sudden deflation of the tyre	216	300	257	278	279	250	271	238	153	278	253	308	3081	0.0%
8398	Tyre(s) valve stem	a seriously damaged or misaligned valve stem which could cause sudden deflation of the tyre	106	140	153	140	140	117	130	126	89	124	127	159	1551	0.0%
8587	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	217	261	259	238	195	206	189	171	110	190	174	222	2432	0.0%
8588	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	41	43	45	56	52	57	54	52	38	55	60	52	605	0.0%
8589	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	1634	1870	1825	1857	1667	1694	1880	1563	1121	1705	1583	1856	20255	0.1%
8590	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	97	78	75	93	89	62	107	66	43	61	47	49	867	0.0%
8591	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	3	3	1	4	2	5	1	1		1	5	11	37	0.0%
8592	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	6	8	4	7	6	5	4	2				1	43	0.0%
8593	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	3		1	1	1	1	1	3	1	2			14	0.0%

Total MOT Tests	2058553	2216639	2159429	2173445	2174103	2226252	2224403	1875678	1290823	2067855	2066769	2365326	24899275
-----------------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	----------

2008/09

RfR ID	Component	RfR Description	Apr-08	May-08	Jun-08	Jul-08	Aug-08	Sep-08	Oct-08	Nov-08	Dec-08	Jan-09	Feb-09	Mar-09	Total	% Tests Failing for one or more incidences of RfR
8374	Tyre(s) type	One tyre is of a different nominal size or aspect ratio to any other on the same axle.	3982	3765	3682	3865	3899	4965	5334	4380	3610	5025	4786	5817	53110	0.2%
8376	Tyre(s) type	One tyre is of a different nominal size or aspect ratio to any other on the same axle.	530	488	445	507	539	640	660	560	421	625	630	720	6765	0.0%
8378	Tyre(s) type	one tyre is of a different type of structure from another tyre on the same axle	83	76	78	74	85	76	85	75	68	62	87	98	947	0.0%
8380	Tyre(s) type	a 3- or 4-wheeled vehicle fitted with single wheels and a cross-ply or bias belted tyre fitted on rear axle and radial-ply tyre on front axle.	6	3	2	4	5	4	5	6	3	5	5	2	50	0.0%
8382	Tyre(s) type	a 3- or 4-wheeled vehicle fitted with single wheels and a cross-ply tyre fitted on rear axle and a bias-belted tyre on front axle.		2		3		2		1		2	2	1	13	0.0%
8383	Tyre(s) type	Special lightweight or space saving wheels and tyres fitted as a road wheel	263	233	245	291	254	357	409	341	309	425	395	493	4015	0.0%
8384	Tyre(s) condition	a tyre has a cut the length of which is at least 25 mm or 10% of section width, whichever is greater, deep enough to reach the ply or cords	15017	14754	15036	15583	16509	22390	22166	17016	12936	16707	16629	24844	209587	0.8%
8385	Tyre(s) condition	a tyre has any of its ply or cords exposed	13234	13157	13732	14831	15401	21044	20997	16106	12285	15788	14887	20622	192084	0.8%
8386	Tyre(s) condition	a re-cut tyre fitted to a vehicle not permitted to be so equipped	52	48	53	49	60	66	74	54	26	45	55	62	644	0.0%
8387	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	5336	5478	5301	5375	5339	7200	7037	5346	4220	5814	6458	9393	72297	0.3%
8388	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	6373	6166	5801	5997	6050	8184	7969	6287	5199	7360	7754	10851	83991	0.3%
8389	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	3223	3381	3425	3642	3709	5107	5231	3817	2840	3718	3759	5564	47416	0.2%
8390	Tyre(s) condition	a tyre incorrectly seated on the wheel rim	127	133	131	131	134	192	206	158	134	171	166	229	1912	0.0%
8391	Tyre(s) condition	a tyre not fitted in compliance with the manufacturers sidewall instruction, e.g. as asymmetric with a sidewalk marked 'outer' fitted with the marking to the inner side of the wheel	3838	3578	3654	3789	3961	5280	5558	4434	3508	4653	4751	6309	53313	0.2%
8392	Tyre(s) condition	Tyres on twin wheels making wall contact due to under-inflation or incorrect fitment.	18	23	21	28	29	29	30	28	14	21	33	33	307	0.0%
8393	Tyre(s) condition	A tyre fouling a part of the vehicle	1026	1064	1106	1126	1120	1376	1512	1077	797	1041	1060	1467	13772	0.1%
8394	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	107264	99506	99077	106933	110881	152280	154288	126594	101940	138849	129120	159722	1486454	5.8%
8395	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	135	145	135	183	197	245	239	206	125	143	116	158	2027	0.0%
8396	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	52	27	27	37	33	48	58	61	42	26	26	34	471	0.0%
8397	Tyre(s) valve stem	a seriously damaged or misaligned valve stem which could cause sudden deflation of the tyre	297	269	308	297	294	418	417	390	287	458	381	479	4295	0.0%
8398	Tyre(s) valve stem	a seriously damaged or misaligned valve stem which could cause sudden deflation of the tyre	182	169	157	156	200	251	260	274	232	317	267	357	2822	0.0%
8587	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	206	183	193	189	188	248	299	244	205	258	206	238	2657	0.0%
8588	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	43	45	53	54	47	35	57	59	44	63	64	84	648	0.0%
8589	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	1850	1783	1723	1767	1880	2442	2641	2135	1683	2066	2000	2373	24343	0.1%
8590	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	52	56	60	75	79	117	121	82	64	65	98	83	952	0.0%
8591	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	3	11	1	7	5	3	4	5	3	4	3	1	50	0.0%
8592	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area			1	1									2	0.0%
8593	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	6			1			2		1	1		1	12	0.0%

Total MOT Tests	2303614	2201226	2159469	2247002	2048059	2423784	2230773	1796370	1432074	2024794	2002876	2654887	25524928
-----------------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	---------	----------

2009/10

RfR ID	Component	RfR Description	Apr-09	May-09	Jun-09	Jul-09	Aug-09	Sep-09	Oct-09	Nov-09	Dec-09	Jan-10	Feb-10	Mar-10	Total	% Tests Failing for one or more incidences of RfR
8374	Tyre(s) type	One tyre is of a different nominal size or aspect ratio to any other on the same axle.	5341	5115	5448	5364	4737	5349	5304	4686	3683	4773	5299	6428	61527	0.2%
8376	Tyre(s) type	One tyre is of a different nominal size or aspect ratio to any other on the same axle.	620	652	677	723	594	732	687	566	434	598	619	761	7663	0.0%
8378	Tyre(s) type	one tyre is of a different type of structure from another tyre on the same axle	90	79	98	76	83	88	94	78	48	52	78	82	946	0.0%
8380	Tyre(s) type	a 3- or 4-wheeled vehicle fitted with single wheels and a cross-ply or bias belted tyre fitted on rear axle and radial-ply tyre on front axle.	7	6	3	5	6	5	5	2	3	3	3	6	54	0.0%
8382	Tyre(s) type	a 3- or 4-wheeled vehicle fitted with single wheels and a cross-ply tyre fitted on rear axle and a bias-belted tyre on front axle.	1	2	1	3	4	1	1	1		1		1	16	0.0%
8383	Tyre(s) type	Special lightweight or space saving wheels and tyres fitted as a road wheel	416	400	427	404	358	412	443	438	386	512	515	629	5340	0.0%
8384	Tyre(s) condition	a tyre has a cut the length of which is at least 25 mm or 10% of section width, whichever is greater, deep enough to reach the ply or cords	22692	21933	24279	23183	20996	25883	22964	17955	12565	14558	17282	26505	250795	1.0%
8385	Tyre(s) condition	a tyre has any of its ply or cords exposed	19844	19804	22467	22566	20253	25507	23055	18266	13577	15773	16960	24313	242385	0.9%
8386	Tyre(s) condition	a re-cut tyre fitted to a vehicle not permitted to be so equipped	42	71	68	51	65	59	60	32	23	33	32	46	582	0.0%
8387	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	8150	7675	7952	7488	6446	7625	6754	5269	3920	5281	6647	10389	83596	0.3%
8388	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	9443	8550	9143	8733	7536	9028	7911	6652	4878	6763	8768	13412	100817	0.4%
8389	Tyre(s) condition	a tyre has a lump, bulge or tear caused by separation or partial failure of its structure. This includes any lifting of the tread rubber	5205	5088	5495	5276	4639	5235	4908	3811	2626	2968	3585	5521	54357	0.2%
8390	Tyre(s) condition	a tyre incorrectly seated on the wheel rim	167	165	180	174	166	189	167	134	123	129	166	208	1968	0.0%
8391	Tyre(s) condition	a tyre not fitted in compliance with the manufacturers sidewall instruction, e.g. as asymmetric with a sidewalk marked 'outer' fitted with the marking to the inner side of the wheel	5635	5562	5891	5765	5073	6016	5828	4963	3564	4564	5138	6933	64932	0.2%
8392	Tyre(s) condition	Tyres on twin wheels making wall contact due to under-inflation or incorrect fitment.	29	41	32	26	41	34	31	29	17	17	18	43	358	0.0%
8393	Tyre(s) condition	A tyre fouling a part of the vehicle	1471	1385	1503	1523	1258	1529	1421	1068	768	914	1057	1451	15348	0.1%
8394	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	138796	134284	143172	144160	125342	149841	143161	123562	95185	124598	133110	170631	1625842	6.2%
8395	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	164	164	175	164	150	187	167	136	123	145	172	185	1932	0.0%
8396	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	21	45	31	39	34	36	33	31	27	33	43	56	429	0.0%
8397	Tyre(s) valve stem	a seriously damaged or misaligned valve stem which could cause sudden deflation of the tyre	417	420	434	442	389	469	436	339	255	336	419	496	4852	0.0%
8398	Tyre(s) valve stem	a seriously damaged or misaligned valve stem which could cause sudden deflation of the tyre	295	300	314	351	329	351	349	277	214	288	280	380	3728	0.0%
8587	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	213	228	236	235	226	255	198	187	156	213	240	286	2673	0.0%
8588	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area	76	63	95	71	47	57	70	38	36	44	57	75	729	0.0%
8589	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	2099	2120	2264	2268	1883	2163	2095	1811	1416	1783	1914	2409	24225	0.1%
8590	Tyre tread pattern	The grooves of the tread pattern are not at least 1.6mm throughout a continuous band comprising the central three-quarters of the breadth of tread, and round the entire outer circumference of the tyre	88	75	92	75	59	80	111	82	80	96	84	130	1052	0.0%
8591	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area and the depth of which is not at least 1mm throughout a single band round the entire outer circumference of the tyre of at least three-quarters of the breadth of tread	4		1	3	3	4	1	4			2	1	23	0.0%
8592	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area								1			1		2	0.0%
8593	Tyre tread pattern	A tyre with a tread pattern not visible over the whole tread area			1					1				1	5	0.0%

Total MOT Tests

2255399

2188057

2318421

2274029

2055775

2523203

2238080

1868800

1433701

1920873

2074608

2884304

26035250