

EU Type Examination Certificate Number: 0120/SGS0430

Gacia Electrical Appliance Co., LTD.

No.1 Nanxijiang Road Daqiao Industrial Zone Yueqing, Wenzhou China

Instrument Identification:

N8DM-34 Series

Polyphase, Active Import / Export (kWh), Indoor, Electricity Meter

Instrument Traceable Number 0120/SGS0430

has been assessed and certified as meeting the requirements of

EU Directive 2014/32/EU

on Measuring Instruments Annex II, Module B

It is certified that the manufacturer's technical design and specimen for the above instrument has been examined and, based on the evidence submitted, it is considered that the instrument conforms to the requirements of Annex V of EU Directive 2014/32/EU

This certificate must be used in conjunction with a certificate covering the product verification as required in Annex II, Module D or Annex II, Module F

This certificate is valid until 5th January 2025 Issue 1

Certification is based on report number(s) SHES130800321501 dated 26th December 2014 EMA198278/1 dated 26th December 2014 EMA198278/2 dated 21st June 2016 EMA275962

Authorised Signature

#P

SGS United Kingdom Limited, Notified Body 0120 Unit 202B Worle Parkway, Weston-super-Mare, BS22 6WA, UK t +44 (0)1934 522917 f +44 (0)1934 522137 www.sgs.com

Contact Address

SGS United Kingdom Limited, Units 12A & 12B, South Industrial Estate, Bowburn, Durham, DH6 5AD, UK t +44 (0)191 377 2000 f +44 (0)191 377 2020 www.sgs.com

DU_CST-ME-002 Rev 2 EU Type Examination Cert.



0120/SGS0430

Issue Number: 1 Dated: 9th April 2020

1. Technical Data

Manufacturer	Gacia Electrical Appliance Co., LTD				
Meter Type	N8DM-34Standard, N8DM-34MT, N8DM-34Modbus, N8DM-34Mbus, N8DM-34Pulse, N8DM-34-2T				
Voltage Rating (Un)	3x230/400V				
Current Rating (Imin – Iref (Imax))	0.5-10(100)A & 0.5-10(80)A				
Frequency (Fn)	50Hz				
Active Accuracy Class (kWh)	A or B (kWh)				
Type of circuit	3p4w, 3p3w, 1p2w				
Temperature Range	-25°C to +55°C				
Software/ Firmware Version No	N8DM-34Standard, N8DM-34MT, N8DM-34Modbus,				
CRC Checksum	N8DM-34Mbus, N8DM-34Pulse: V1.3 N8DM-34-2T: V1.4				
Identification Location	N8DM-34Standard, N8DM-34MT, N8DM-34Modbus, N8DM-34Pulse: 0x0000AFF9 N8DM-34Mbus: 0x00003C02 N8DM-34-2T: 0x00009DF4				
	Nameplate				
Bill Of Materials Number	N8DM-34Standard, N8DM-34MT, N8DM-34Modbus, N8DM-34Mbus, N8DM-34Pulse: V1.4 N8DM-34-2T: DH-JS-180008-1.0				
IP Rating	IP51				
Insulation Protective Class	Class II				
LED Pulse Constant	400imp/ kWh				
Impulse Voltage Rating	6kV				
AC Voltage Rating	4kV				
Main Cover Sealing Type	1 x Wire & Crimp				
Integrity of meter	Inaccessible without breaking seals				
Intended Location of the Meter	Indoor				
Type of Register	LCD				
Terminal Arrangement(s)	DIN				
Location of Manufacturers Address	On accompanying documentation				



0120/SGS0430

Issue Number: 1 Dated: 9th April 2020

2. Photograph of Meter and Sealing Plan






0120/SGS0430

Issue Number: 1 Dated: 9th April 2020

3. Examples of Nameplates



GACIA

N8DM-34Pulse 0120/SGS0430 Three Phase Energy Meter 3x230/400V AC 0,5-10(100)A AC 50Hz 2020 400imp/kWh EN50470-1/3 IP51 SW:1.3 CAT III



Gacia Electrical Appliance Co., LTD No.1 Nanxijiang Road, Wenzhou, Zhejiang




GACIA

N8DM-34Standard 0120/SGS0430 Three Phase Energy Meter 3x230/400V AC 0,5-10(100)A AC 50Hz 2020 400imp/kWh EN50470-1/3 IP51 SW:1.3 CAT III



Gacia Electrical Appliance Co., LTD No.1 Nanxijiang Road, Wenzhou, Zhejiang



GACIA

N8DM-34Modbus 0120/SGS0430 Three Phase Energy Meter

3x230/400VAC 0,5-10(100)AAC 50Hz 2020 400imp/kWh EN50470-1/3 IP51 SW:1.3 CAT III



Gacia Electrical Appliance Co., LTD No.1 Nanxijiang Road, Wenzhou, Zhejiang



0120/SGS0430

Issue Number: 1 Dated: 9th April 2020



GACIA

N8DM-34Mbus 0120/SGS0430 Three Phase Energy Meter

3x230/400VAC 0,5-10(100)AAC 50Hz 2020 400imp/kWh EN50470-1/3 IP51 SW:1.3 CAT III



Gacia Electrical Appliance Co., LTD No.1 Nanxijiang Road, Wenzhou, Zhejiang



GACIA

N8DM-34MT 0120/SGS0430 Three Phase Energy Meter

3x230/400VAC 0,5-10(100)AAC 50Hz 2020 400imp/kWh EN50470-1/3 IP51 SW:1.3 CAT III



Gacia Electrical Appliance Co., LTD No.1 Nanxijiang Road, Wenzhou, Zhejiang



GACIA

N8DM-34-2T 0120/SGS0430
Three Phase Energy Meter

3x230/400VAC 0,5-10(100)AAC 50Hz 2020 400imp/kWh EN50470-1/3 IP51 SW:1.4 CAT III



Gacia Electrical Appliance Co., LTD No.1 Nanxijiang Road, Wenzhou, Zhejiang



0120/SGS0430

Issue Number: 1 Dated: 9th April 2020

4. Calculation of the composite error/ MPE

During the type approval examination the influence factors for temperature, frequency and voltage are determined per load point. The table below represents the sum of the square values per load, determined via the following formula:-

 $\delta e(T, U, f) = \sqrt{(\delta e^2(T, I, \cos\varphi), \delta e^2(U, I, \cos\varphi), \delta e^2(f, I, \cos\varphi))}$

where

 $\delta e(T, I, \cos \varphi) = Additional error due to variation of the temperature at the same load <math>\delta e(U, I, \cos \varphi) = Additional error due to variation of the voltage at the same load <math>\delta e(f, I, \cos \varphi) = Additional error due to variation of the frequency at the same load$



0120/SGS0430

Issue Number: 1 Dated: 9th April 2020

Influence Factors for Temperature. Frequency & Voltag					Voltage		
Current	PF Cos	-25°C	-10°C	5°C	30°C	40°C	55°C
Imin	1.0	0.46	0.34	0.14	0.18	0.29	0.52
ltr	1.0	0.57	0.39	0.19	0.11	0.24	0.46
10ltr	1.0	0.64	0.45	0.25	0.06	0.20	0.42
Imax	1.0	0.75	0.60	0.44	0.26	0.23	0.30
 Itr	0.5ind	0.56	0.40	0.20	0.14	0.24	0.49
10ltr	0.5ind	0.60	0.43	0.23	0.11	0.23	0.45
Imax	0.5ind	0.62	0.47	0.30	0.05	0.10	0.28
ltr	0.8cap	0.65	0.46	0.27	0.11	0.21	0.43
10ltr	0.8cap	0.62	0.44	0.24	0.12	0.24	0.46
Imax	0.8cap	0.69	0.55	0.37	0.16	0.14	0.28
L1							
Itr	1.0	0.84	0.60	0.32	0.08	0.20	0.48
10ltr	1.0	0.97	0.71	0.46	0.10	0.13	0.36
Imax	1.0	0.93	0.70	0.48	0.16	0.06	0.25
Itr	0.5ind	0.60	0.32	0.09	0.25	0.42	0.66
10ltr	0.5ind	0.79	0.56	0.29	0.12	0.27	0.53
lmax	0.5ind	0.84	0.63	0.40	0.10	0.11	0.33
L2							
ltr	1.0	0.40	0.26	0.09	0.08	0.16	0.37
10ltr	1.0	0.42	0.31	0.19	0.08	0.17	0.36
lmax	1.0	0.44	0.36	0.25	0.08	0.08	0.23
Itr	0.5ind	0.20	0.09	0.24	0.27	0.35	0.53
10ltr	0.5ind	0.43	0.30	0.17	0.10	0.20	0.40
lmax	0.5ind	0.46	0.35	0.25	0.09	0.06	0.20
L3							
Itr	1.0	0.55	0.37	0.15	0.14	0.30	0.51
10ltr	1.0	0.51	0.33	0.11	0.20	0.33	0.56
lmax	1.0	0.55	0.39	0.21	0.10	0.21	0.52
Itr	0.5ind	0.41	0.24	0.06	0.32	0.46	0.66
10ltr	0.5ind	0.41	0.22	0.04	0.31	0.46	0.67
Imax	0.5ind	0.43	0.30	0.34	0.17	0.30	0.53



0120/SGS0430

Issue Number: 1 Dated: 9th April 2020

5. Annex of Variants

Product Variant Identification Details:

Type Designation	Description of meter
N8DM-34MT:	Three phase, multi-function, multi-tariff, 2 pulse outputs and 1 RS485 Modbus communication port
N8DM-34Modbus:	Three phase, multi-function, 2 pulse outputs and 1 RS485 communication port
N8DM-34Mbus:	Three phase, multi-function, 2 pulse outputs and 1 Mbus communication port
N8DM-34Pulse:	Three phase, multi-function, 2 pulse outputs
N8DM-34Standard:	Three phase, 2 pulse outputs and 1 RS485 communication port
N8DM-34-2T:	Three phase, multi-function, dual tariffs, 2 pulse outputs and 1 RS485 communication port

Modifications to the meter(s) described according to approval No.0120/SGS0430 must be notified to the issuing body to confirm the meter(s) continuing compliance to the relevant pattern approval standard(s).



0120/SGS0430

Issue Number: 1 Dated: 9th April 2020

6. Document Revision History

Issue	Date	Comments
1	09/04/2020	Initial Issue

This document is issued by the Company subject to its General Conditions for Certification Services, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 28 days only.

END OF CERTIFICATE