# Review of an Environmental Permit for an Installation subject to Chapter II of the Industrial Emissions Directive under the Environmental Permitting (England & Wales) Regulations 2016 (as amended)

# Decision document recording our decision-making process following review of a permit

The Permit number is: EPR/HB3138AU

The Operator is: Tamar Renewable Power (Essex) Limited The Installation is: Halstead Anaerobic Digestion Facility This Variation Notice number is: EPR/HB3138AU/V005

#### What this document is about

Article 21(3) of the Industrial Emissions Directive (IED) requires the Environment Agency to review conditions in permits that it has issued and to ensure that the permit delivers compliance with relevant standards, within four years of the publication by the European Commission of updated decisions on BAT Conclusions.

We have reviewed the permit for this installation against the revised BAT Conclusions for the Waste Treatment industry sector published on 10 August 2018 in the Official Journal of the European Union. In this decision document, we set out the reasoning for the consolidated variation notice that we have issued.

It explains how we have reviewed and considered the techniques used by the Operator in the operation and control of the plant and activities of the installation. This review has been undertaken with reference to the decision made by the European Commission establishing Best Available Techniques (BAT) Conclusions (BATc) for Waste Treatment as detailed in document reference C(2018) 5070. It is our record of our decision-making process and shows how we have taken into account all relevant factors in reaching our position. It also provides a justification for the inclusion of any specific conditions in the permit that are in addition to those included in our generic permit template.

As well as considering the review of the operating techniques used by the Operator for the operation of the plant and activities of the installation, the consolidated variation notice takes into account and brings together in a single document all previous variations that relate to the original permit issue. Where this has not already been done, it also modernises the entire permit to reflect the conditions contained in our current generic permit template.

The introduction of new template conditions makes the Permit consistent with our current general approach and with other permits issued to Installations in this sector. Although the wording of some conditions has changed, while others have been deleted because of the new regulatory approach, it does not reduce the level of environmental

protection achieved by the Permit in any way. In this document, we therefore address only our determination of substantive issues relating to the new BAT Conclusions.

We try to explain our decision as accurately, comprehensively and plainly as possible. Achieving all three objectives is not always easy, and we would welcome any feedback as to how we might improve our decision documents in future.

#### How this document is structured

- 1. Our decision
- 2. How we reached our decision
- 3. The legal framework
- 4. Annex 1 Review of operating techniques within the Installation against the BAT Conclusions.
- 5. Annex 2 Review and assessment of changes that are not part of the BAT Conclusions derived permit review
- 6. Annex 3 Improvement Conditions

#### 1 Our decision

We have decided to issue the Variation Notice to the Operator. This will allow the Operator to continue to operate the Installation, subject to the conditions in the Consolidated Variation Notice that updates the whole permit.

We consider that, in reaching our decision, we have taken into account all relevant considerations and legal requirements and that the varied permit will ensure that a high level of protection is provided for the environment and human health.

The Consolidated Variation Notice contains many conditions taken from our standard Environmental Permit template including the relevant annexes. We developed these conditions in consultation with industry, having regard to the legal requirements of the Environmental Permitting Regulations and other relevant legislation. This document does not therefore include an explanation for these standard conditions. Where they are included in the Notice, we have considered the techniques identified by the Operator for the operation of their installation, and have accepted that the details are sufficient and satisfactory to make those standard conditions appropriate. This document does, however, provide an explanation of our use of "tailor-made" or installation-specific conditions, or where our Permit template provides two or more options.

#### 2 How we reached our decision

## 2.1 Requesting information to demonstrate compliance with BAT Conclusion techniques

We issued a Notice under Regulation 61(1) of the Environmental Permitting (England and Wales) Regulations 2016 (a Regulation 61 Notice) on 19 July 2019 requiring the Operator to provide information to demonstrate where the operation of their installation currently meets, or how it will subsequently meet, the revised standards described in the relevant BAT Conclusions document.

The Notice required that where the revised standards are not currently met, the Operator should provide information that:

- describes the techniques that will be implemented before 17 August 2022, which will then ensure that operations meet the revised standards, or
- justifies why standards will not be met by 17 August 2022, and confirmation of the date when the operation of those processes will cease within the Installation or an explanation of why the revised BAT standard is not applicable to those processes, or
- justifies why an alternative technique will achieve the same level of environmental protection equivalent to the revised standards described in the BAT Conclusions.

Where the Operator proposed that they were not intending to meet a BAT standard that also included a BAT Associated Emission Level (BAT-AEL) described in the BAT Conclusions Document, the Regulation 61 Notice required that the Operator make a formal request for derogation from compliance with that BAT-AEL (as provisioned by Article 15(4) of IED). In this circumstance, the Notice identified that any such request for derogation must be supported and justified by sufficient technical and commercial information that would enable us to determine acceptability of the derogation request.

The Regulation 61 Notice response from the Operator was received on 17/01/2020, 18/02/2020, 20/05/2020, 12/06/2020 and 22/07/2020 and 11/08/2020.

We considered it was in the correct form and contained sufficient information for us to begin our determination of the permit review.

# 2.2 Review of our own information in respect to the capability of the Installation to meet revised standards included in the BAT Conclusions document

Based on our records and previous experience in the regulation of the installation, we consider that the operator will be able to comply with the techniques and standards described in the BAT Conclusions other than for those techniques and requirements described in BAT Conclusion 2, 3, 8, 23 and 34. In relation to these BAT Conclusions, we do not fully agree with the operator in respect of their current stated capability as recorded in their Regulation 61 Notice response. We have therefore included Improvement Condition 1 and 2 in the Consolidated Variation Notice to ensure that the requirements of the BAT Conclusion are delivered before 17 August 2022.

#### 3 The legal framework

The Consolidated Variation Notice will be issued, under Regulations 18 and 20 of the EPR. The Environmental Permitting regime is a legal vehicle which delivers most of the relevant legal requirements for activities falling within its scope. In particular, the regulated facility is:

- an installation as described by the IED;
- subject to aspects of other relevant legislation which also have to be addressed.

We consider that, in issuing the Consolidated Variation Notice, it will ensure that the operation of the Installation complies with all relevant legal requirements and that a high level of protection will be delivered for the environment and human health.

We explain how we have addressed specific statutory requirements more fully in the rest of this document.

#### **Annex 1: decision checklist regarding relevant BAT Conclusions**

BAT Conclusions for the Waste Treatment sector, were published by the European Commission on 10 August 2018. There are 53 BAT Conclusion but not all of them will be relevant to the installation. This annex provides a record of decisions made in relation to each relevant BAT Conclusion which are applicable to the biowaste treatment installation. This annex should be read in conjunction with the Consolidated Variation Notice.

The overall status of compliance with the BAT conclusion is indicated in the table as:

NA – Not Applicable

**CC – Currently Compliant** 

FC – Compliant in the future (within 4 years of publication of BAT conclusions)

NC - Not Compliant

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
1	In order to improve the overall environmental performance, BAT is to implement and adhere to an environmental management system (EMS) that incorporates all of the following features:  I. commitment of the management, including senior management; II. definition, by the management, of an environmental policy that includes the continuous improvement of the environmental performance of the installation; III. planning and establishing the necessary procedures, objectives and targets, in conjunction with financial planning and investment; IV. implementation of procedures paying particular attention to:  (a) structure and responsibility, (b) recruitment, training, awareness and competence, (c) communication, (d) employee involvement, (e) documentation, (f) effective process control, (g) maintenance programmes, (h) emergency preparedness and response, (i) safeguarding compliance with environmental legislation;	CC	Environment Agency assessment The operator has provided information to support compliance with BATc 1. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 1.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	V. checking performance and taking corrective action, paying particular attention to:  (a) monitoring and measurement (see also the JRC Reference Report on Monitoring of emissions to air and water from IED installations – ROM), (b) corrective and preventive action, recruitment, training, awareness and competence, (c) maintenance of records, (d) independent (where practicable) internal or external auditing in order to determine whether or not the EMS conforms to planned arrangements and has been properly implemented and maintained		
	<ul> <li>VI. review, by senior management, of the EMS and its continuing suitability, adequacy and effectiveness;</li> <li>VII. following the development of cleaner technologies;</li> <li>VIII. consideration for the environmental impacts from the eventual decommissioning of the plant at the stage of designing a new plant, and throughout its operating life;</li> <li>IX. application of sectoral benchmarking on a regular basis;</li> <li>X. waste stream management (see BAT 2);</li> <li>XI. an inventory of waste water and waste gas streams (see BAT 3);</li> <li>XII. residues management plan (see description in Section 6.5);</li> </ul>		

BAT Conclusion No	XIII. accident management plan (see description in Section 6.5); XIV. odour management plan (see BAT 12) XV. noise and vibration management plan (see BAT 17).	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
2	In order to improve the overall environmental performance of the plant, BAT is to use all of the techniques listed below:  (a) Set up and implement waste characterisation and pre-acceptance procedures; (b) Set up and implement waste acceptance procedures; (c) Set up and implement a waste tracking system and inventory; (d) Set up and implement an output quality management system; (e) Ensure waste segregation; (f) Ensure waste compatibility prior to mixing or blending of waste; (g) Sort incoming solid waste	FC	The operator provided information to support compliance with BATc 2.  Environment Agency assessment  We have assessed the information provided in the response. Although there is information relevant to the compliance with BATc 2, we consider that aspects of BATc 2a have not been adequately addressed with respect to characterisation of the following non-standard waste streams: EWC 02 06 02, 03 03 02, 03 03 08, 03 03 10, 04 01 01, 04 01 05, 04 01 07, 04 02 13 and 20 01 38.  We consider that the operator will be future compliant with BATc 2a. Improvement

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
			condition 3 has been included in the permit to achieve compliance (see Annex 3).
3	In order to facilitate the reduction of emissions to water and air, BAT is to establish and to maintain an inventory of waste water and waste gas streams, as part of the environmental management system (see BAT 1), that incorporates all of the following features:  (i) information about the characteristics of the waste to be treated and the waste treatment processes, including: (a) simplified process flow sheets that show the origin of the emissions; (b) descriptions of process-integrated techniques and waste water/waste gas treatment at source including their performances;  (ii) information about the characteristics of the waste water streams, such as: (a) average values and variability of flow, pH, temperature, and conductivity; (b) average concentration and load values of relevant substances and their variability (e.g. COD/TOC, nitrogen species, phosphorus, metals, priority substances /micropollutants); (c) data on bioeliminability (e.g. BOD, BOD to COD ratio, Zahn-Wellens test, biological inhibition potential (e.g. inhibition of activated sludge)) (see BAT 52);  (iii) information about the characteristics of the waste gas streams, such as:	FC	Environment Agency assessment  The operator has provided information to support compliance with BATc 3. We have assessed the information provided and reviewed the site compliance report. The information does not include characteristics of the waste gas produced from the biologically treatment and fed to the abatement systems. We are not satisfied that the operator has demonstrated compliance with BATc 3.  We consider that the operator will be future compliant with BATc 3. Improvement condition 2 has been included in the permit to achieve compliance (see Annex 3).

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul> <li>(a) average values and variability of flow and temperature;</li> <li>(b) average concentration and load values of relevant substances and their variability (e.g. organic compounds, POPs such as PCBs);</li> <li>(c) flammability, lower and higher explosive limits, reactivity;</li> <li>(d) presence of other substances that may affect the waste gas treatment system or plant safety (e.g. oxygen, nitrogen, water vapour, dust).</li> </ul>		
4	In order to reduce the environmental risk associated with the storage of waste, BAT is to use all of the techniques given below:  (a) Optimised storage location; (b) Adequate storage capacity; (c) Safe storage operation; (d) Separate area for storage and handling of packaged hazardous waste.	cc	Environment Agency assessment  The operator has provided information to support compliance with BATc 4. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 4.
5	In order to reduce the environmental risk associated with the handling and transfer of waste, BAT is to set up and implement handling and transfer procedures.  Handling and transfer procedures aim to ensure that wastes are safely handled and transferred to the respective storage or treatment. They include the following elements:	СС	Environment Agency assessment  The operator has provided information to support compliance with BATc 5. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 5.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul> <li>handling and transfer of waste are carried out by competent staff;</li> <li>handling and transfer of waste are duly documented, validated prior to execution and verified after execution;</li> <li>measures are taken to prevent, detect and mitigate spills;</li> <li>operation and design precautions are taken when mixing or blending wastes (e.g. vacuuming dusty/powdery wastes).</li> <li>Handling and transfer procedures are risk-based considering the likelihood of accidents and incidents and their environmental impact.</li> </ul>		
6	For relevant emissions to water as identified by the inventory of waste water streams (see BAT 3), BAT is to monitor key process parameters (e.g. waste water flow, pH, temperature, conductivity, BOD) at key locations (e.g. at the inlet and/or outlet of the pre-treatment, at the inlet to the final treatment, at the point where the emission leaves the installation).	NA	Environment Agency assessment We are satisfied that BATc 6 is not applicable to this Installation.
7	BAT is to monitor emissions to water with at least the frequency given in BATc 7, and in accordance with EN standards. If EN standards are not available, BAT is to use ISO, national or other international standards that ensure the provision of data of an equivalent scientific quality.	NA	Environment Agency assessment We are satisfied that BATc 7 is not applicable to this Installation.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
8	BAT is to monitor channelled emissions to air with at least the frequency given in BATc 8, and in accordance with EN standards. If EN standards are not available, BAT is to use ISO, national or other international standards that ensure the provision of data of an equivalent scientific quality.	FC	Environment Agency assessment  The operator has provided information to support compliance with BATc 8. We have assessed the information provided and reviewed the site compliance report.  There is an odour abatement plant serving the reception building at the installation. The treated gas waste stream is then discharged to air. There are no monitoring requirements for the odour abatement plant but this permit variation will stipulate this, in accordance with BATc 8.  We consider that the operator will be future compliant with BATc 8. Improvement condition 1 has been included in the permit to achieve compliance (see Annex 3).
10	BAT is to periodically monitor odour emissions.	СС	Environment Agency assessment
	Odour emissions can be monitored using:		The operator has provided information to support compliance with BATc 10. We have

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul> <li>EN standards (e.g. dynamic olfactometry according to EN 13725 in order to determine the odour concentration or EN 16841-1 or -2 in order to determine the odour exposure);</li> <li>when applying alternative methods for which no EN standards are available (e.g. estimation of odour impact), ISO, national or other international standards that ensure the provision of data of an equivalent scientific quality.</li> <li>The monitoring frequency is determined in the odour management plan (see BAT 12).</li> </ul>		assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 10.
11	BAT is to monitor the annual consumption of water, energy and raw materials as well as the annual generation of residues and waste water, with a frequency of at least once per year.  Monitoring includes direct measurements, calculation or recording, e.g. using suitable meters or invoices. The monitoring is broken down at the most appropriate level (e.g. at process or plant/installation level) and considers any significant changes in the plant/installation.	cc	Environment Agency assessment  The operator has provided information to support compliance with BATc 11. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 11.
12	In order to prevent or, where that is not practicable, to reduce odour emissions, BAT is to set up, implement and regularly review an odour management plan, as	СС	Environment Agency assessment

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul> <li>part of the environmental management system (see BAT 1), that includes all of the following elements:</li> <li>a protocol containing actions and timelines;</li> <li>a protocol for conducting odour monitoring as set out in BAT 10;</li> <li>a protocol for response to identified odour incidents, e.g. complaints;</li> <li>an odour prevention and reduction programme designed to identify the source(s); to characterise the contributions of the sources; and to implement prevention and/or reduction measures.</li> </ul>		The operator has provided information to support compliance with BATc 12. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 12.
13	In order to prevent or, where that is not practicable, to reduce odour emissions, BAT is to use one or a combination of the techniques given below:  (a) Minimising residence times; (b) Using chemical treatment; (c) Optimising aerobic treatment	CC	Environment Agency assessment  The operator has provided information to support compliance with BATc 13. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 13.
14	In order to prevent or, where that is not practicable, to reduce diffuse emissions to air, in particular of dust, organic compounds and odour, BAT is to use an appropriate combination of the techniques given below:  (a) Minimising the number of potential diffuse emission sources; (b) Selection and use of high-integrity equipment;	СС	Environment Agency assessment The operator has provided information to support compliance with BATc 14. We have assessed the information provided and we are

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul> <li>(c) Corrosion prevention;</li> <li>(d) Containment, collection and treatment of diffuse emissions;</li> <li>(e) Dampening;</li> <li>(f) Maintenance;</li> <li>(g) Cleaning of waste treatment and storage areas;</li> <li>(h) Leak detection and repair (LDAR) programme</li> </ul>		satisfied that the operator has demonstrated compliance with BATc 14.
15	BAT is to use flaring only for safety reasons or for non-routine operating conditions (e.g. start-ups, shutdowns) by using both of the techniques given below:  (a) Correct plant design; (b) Plant management	CC	Environment Agency assessment  The operator has provided information to support compliance with BATc 15. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 15.
16	In order to reduce emissions to air from flares when flaring is unavoidable, BAT is to use both of the techniques given below:  (a) Correct design of flaring devices; (b) Monitoring and recording as part of flare management	CC	Environment Agency assessment The operator has provided information to support compliance with BATc 16. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 16.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
17	In order to prevent or, where that is not practicable, to reduce noise and vibration emissions, BAT is to set up, implement and regularly review a noise and vibration management plan, as part of the environmental management system (see BAT 1), that includes all of the following elements:  I. a protocol containing appropriate actions and timelines; II. a protocol for conducting noise and vibration monitoring; III. a protocol for response to identified noise and vibration events, e.g. complaints; IV. a noise and vibration reduction programme designed to identify the source(s), to measure /estimate noise and vibration exposure, to characterise the contributions of the sources and to implement prevention and /or reduction measures.	CC	Environment Agency assessment The operator has provided information to support compliance with BATc 17. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 17.
18	In order to prevent or, where that is not practicable, to reduce noise and vibration emissions, BAT is to use one or a combination of the techniques given below:  (a) Appropriate location of equipment and buildings; (b) Operational measures; (c) Low noise-equipment; (d) Noise and vibration equipment; (e) Noise attenuation	CC	Environment Agency assessment  The operator has provided information to support compliance with BATc 18. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 18.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
19	In order to optimise water consumption, to reduce the volume of waste water generated and to prevent or, where that is not practicable, to reduce emissions to soil and water, BAT is to use an appropriate combination of the techniques given below:  (a) Water management; (b) Water recirculation; (c) Impermeable surface; (d) Techniques to reduce the likelihood and impact of overflows and failures from tanks and vessels; (e) Roofing of waste storage and treatment areas; (f) Segregation of water streams (g) Adequate drainage infrastructure; (h) Design and maintenance provisions to allow detection and repair of leaks (i) Appropriate buffer storage capacity	СС	Environment Agency assessment The operator has provided information to support compliance with BATc 19. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 19.
20	In order to reduce emissions to water, BAT is to treat waste water using an appropriate combination of the techniques given below:  *Preliminary and primary treatment, e.g.*  (a) Equalisation	NA	Environment Agency assessment We are satisfied that BATc 20 is not applicable to this Installation.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	(b) Neutralisation (c) Physical separation, e.g. screens, sieves, grit separators, grease separators, oil-water separation or primary settlement tanks  **Physico-chemical treatment, e.g.** (d) Adsorption (e) Distillation /rectification (f) Precipitation (g) Chemical oxidation (h) Chemical reduction (i) Evaporation (j) Ion exchange (k) Stripping		
	Biological treatment, e.g. (I) Activated sludge process (m) Membrane bioreactor (n) Nitrification / denitrification when the treatment includes a biological treatment  Solids removal, e.g. (o) Coagulation and flocculation (p) Sedimentation		

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	(q) Filtration (e.g. sand filtration, microfiltration, ultrafiltration) (r) Flotation  See also: Table 6.1: BAT-associated emission levels (BAT-AELs) for direct discharges to a receiving water body  See also: Table 6.2: BAT-associated emission levels (BAT-AELs) for indirect discharges to a receiving water body		
21	In order to prevent or limit the environmental consequences of accidents and incidents, BAT is to use all of the techniques given below, as part of the accident management plan (see BAT 1):  (a) Protection measures; (b) Management of incidental /accidental emissions; (c) Incident /accident registration and assessment system	cc	Environment Agency assessment The operator has provided information to support compliance with BATc 21. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 21.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
22	In order to use materials efficiently, BAT is to substitute materials with waste.  Waste is used instead of other materials for the treatment of wastes (e.g. waste alkalis or waste acids are used for pH adjustment, fly ashes are used as binders).	NA	Environment Agency assessment We are satisfied that BATc 22 is not applicable to this Installation.
23	In order to use energy efficiently, BAT is to use both of the techniques given below:  (a) Energy efficiency plan; (b) Energy balance record	FC	Environment Agency assessment  The operator has provided information to support compliance with BATc 23. We have assessed the information provided and reviewed the site compliance report.  The Operator has submitted some information on monitoring of energy generation. However the information does not include an energy efficiency plan or an energy balance record. We are not satisfied that the operator has demonstrated compliance with BATc 23.  We consider that the operator will be future compliant with BATc 23. Improvement condition 2 has been included in the permit to achieve compliance (see Annex 3).

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
24	In order to reduce the quantity of waste sent for disposal, BAT is to maximise the reuse of packaging, as part of the residues management plan (see BAT 1).  Packaging (drums, containers, IBCs, pallets, etc.) is reused for containing waste, when it is in good condition and sufficiently clean, depending on a compatibility check between the substances contained (in consecutive uses). If necessary, packaging is sent for appropriate treatment prior to reuse (e.g. reconditioning, cleaning).	СС	Environment Agency assessment The operator has provided information to support compliance with BATc 24. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 24.
33	In order to reduce odour emissions and to improve the overall environmental performance, BAT is to select the waste input.  The technique consists of carrying out the pre-acceptance, acceptance and sorting of the waste input (see BAT 2) so as to ensure the suitability of the waste input for the waste treatment, e.g. in terms of nutrient balance, moisture or toxic compounds which may reduce the biological activity.	CC	Environment Agency assessment  The operator has provided information to support compliance with BATc 33. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 33.
34	In order to reduce channelled emissions to air of dust, organic compounds and odorous compounds, including $H_2S$ and $NH_3$ , BAT is to use one or a combination of the techniques given below:	BATc 34 CC	Environment Agency assessment The operator has provided information to support compliance with BATc 34. We have assessed the information provided and we are

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul> <li>(a) Adsorption;</li> <li>(b) Biofilter;</li> <li>(c) Fabric filter;</li> <li>(d) Thermal oxidation;</li> <li>(e) Wet scrubbing</li> <li>See also: Table 6.7: BAT-associated emission levels (BAT-AELs) for channelled NH<sub>3</sub>, odour, dust and TVOC emissions to air from the biological treatment of waste.</li> </ul>	BATc 34 Table 6.7 FC	satisfied that the operator has demonstrated compliance with BATc 34.  Environment Agency assessment  The operator provided information to support compliance with BATc 34. Abatement in the form of biofilter, carbon filter and scrubber are installed at the facility.  We have assessed the information provided
			and we are satisfied that the operator has demonstrated compliance with BATc 34.  We have set a BAT-AEL for ammonia as specified in the Waste Treatment BREF and BAT Conclusions.  Improvement condition 1 (IC1) has been included in the permit to achieve compliance.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
			The operator is required to complete the improvement condition and demonstrate compliance with BAT-AEL by the compliance date, 17 August 2022.
			In addition to the BAT-AEL, we have inserted the requirement to monitor odour concentration, hydrogen sulphide and ammonia on a 6-monthly frequency in Table S3.3 (process monitoring).
			As part of the Environment Agency approach to reduce emissions in the biowaste treatment sector, we have included Improvement condition 6 (IC6) which requires the operator to review abatement plant on site, in order to determine whether existing measures have been effective and adequate to prevent and /or minimise emissions released to air. Where further improvements are identified, the

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
			measures.
35	In order to reduce the generation of waste water and to reduce water usage, BAT is to use all of the techniques given below:  (a) Segregation of water streams; (b) Water recirculation; (c) Minimisation of the generation of leachate	СС	Environment Agency assessment The operator has provided information to support compliance with BATc 35. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 35.
36	In order to reduce emissions to air and to improve the overall environmental performance, BAT is to monitor and/or control the key waste and process parameters.	NA	Environment Agency assessment We are satisfied that BATc 36 is not applicable to this Installation.
	<ul> <li>Monitoring and/or control of key waste and process parameters, including:</li> <li>waste input characteristics (e.g. C to N ratio, particle size);</li> <li>temperature and moisture content at different points in the windrow;</li> <li>aeration of the windrow (e.g. via the windrow turning frequency, O<sub>2</sub> and/or CO<sub>2</sub> concentration in the windrow, temperature of air streams in the case of forced aeration);</li> </ul>		

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment  windrow porosity, height and width.	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
37	In order to reduce diffuse emissions to air of dust, odour and bioaerosols from open-air treatment steps, BAT is to use one or both of the techniques given below:  (a) Use of semi permeable membrane covers; (b) Adaptation of operations to the meteorological conditions	NA	Environment Agency assessment We are satisfied that BATc 37 is not applicable to this Installation.
38	In order to reduce emissions to air and to improve the overall environmental performance, BAT is to monitor and/or control the key waste and process parameters.  This includes monitoring and/or control of key waste and process parameters:  • pH and alkalinity of the digester feed;  • digester operating temperature;  • hydraulic and organic loading rates of the digester feed;  • concentration of volatile fatty acids (VFA) and ammonia within the digester and digestate;  • biogas quantity, composition (e.g. H <sub>2</sub> S) and pressure;  • liquid and foam levels in the digester.	СС	Environment Agency assessment The operator has provided information to support compliance with BATc 38. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 38.

BAT Conclusion No	Summary of BAT Conclusion requirement for Waste Treatment	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
39	In order to reduce emissions to air, BAT is to use both of the techniques given below:  (a) Segregation of the waste gas streams; (b) Recirculation of waste gas	NA	Environment Agency assessment We are satisfied that BATc 39 is not applicable to this Installation.

# Annex 2: Review and assessment of changes that are not part of the BAT Conclusions derived permit review

#### **Existing Medium Combustion Plant**

We asked the Operator to provide information on all combustion plant on site in the Regulation 61 Notice as follows:

- Number of combustion plant (CHP engines, back-up generators, boilers);
- Size of combustion plant rated thermal input (MWth)
- Date each combustion plant came into operation
- Confirmation as to whether or not the combustion plant is subject to a capacity market agreement (2014 or 2015 auction) or whether or not a Feedin Tariff preliminary accreditation application was received prior to 1 December 2016

The Operator provided the information in the table(s) below:

#### Combined heat and power (CHP) engines

Rated thermal input (MW) of the medium combustion plant.	1.352MWth per CHP engine
2. Type of the medium combustion plant (diesel engine, gas turbine, dual fuel engine, other engine or other medium combustion plant).	2 x Jenbacher 416 CHP gas engines
3. Type and share of fuels used according to the fuel categories laid down in Annex II.	Biogas from food waste
4. Date of the start of the operation of the medium combustion plant or, where the exact date of the start of the operation is unknown, proof of the fact that the operation started before 20 December 2018.	18 July 2014
5. Confirmation of capacity market agreement arising from 2014 or 2015 capacity auctions.	Not in the capacity market – accredited under the FIT scheme
6. Confirmation of Feed-in Tariff preliminary accreditation application received by the Gas and Electric Markets Authority prior to 1 December 2016.	Site accredited for FITs – accreditation 18 July 2014

We consider that the combustion plant qualify as "existing" medium combustion plant based on previous permit applications and site compliance history. The existing CHP engines were permitted in 2012 and were in operation prior to 20 December 2018.

For existing MCP with a rated thermal input of less than or equal to 5 MW, the emission limit values set out in tables 1 and 3 of Part 1 of Annex II MCPD shall apply from 1 January 2030. We have included the appropriate emission limit values for existing medium combustion plant as part of this permit review (see Table S3.1 in the permit).

We have included improvement condition 3 in the permit which requires the operator to assess methane slip resulting from the combustion of biogas via the CHP engines. Following an assessment of the data, the Environment Agency shall consider whether or not emission limits for volatile organic compounds are applicable for this installation.

#### **Bioaerosols monitoring requirements**

We asked the Operator to confirm the following aspects regarding the site operations in the Regulation 61 Notice:

- Whether or not the operational processes of biodegradable waste are in open processes within 250 metres of human receptors.
- Whether or not there is a channelled or point source release within 250 metres that are open sources e.g. biofilters within 250 metres of human receptors; and
- The existing permit contains bioaerosols monitoring requirements, the microbiological markers, associated bioaerosols limits and the monitoring standards

The Operator did not provide information regarding bioaerosols monitoring in their response to the Regulation 61 Notice. We carried out an assessment of the site location and the distance of site processes from sensitive receptors as part of this determination. The site operates a biofilter which is located within 250 metres of a sensitive receptor.

We consider it appropriate to insert the bioaerosols monitoring requirements in the permit in accordance with our guidance TGN M9 Environmental monitoring of bioaerosols at regulated facilities (version 2, July 2018). The Operator is required to comply with the new monitoring requirements from the date of permit issue.

#### Soil & groundwater risk assessment (baseline report)

The IED requires that the operator of any IED installation using, producing or releasing "relevant hazardous substances" (RHS) shall, having regarded the possibility that they might cause pollution of soil and groundwater, submit a "baseline report" with its permit application. The baseline report is an important reference document in the assessment of contamination that might arise during the operational lifetime of the regulated facility and at cessation of activities. It must enable a quantified comparison to be made between the baseline and the state of the site at surrender.

At the definitive cessation of activities, the Operator has to satisfy us that the necessary measures have been taken so that the site ceases to pose a risk to soil or groundwater, taking into account both the baseline conditions and the site's current or approved future use. To do this, the Operator has to submit a surrender application to us, which we will not grant unless and until we are satisfied that these requirements have been met.

The Operator submitted a site condition report (Ref: JER5371 R 120427HM Application Site Condition Report, Rev 1 dated 30 April 2012) during the original application received on 03/05/2012. The site condition report did not include a report on the baseline conditions as required by Article 22. We reviewed that report and considered that it adequately described the condition of the soil and groundwater at that time.

The Operator reported, in the previous application in 2012 that given that no historical development works had taken place at the site and the development consists of the placement of an impermeable hardstanding at the facility, it was considered that intrusive ground works not required.

As no soil and groundwater data was submitted to the Environment Agency in the original application in 2012, we consider the Operator has assumed 'zero contamination' beneath the site. This means that when the Operator applies to surrender the Permit, any contamination by substances used at, produced or released from the facility would be considered to have resulted from the operation of the installation. This is in accordance with the Environment Agency Guidance H5 – Site Condition Report.

#### **Waste types**

We have specified the permitted waste types, descriptions and quantities, which can be accepted at the regulated facility. The wastes are specified in Table S2.2 in the permit.

We are satisfied that the Operator can accept these wastes for the following reasons:

- they are suitable for the proposed activities
- the proposed infrastructure is appropriate
- the environmental risk assessment is acceptable.

#### Other wastes (non-standard waste codes)

The following wastes in the current permit are not specified in the our revised biowaste treatment permit templates. We have retained these wastes in the current permit provided the Operator undertakes a detailed characterisation of the wastes prior to acceptance for treatment at the site in accordance with BATc 2a.

Waste code	Description
02 06 02	wastes from preserving agents
03 03 02	green liquor sludge (from recovery of cooking oil)
03 03 08	wastes from sorting of paper and cardboard destined for recycling  – not allowed if non-biodegradable coating or preserving substance present
03 03 10	fibre rejects, fibre-, filler- and coating-sludges from mechanical separation
04 01 01	fleshings and lime split wastes
04 01 05	tanning liquor free of chromium
04 01 07	sludges not containing chromium
04 02 13	waste plastic - must conform to BS EN 13432
20 01 38	wood other than that mentioned in 20 01 37 – untreated wood where no non-biodegradable coating or preserving substance present

We consider that the Operator will be future compliant with BATc 2a. Improvement condition 2 has been included in the permit to achieve compliance (see Annex 3).

We made this decision with respect to waste types in accordance with the Framework Guidance Note – Framework for assessing suitability of wastes going to anaerobic digestion, composting and biological treatment (July 2013).

#### Excluded wastes (99 waste codes)

We have excluded the following waste streams ending with "99" code(s) because more suitable waste codes are already in the European Waste Catalogue (EWC) that accommodate the waste described:

02 02 99	non specified sludges from gelatine production – animal gut contents	
02 04 99	other biodegradable wastes	
02 07 99	spent grains, hops and whisky filter sheets/cloths	

Our technical guidance on waste classification WM3 specifically sets out clear instructions for the use of the European Waste Catalogue (EWC), particularly with regard to "99" codes.

The guidance specifies that the Operator must:

- Identify the source generating the waste in chapters 01 to 12 or 17 to 20 and identify the appropriate six-digit code of the waste (excluding codes ending with 99 of these chapters).
- If no appropriate waste code can be found in chapters 01 to 12 or 17 to 20, the chapters 13, 14 and 15 must be examined to identify the waste.
- If none of these waste codes apply, the waste must be identified according to chapter 16.
- If the waste is not in chapter 16, the 99 code (wastes not otherwise specified)
  must be used in the section of the list corresponding to the activity identified in
  step one as a last resort.

We made this decision with respect to "99" codes in accordance with the Technical Guidance WM3: Waste Classification – Guidance on the classification and assessment of waste [1st Edition v1.1, May 2018].

## <u>Primary containment infrastructure design (tanks /vessels used for storage and/or treatment activities)</u>

We assessed primary containment as part of the permit review. This information was not requested in the Regulation 61 Notice issued to the Operator, however, it was considered prudent to address this aspect as part of the permit review process. In this instance, the required information relating to the review of primary containment infrastructure against CIRIA C535 was not previously submitted to the Environment Agency, nor was it included in the supporting documentation submitted by the Operator in their Regulation 61 response.

We have therefore set an Improvement Condition (IC4) in the permit to address this aspect of the permit review (see Annex 3).

#### Secondary containment and lagoon storage infrastructure design

We asked the Operator via the Regulation 61 Notice to:

- describe any secondary containment and whether it currently meets the relevant standard in the "Containment systems for the prevention of pollution (C736)" report, where there are above-ground storage or primary containment on site; or
- explain why the current site infrastructure design and construction is fit for purpose, where it is concluded that secondary containment is not required or does not need to meet the standards in the C736 report, to enable a baseline standard so as to establish a quantified comparison; and
- describe how the construction of the lagoons meets the relevant standard in CIRIA C736 report, where there are storage lagoons used for the storage of digestate on site.

### Assessment of existing secondary containment & lagoon storage design and construction

The Operator's report included a review of the design, method of construction and integrity of the site secondary containment and storage which was carried out by a qualified engineer. The review compared the existing site secondary containment against CIRIA C736. The report included a review of the:

- physical condition of the secondary containment
- the suitability for providing containment when subjected to the dynamic and static loads caused by catastrophic tank failure;
- a preventative maintenance and inspection regime;
- future work required to ensure compliance with the standards set out in CIRIA C736 or other relevant industry standard; and
- Recommendations (where relevant)

There are no storage lagoons at the installation. The report described the site as clean, tidy and well operated, and has been designed with simple engineering principles considered. The report outlined minor recommendations to ensure the required pollution containment and structural integrity meet the standards set out in CIRIA C736. Recommendations have also been provided in relation to additional works required and the future management /inspection of infrastructure. The integrity of the sub-surface tank was not assessed at the time of the visit. The report concludes that the existing primary and secondary containment operate in accordance with the requirements set out in CIRIA C736.

We assessed the Operator's assessment having regard to following guidance documents:

- CIRIA C736 Containment systems for the prevention of pollution
- ADBA Industry Guide: Secondary Containment at AD Plants (Version 1, 2016)

We reviewed the Operator's report and its findings. We are not satisfied that the information in the report is sufficient to demonstrate that the existing site secondary containment meets the standards set out in CIRIA C736 for the following reasons:

- A site risk assessment of the existing site secondary assessment has not been undertaken in accordance with Chapter 2 of CIRIA C736
- The integrity of the sub-surface tank has not been assessed;
- The sectional concrete wall requires inspection to determine if sectional concrete panels are fixed to basal slab and joint seals replaced where required in line with requirements.
- There are other recommendations in relation to additional works required and the future management /inspection of infrastructure.

We have set improvement condition 5 in the permit to address the deficiencies in the existing site secondary containment (see Annex 3 of this decision document).

#### **Annex 3: Improvement Conditions**

Based on the information in the Operator's Regulation 61 Notice response and our own records of the capability and performance of the installation at this site, we consider that we need to set improvement conditions so that the outcome of the techniques detailed in the BAT Conclusions are achieved by the installation. These improvement conditions are set out below – justifications for them is provided at the relevant section of the decision document (Annex 1 or Annex 2).

We also consider that we need to set improvement conditions relating to changes in the permit not arising from the review of compliance with BAT Conclusions. The justifications for these are provided in Annex 2 of this decision document.

If the consolidated permit contains existing improvement conditions that are not yet complete or the opportunity has been taken to delete completed improvement conditions then the numbering in the table below will not be consecutive as these are only the improvement conditions arising from this permit variation.

Improvement programme requirements				
Reference	Requirement	Date		
Improvement condition for progress report to achieve BAT-AELs				
IC1	The operator shall submit, for approval by the Environment Agency, a report setting out progress to achieving the Best Available Techniques Conclusion Associated Emission Levels (BAT-AELs) where BAT is currently not achieved, but will be achieved before 17 August 2022. The report shall include, but not be limited to, the following:  1) Current performance against the BAT-AELs. 2) Methodology for reaching the BAT-AELs. 3) Associated targets /timelines for reaching compliance by 17 August 2022. 4) Any alterations to the initial plan (in progress reports).  The report shall address the BAT Conclusions for Waste Treatment with respect to the following:  • BAT 34 Table 6.7 (compliance with BAT-AELs for channelled NH <sub>3</sub> , odour, dust and TVOC emissions to air from the biological treatment of waste.  Refer to BAT Conclusions for a full description of the BAT requirement.	Progress reports at six monthly intervals from date of permit issue: 28/03/2021 28/09/2021 28/03/2022		
Improvement condition for progress report to achieve Narrative BAT				
IC2	The operator shall submit, for approval by Environment Agency, a report setting out progress to achieving the 'Narrative' BAT where BAT is currently not achieved, but will be achieved before	Progress reports at six monthly intervals from		

Reference	Requirement	Date
	17 August 2022. The report shall include, but not be limited to, the following:	date of permi
	<ol> <li>Methodology for achieving BAT</li> <li>Associated targets /timelines for reaching compliance by 17 August 2022</li> <li>Any alterations to the initial plan (in</li> </ol>	28/03/2021 28/09/2021 28/03/2022
	progress reports).  The report shall address the BAT Conclusions for	
	Waste Treatment with respect to BAT 2, 3, 8 and 23.  Refer to BAT Conclusions for a full description of	
	the BAT requirement.	
Improvemen	t condition for assessment of methane slip	
IC3	The operator shall establish the methane emissions in the exhaust gas from engines burning biogas and compare these to the manufacturer's specification and benchmark levels agreed in writing with the Environment Agency. The operator shall, as part of the methane leak detection and repair (LDAR) programme, develop proposals to assess the potential for methane slip and take corrective actions where emissions above the manufacturer's specification or appropriate benchmark levels are identified.	28/09/2021 or other date as agreed in writing with the Environment Agency
Improvemen	t condition for primary containment	
IC4	The operator shall submit a written 'primary containment plan' and shall obtain the Environment Agency's written approval to it. The plan shall contain the results of a review conducted, by a competent person, and shall compare the design specification of primary containment systems where all polluting liquids and solids are being stored, treated, and/or handled against the design standards within CIRIA C535 guidance or equivalent.	28/09/2021 or other date as agreed in writing with the Environment Agency
	The review shall include:	
	<ul> <li>physical condition of all primary containment systems (storage and treatment vessels);</li> </ul>	
	<ul> <li>the suitability for providing primary containment when subjected to the dynamic and static loads caused by the vessels' contents;</li> </ul>	
	<ul> <li>any work required to ensure compliance with the standards set out in CIRIA C535 or equivalent; and</li> </ul>	

Reference	Requirement	Date
Reference	Requirement  a preventative maintenance and inspection regime  The plan must contain dates for the implementation of individual improvement measures necessary for the primary containment to adhere to the standards detailed/referenced within CIRIA C535 guidance, or equivalent.  The plan shall be implemented in accordance with the Environment Agency's written approval.  condition for secondary containment design  The operator shall submit an updated written 'secondary and tertiary containment report' and shall obtain the Environment Agency's written approval to it.  The report shall contain:  the results of a review conducted, by a competent person, in accordance with the risk assessment methodology detailed within CIRIA C736 (2014) guidance, of the condition and extent of secondary and tertiary containment systems where all polluting liquids and solids are being stored, treated, and/or handled. The review shall consider, but not limited to, the storage vessels, bunds, loading and unloading areas, transfer pipework/pumps, temporary storage areas, and sub-surface drainage, underground storage tanks and liners underlying the site.  the results of remedial actions taken in response to the recommendations outlined within the Report entitled "Halstead Anaerobic Digestion Facility, Containment System Assessment; Regulation 61 (Schedule 1) CQA Reference No. 30430, dated February 2020; and  a maintenance and inspection regime.  The review report must be validated by a competent person to ensure that the site's secondary containment is fully compliant with the standards set in CIRIA C736 (2014) guidance, or equivalent.	28/09/2021 or other date as agreed in writing with the Environment Agency
Improvement	t condition for review of effectiveness of abatemen	t plant
		28/09/2021
IC6	The operator shall carry out a review of the abatement plant on site, in order to determine whether the measures have been effective and	or other date as agreed in

Improvement	Improvement programme requirements				
Reference	Requirement	Date			
	adequate to prevent and where not possible minimise emissions released to air including but not limited to odour and ammonia.	writing with the Environment			
	The operator shall submit a written report to the Environment Agency following this review for assessment and approval.	Agency			
	The report shall include but not limited to the following aspects:				
	<ul> <li>Full investigation and characterisation of the waste gas streams.</li> </ul>				
	<ul> <li>Abatement stack monitoring results (not limited to odour and ammonia)</li> </ul>				
	<ul> <li>Abatement process monitoring results (not limited to odour and ammonia)</li> </ul>				
	<ul> <li>Details of air quality quantitative impact assessment including modelling and a proposal for site-specific "action levels" (not limited to odour concentration, hydrogen sulphide and ammonia).</li> </ul>				
	<ul> <li>Odour monitoring results at the site boundary</li> </ul>				
	<ul> <li>Records of odour complaints and odour related incidents</li> </ul>				
	<ul> <li>Details of air quality quantitative impact assessment including modelling and a proposal for site-specific "action levels" (not limited to odour concentration, hydrogen sulphide and ammonia).</li> </ul>				
	<ul> <li>Recommendations for improvement including the replacement or upgrading the abatement plant</li> </ul>				
	<ul> <li>Timescales for implementation of improvements to the abatement plant</li> </ul>				
	The operator shall implement the improvements in line with the timescales as approved by the Environment Agency.				