

Construction noise and vibration Monthly Report – December 2021

Solihull Metropolitan District

© HS₂ Ltd. qov.uk/hs₂

Non-Techn	ical Summary	1						
Abbreviati	ons and Descriptions	3						
1 Introduction								
1.2	Measurement Locations	5						
2 Sum	mary of Results	7						
2.1	Summary of Measured Noise Levels	7						
2.2	Exceedances of the LOAEL and SOAEL	10						
2.3	Exceedances of Trigger Level	12						
2.4	Complaints	12						
Appendix A	A Site Locations	13						
Appendix E	B Monitoring Locations	19						
Appendix (Data	24						
List of tabl	es							
Table 1: Tab	ole of Abbreviations	3						
Table 2: Mo	nitoring Locations	6						
Table 3: Sur	mmary of Measured dB L _{Aeq} Data over the Monitoring Period	8						
Table 4: Summary of Measured PPV Data over the Monitoring Period								
Table 5: Summary of Exceedances of LOAEL and SOAEL								
Table 6: Summary of Exceedances of Trigger Levels								
Table 7: Sur	nmary of Complaints	12						

Non-Technical Summary

This Noise and Vibration Monitoring Report fulfils HS2 Limited's commitment detailed in the Environmental Minimum Requirements (EMRs), Annex 1, Code of Construction Practice, to present the results of noise and vibration monitoring carried out within the Solihull Metropolitan District (SMD) during the month of December 2021.

Within this period monitoring was undertaken at the following worksites:

- Noise monitoring was undertaken in the vicinity of the Birmingham Interchange Highways Worksite (ref.: WP062), where drainage works, highway construction works, and landscaping works were underway.
- Noise monitoring was undertaken in the vicinity of the A452 compound (ref.: A452), where no works took place within the vicinity throughout December 2021.
- Noise monitoring was undertaken in the vicinity of the Park Lane Worksite (ref.: PL)
 where pond headwall installation, haul route completion, installation of haul route,
 installation of culvert crossing, coring, trial holes and v-ditch (drainage ditch
 installation) on the haul route, roundabout construction works, and the joining
 process 'tie in' of the roundabout to Park Lane, including re-surfacing were
 undertaken.
- Vibration monitoring was undertaken in the vicinity of the Balsall Common Viaduct Worksite (ref.: BCV) where Beechwood rigid inclusion (piling works), sandbags installation to ditch pond, and site setup were undertaken.
- Noise monitoring was undertaken in the vicinity of the Carol Green Rail Underbridge Worksite (ref.: CGRU), where exclusion zones were set-up and site maintenance works were undertaken.
- Noise and vibration monitoring were undertaken in the vicinity of the Waste Lane Overbridge and Satellite Worksite (ref.: WLOS), where cable installation and piling works were underway.

Further works, where monitoring did not take place, were also undertaken at the following locations:

- Between Meriden Road & Diddington Lane (diversion of water main).
- Birmingham Interchange Station (electricity works).

There were no exceedances of the HS2 threshold levels for significant noise impacts, which are defined in Information Paper E23 (https://www.gov.uk/government/publications/hs2-information-papers-environment), during the reporting period.

There were no exceedances of trigger levels as defined in Section 61 consents during the reporting period at any monitoring position.

No complaints were received during the monitoring period.

Abbreviations and Descriptions

The abbreviations, descriptions and project terminology used within this report can be found in Table 1.

Table 1: Table of Abbreviations

Acronym/Term	Definition
L _{Aeq,T}	See equivalent continuous sound pressure level
Ambient sound	A description of the all-encompassing sound at a given location and time which will include sound from many sources near and far. Ambient sound can be quantified in terms of the equivalent continuous sound pressure level, $L_{pAeq,T}$
Decibel(s), or dB	Between the quietest audible sound and the loudest tolerable sound there is a million to one ratio in sound pressure (measured in Pascal (Pa)). Because of this wide range, a level scale called the decibel (dB) scale, based on a logarithmic ratio, is used in sound measurement. Audibility of sound covers a range of approximately 0-140dB.
Decibel(s) A- weighted, or dB(A)	The human ear system does not respond uniformly to sound across the detectable frequency range and consequently instrumentation used to measure sound is weighted to represent the performance of the ear. This is known as the 'A weighting' and is written as 'dB(A)'.
Equivalent continuous sound pressure level, or L _{Aeq,T}	An index used internationally for the assessment of environmental sound impacts. It is defined as the notional unchanging level that would, over a given period of time (T), deliver the same sound energy as the actual time-varying sound over the same period. Hence fluctuating sound levels can be described in terms of an equivalent single figure value, typically expressed as a decibel level.
Exclusion of data	Measurement of noise levels can be affected by weather conditions such as prolonged periods of rain, winds speeds higher than 5m/s and snow/ice ground cover. Noise levels measured during these periods are considered not representative of normal noise conditions at the site and, for the purposes of this report, are excluded from the assessment of exceedances and calculation of typical noise levels and are also greyed out in charts. Identifiable incongruous noise and vibration events not attributable to HS2 construction noise are also excluded.
Façade	A facade noise level is the noise level 1m in front of a large reflecting surface. The effect of reflection, is to produce a slightly higher (typically +3 dB) sound level than it would be if the reflecting surface was not there.
Free-field	A free-field noise level is the noise level measured at a location where no reflective surfaces, other than the ground, lies within 3.5 metres of the microphone position.
LOAEL	Lowest Observed Adverse Effect Level - the level above which adverse effects on health and quality of life can be detected.
Peak particle velocity, or PPV	Instantaneous maximum velocity reached by a vibrating element as it oscillates about its rest position. The PPV is a simple indicator of perceptibility and risk of damage to structures due to vibration. It is usually measured in mm/s.
SOAEL	Significant Observed Adverse Effect Level - the level above which significant adverse effects on health and quality of life occur.
Sound pressure level	The parameter by which sound levels are measured in air. It is measured in decibels. The threshold of hearing has been set at 0dB, while the threshold of pain is approximately 120dB. Normal speech is approximately 60dB at a distance of 1 metre and a change of 3dB in a time varying sound signal is commonly regarded as being just detectable. A change of 10dB is subjectively twice, or half, as loud.
Vibration dose value, or VDV	An index used to evaluate human exposure to vibration in buildings. While the PPV provides information regarding the magnitude of single vibration events, the VDV provides a measure of the total vibration experienced over a specified period of time (typically 16h daytime and 8h night-time). It takes into account the magnitude, the number and the duration of vibration events and can be used to quantify exposure to continuous, impulsive, occasional and intermittent vibration. The vibration dose value is measured in m/s ^{1.75} .

1 Introduction

- 1.1.1 HS2 is required to undertake noise (and vibration) monitoring as necessary to comply with the requirements of the High Speed Rail (London-West Midlands) Environmental Minimum Requirements, including specifically Annex 1: Code of Construction Practice, in addition to any monitoring requirements arising from conditions imposed through consents under Section 61 of the Control of Pollution Act, 1974 or through Undertakings & Assurances given to third parties. Such monitoring may be undertaken for the following purposes:
 - monitoring the impact of construction works;
 - to investigate complaints, incidents and exceedance of trigger levels; or
 - monitoring the effectiveness of noise and vibration control measures.
- 1.1.2 Monitoring data and interpretive reports are to be provided to each relevant local authority on a monthly basis and shall include a summary of the construction activities occurring, the data recorded over the monitoring period, any complaints received, any periods in exceedance of agreed trigger levels, the results of any investigations and any actions taken or mitigation measures implemented. This report provides noise data, and interpretation thereof, for monitoring carried out by HS2 within the Solihull Metropolitan District (SMD) for the period 1st to 31st December 2021.
- 1.1.3 Construction sites in the local authority area where monitoring was undertaken during this period include:
 - Birmingham Interchange Highway / WP062 worksite, reference WP062 (see plan 1 in Appendix A), where work activities included:
 - o drainage works on the ramp up to the new bridge over the M42;
 - new highway construction works at the entrance to Birmingham Business
 Park; and
 - o landscaping works on the "longabout" and around the new attenuation pond.
 - A452 worksite, reference A452 (see plan 2 in Appendix A), where there were no work activities within this vicinity throughout December 2021.
 - Park Lane worksite, reference PL (see plan 2 and 3 in Appendix A), where work activities included:
 - Installation of headwall to pond chainage;
 - Finishing haul route by dam;
 - Installation of haul route;
 - Installation of culvert crossing;

- Coring works, trial holes and v-ditch (small ditch used for surface water drainage) on the haul route is ongoing;
- o Completion of the southbound element of the roundabout; and
- The joining process 'tie in' of the roundabout to Park Lane, including resurfacing.
- Balsall Common Viaduct worksite, reference BCV (see plan 4 in Appendix A), where work activities included:
 - Beechwood rigid inclusion (10m holes dug using a large piling rig/hole borer, filled with concrete to eventually support an embankment);
 - Sandbags installation to ditch pond at chainage;
 - o Installation of haul route; and
 - o Installation of control points.
- Carol Green Rail Underbridge worksite, reference CGRU (see plan 4 in Appendix A), where work activities included:
 - o Exclusion zone set-up; and
 - o Site maintenance.
- Waste Lane Overbridge and Satellite worksite, reference WLOS (see plan 4 in Appendix A), where work activities included:
 - Cable installation including small excavation; and
 - o Work on barrette piling including use of excavators and dumpers.
- 1.1.4 Further works, where monitoring did not take place, were also undertaken at the following locations:
 - Between Meriden Road & Diddington Lane (diversion of water main).
 - Birmingham Interchange Station (electricity works).
- 1.1.5 Applicable standards, guidance, and monitoring methodology are outlined in the construction noise and vibration monitoring methodology report which can be found at the following location

 https://www.gov.uk/government/collections/monitoring-the-environmental-effects-of-hs2. Noise and vibration monitoring reports for previous months can also be

1.2 Measurement Locations

found at this location.

1.2.1 Twelve (12) noise and two (2) vibration monitoring installations were active in December in the SMD area. Table 2 summarises the position of noise and vibration monitoring installations within the SMD area in December 2021.

1.2.2 Maps showing the position of noise monitoring installations are presented in Appendix B.

Table 2: Monitoring Locations

Worksite Reference	Measurement Reference	Address					
WP062	WP062-1	Birmingham Business Park, Solihull Parkway, Solihull					
	WP062-2	Holiday Inn Express, Bickenhill Parkway, Solihull					
A452 compound	A452-1	Marsh House Farm, Brandocks Marsh, Solihull					
Park Lane	PL-1	Park Lane, Balsall Common, Solihull					
	PL-2	The Laurel, Lavender Hall Lane, Balsall Common, Solihull					
	PL-3	Holly Acre Lodge, Kenilworth Road, Solihull					
	PL-4	Top Lodge, Kenilworth Road, Solihull					
Balsall Common Viaduct	BCV-1	Cherry Tree Cottage, Truggist Lane, Balsall Common, Solihull					
Carol Green Rail Underbridge	CGRU-1	The Stables, Truggist Lane, Balsall Common, Solihull					
Waste Lane	WLOS-1	19 Hodgetts Lane, Burton Green, Warwickshire					
Overbridge and Satellite	WLOS-2	Little Beanitt Farm, Waste Lane, Balsall Common, Solihull					
	WLOS-3	Dragonflies, Waste Lane, Balsall Common, Solihull					
	WLOS-V1	19 Hodgetts Lane, Burton Green, Warwickshire					
	WLOS-V2	Little Beanitt Farm, Waste Lane, Balsall Common, Solihull					

2 Summary of Results

2.1 Summary of Measured Noise Levels

2.1.1 Table 3 presents a summary of the measured noise levels at each monitoring location over the reporting period. The $L_{Aeq,T}$ is presented for each of the relevant time periods averaged over the calendar month, along with the highest single period $L_{Aeq,T}$ that was found to occur within the month.

Table 3: Summary of Measured dB L_{Aeq} Data over the Monitoring Period

Worksite Reference	Measurement Reference	Site Address	Free-field or Façade Measurement	,	Weekday Average L _{Aeq,T} (highest day L _{Aeq,T})			Saturday Average L _{Aeq,T} (highest day L _{Aeq,T})					Sunday / Public Holiday Average L _{Aeq,T} (highest day L _{Aeq,T})		
				0700 - 0800	0800 - 1800	1800 - 1900	1900 - 2200	2200 - 0700	0700 - 0800	0800 - 1300	1300 - 1400	1400 - 2200	2200 - 0700	0700 - 2200	2200 - 0700
WP062	WP062-1	Birmingham	Free-field	60.8	61.6	60.9	59.5	57.5	58.5	63.9	63.7	61.7	57.0	61.4	59.1
		Business Park		(65.1)	(67.0)	(66.2)	(64.9)	(66.5)	(61.6)	(65.0)	(65.5)	(69.4)	(66.3)	(70.5)	(69.3)
	WP062-2	Holiday Inn	Free-field	63.4	64.4	63.2	62.1	60.3	58.8	62.6	62.1	62.1	57.5	61.3	60.0
		Express		(66.4)	(70.8)	(68.0)	(66.4)	(65.5)	(60.1)	(64.7)	(64.5)	(66.1)	(61.6)	(63.7)	(71.8)
A452		Marsh House Farm	Free-field	49.7	49.6	47.3	46.6	44.1	46.8	48.8	47.7	46.7	43.7	47.8	42.5
Compound				(54.3)	(52.7)	(51.3)	(51.6)	(53.9)	(49.7)	(53.3)	(52.5)	(53.2)	(53.7)	(50.9)	(48.8)
Park Lane	PL-1	Park Lane	Free-field	56.2	60.4	48.8	48.4	46.0	48.4	51.6	52.3	55.6	46.4	48.8	45.5
				(69.8)	(62.7)	(53.6)	(59.1)	(52.6)	(48.6)	(51.9)	(53.4)	(68.8)	(49.9)	(53.0)	(50.7)
	PL-2	The Laurel	Free-field	48.0	49.4	47.4	46.6	42.4	46.2	49.4	49.4	48.5	43.8	47.9	40.5
				(53.6)	(52.6)	(50.2)	(54.2)	(53.3)	(46.6)	(49.7)	(49.9)	(53.0)	(54.0)	(51.8)	(48.3)
	PL-3	Holly Acre Lodge	Free-field	53.7	54.1	52.0	50.4	46.9	50.2	52.6	53.8	52.4	47.9	51.3	45.7
				(59.0)	(57.3)	(55.8)	(54.3)	(57.2)	(52.5)	(55.5)	(55.9)	(56.2)	(56.9)	(54.5)	(52.7)
	PL-4	Top Lodge	Free-field	60.3	60.6	58.2	56.0	53.8	55.7	57.1	57.8	57.5	53.3	56.9	53.4
				(66.1)	(64.6)	(62.8)	(60.7)	(64.2)	(58.2)	(58.3)	(61.5)	(63.5)	(58.0)	(61.8)	(58.4)
Balsall	BCV-1	Cherry Tree	Free-field	51.3	55.0	50.3	49.7	47.5	49.4	50.9	51.4	50.9	46.3	49.5	47.0
Common Viaduct		Cottage		(56.5)	(59.7)	(52.8)	(52.4)	(55.4)	(49.8)	(51.0)	(51.6)	(53.1)	(53.4)	(52.7)	(52.2)

Worksite Reference	Measurement Reference	Site Address	Free-field or Façade Measurement	Weekday Average L _{Aeq,} т (highest day L _{Aeq,} т)		Saturday Average L _{Aeq,T} (highest day L _{Aeq,T})					Sunday / Public Holiday Average L _{Aeq,T} (highest day L _{Aeq,T})				
				0700 - 0800	0800 - 1800	1800 - 1900	1900 - 2200	2200 - 0700	0700 - 0800	0800 - 1300	1300 - 1400	1400 - 2200	2200 - 0700	0700 - 2200	2200 - 0700
Carol Green Rail Underbridge	CGRU-1	The Stables	Free-field	50.1 (54.9)	52.5 (58.3)	49.3 (54.8)	49.1 (54.5)	46.7 (56.3)	44.8 (50.9)	48.5 (52.9)	48.2 (55.7)	48.1 (55.6)	46.6 (55.7)	47.8 (54.5)	43.3 (54.6)
Waste Lane Overbridge and Satellite	WLOS-1	19 Hodgetts Lane	Façade	49.6 (61.0)	53.7 (63.1)	43.0 (50.5)	40.4 (47.9)	37.6 (55.5)	44.1 (50.3)	50.2 (53.0)	49.8 (54.7)	45.6 (54.8)	40.2 (51.4)	44.5 (51.9)	35.4 (42.3)
WP062	WLOS-2	Waste Lane (East)	Free-field	48.8 (55.9)	50.3 (53.6)	47.5 (53.1)	45.2 (57.6)	40.7 (54.0)	45.7 (46.5)	49.8 (51.1)	49.9 (51.0)	48.1 (54.0)	43.1 (52.5)	48.1 (53.2)	38.8 (45.9)
	WLOS-3	Waste Lane (West)	Free-field	54.7 (60.0)	56.8 (60.6)	55.6 (61.1)	53.6 (59.4)	47.9 (58.4)	48.6 (48.6)	56.6 (58.5)	56.8 (58.1)	56.8 (61.6)	49.2 (54.3)	54.4 (58.6)	43.9 (47.5)

2.1.2 Table 4 presents a summary of the measured vibration levels at the monitoring location over the reporting period. The highest PPV measured during the monitoring along any axis is presented in the table.

Table 4: Summary of Measured PPV Data over the Monitoring Period

Worksite Reference	Measurement Reference	Monitor Address	Highest PPV measured in any axis, mm/s
WLOS	WLOS-V1	19 Hodgetts Lane, Burton Green, Warwickshire, CV8 1PH	0.93 (X-axis)
WLOS	WLOS-V2	Little Beanitt Farm, Waste Lane, Berkswell, Balsall Common, Solihull, CV7 7GH	0.65 (X-axis)

Appendix C presents graphs of the noise and vibration monitoring data over the month for each of the measurement locations. Noise data presented consists of the hourly L_{Aeq} values and, where relevant, the L_{Aeq,T} values (where the time period T has been taken to be the averaging period as specified in Table 1 of HS2 Information Paper E23). Vibration data presented consist of hourly PPV values. The full data set for the monitoring equipment can be found at the following location: https://data.gov.uk/dataset/24542ae7-dd44-444f-b259-871c4cc43b5e/environmental-monitoring-data.

2.2 Exceedances of the LOAEL and SOAEL

- 2.2.1 The lowest observed adverse effect level (LOAEL) is defined in the Planning Practice Guidance Noise (PPG) as the level above which "noise starts to cause small changes in behaviour and/or attitude, e.g. turning up volume of television; speaking more loudly; where there is no alternative ventilation, having to close windows for some of the time because of the noise. Potential for some reported sleep disturbance. Affects the acoustic character of the area such that there is a perceived change in the quality of life".
- 2.2.2 The significant observed adverse effect level (SOAEL) is defined in the 'Planning Practice Guidance Noise' as the level above which "noise causes a material change in behaviour and/or attitude, e.g. avoiding certain activities during periods of intrusion; where there is no alternative ventilation, having to keep windows closed most of the time because of the noise. Potential for sleep disturbance resulting in difficulty in getting to sleep, premature awakening and difficulty in getting back to sleep. Quality of life diminished due to change in acoustic character of the area."
- 2.2.3 HS2 Phase One Information Paper E23: Control of Construction Noise and Vibration sets out the LOAELs and SOAELs for construction noise.

- 2.2.4 Where reported construction noise levels exceed the LOAEL and SOAEL, relevant periods will be identified. Summary statistics to evaluate ongoing qualification for noise insulation and temporary rehousing are also presented where relevant.
- 2.2.5 Table 5 presents a summary of recorded exceedances of the LOAEL and SOAEL at each measurement location over the reporting period, including the number of exceedances during each time period.

Table 5: Summary of Exceedances of LOAEL and SOAEL

Worksite Reference	Measurement Reference	Site Address	Day (Weekday, Saturday, Sunday, Night)	Time period	Number of exceedances of LOAEL	Number of exceedances of SOAEL
WP062	WP062-1	Birmingham Business Park	All Days	All Periods	Not applicable*	Not applicable*
	WP062-2	Holiday Inn Express	All Days	All Periods	Not applicable*	Not applicable*
A452 Compound	A452-1	Marsh House Farm	All Days	All Periods	No exceedance	No exceedance
Park Lane	PL-1**	Park Lane	All Days	All Periods	No exceedance	No exceedance
	PL-2**	The Laurel	All Days	All Periods	No exceedance	No exceedance
	PL-3**	Holly Acre Lodge	All Days	All Periods	No exceedance	No exceedance
Park Lane	PL-4	Top Lodge	Weekday	0800-1800	4	No exceedance
Balsall Common Viaduct	BCV-1**	Cherry Tree Cottage	All Days	All Periods	No exceedance	No exceedance
Carol Green Rail Underbridge	CGRU-1**	The Stables	All Days	All Periods	No exceedance	No exceedance
Waste Lane Overbridge	WLOS-1**	19 Hodgetts Lane	All Days	All Periods	No exceedance	No exceedance
and Satellite	WLOS-2	Waste Lane (East)	All Days	All Periods	No exceedance	No exceedance
	WLOS-3	Waste Lane (West)	All Days	All Periods	No exceedance	No exceedance

^{*}The defined LOAEL and SOAEL criteria are not applicable to non-residential properties.

^{**}A distance correction has been applied when calculating exceedances of the LOAEL and SOAEL.

2.2.6 Four (4) exceedances of the LOAEL were recorded due to HS2 construction works during December 2021 at Park Lane worksite. No exceedances of the SOAEL were recorded during December 2021 across all worksites.

2.3 Exceedances of Trigger Level

2.3.1 Table 6 provides a summary of exceedances of the S61 trigger noise levels determined to be due to HS2 related construction noise measured during the reporting period, along with the findings of any investigation.

Table 6: Summary of Exceedances of Trigger Levels

Complaint Reference Number (if applicable)	Worksite Reference	Date and Time Period	Identified Source	Results of Investigation (including noise monitoring results)	Actions Taken
-	-	-	-	-	-

2.4 Complaints


2.4.1 Table 7 provides a summary of complaint information related to noise and vibration received during the reporting period, along with the findings of any investigation.

Table 7: Summary of Complaints

Complaint Reference Number		•	Results of Investigation	Actions Taken
-	-	-	-	-


Appendix A Site Locations

Worksite Identification Plan - Overview




Active Worksites

HS2 Worksite Identification Plan - 1




Worksite Identification Plan - 2



Worksite Identification Plan - 3




Worksite Identification Plan - 4



Legend
Active Worksites

Appendix B Monitoring Locations

Noise Monitoring Plan - 1




Noise Monitoring Plan - 2



Noise Monitoring Plan - 3



Noise Monitoring Plan - 4





Appendix C Data


Noise


The following graphs show the hourly measured ambient noise level $L_{Aeq,1h}$ and, where relevant, the averaged noise level $L_{Aeq,T}$ values, where the time period T is as specified in Table 1 of HS2 Information Paper E23. Periods with adversely weather affected noise levels are greyed out and have been excluded from the calculation of the $L_{Aeq,T}$ values in Table 3 of the main report.


Worksite: WP062 - Monitoring Ref: WP062-1
















Worksite: WP062 - Monitoring Ref: WP062-2















Note: Missing data during the week were due to loss of power to the monitor caused by insufficient sunlight to charge ancillary batteries.


Worksite: A452 Compound - Monitoring Ref: A452-1















Worksite: PL - Monitoring Ref: PL-1






Note: Missing data throughout the week were due to loss of power to the monitor caused by insufficient solar energy to charge ancillary batteries.







Note: Missing data throughout the week were due to loss of power to the monitor caused by insufficient solar energy to charge ancillary batteries.





Note: Missing data throughout the week were due to loss of power to the monitor caused by insufficient solar energy to charge ancillary batteries.

Worksite: PL - Monitoring Ref: PL-2















Worksite: PL - Monitoring Ref: PL-3












Note: Missing data throughout the week were due to loss of power to the monitor caused by insufficient solar energy to charge ancillary batteries. High noise levels at 02:00 on Monday 20th December were due to communication error between the noise equipment and the embedded system.





Worksite: PL - Monitoring Ref: PL-4




Note: Missing data at 00:00 on Wednesday 1st December were due to monitoring equipment updating and synchronizing.











Vibration

The following graphs show the hourly measured peak particle velocity PPV recorded during the monitoring period. The graphs show the highest PPV of the three orthogonal axis x, y and z. Where high values of PPV were caused by local interference with the vibration monitor, which are not representative of HS2 construction works, these values have been greyed out in the following charts and have been excluded to calculate values in **Error! Reference source not found.** of the main report.


Worksite: BCV - Monitoring Ref: BCV-1








Note: Missing data between 13:00 on Tuesday 14th December and 11:00 on Friday 31st December were due to loss of power to the monitor caused by insufficient sunlight to charge ancillary batteries.




Note: Missing data between 13:00 on Tuesday 14th December and 11:00 on Friday 31st December were due to loss of power to the monitor caused by insufficient sunlight to charge ancillary batteries.


Worksite: CGRU- Monitoring Ref: CGRU-1



Note: Missing data throughout the week were due to loss of power to the monitor caused by insufficient solar energy to charge ancillary batteries.














Worksite: WLOS - Monitoring Ref: WLOS-1














Note: Missing data throughout the week were due to loss of power to the monitor caused by insufficient solar energy to charge ancillary batteries.

Worksite: WLOS - Monitoring Ref: WLOS-2







Note: Missing data between 03:00 on Sunday 12th December and 10:00 on Monday 13th December were due to power outage at the residential property.




Note: Missing data between 03:00 on Sunday 12^{th} December and 10:00 on Monday 13^{th} December were due to power outage at the residential property.







Worksite: WLOS - Monitoring Ref: WLOS-3





Note: Missing data during the week were due to loss of power to the monitor caused by insufficient sunlight to charge ancillary batteries.



Note: Missing data during the week were due to loss of power to the monitor caused by insufficient sunlight to charge ancillary batteries.










Vibration

The following graphs show the hourly measured peak particle velocity PPV recorded during the monitoring period. The graphs show the highest PPV of the three orthogonal axes x, y and z. Where high values of PPV were caused by local interference with the vibration monitor, which are not representative of HS2 construction works, these values have been greyed out in the following charts and have been excluded to calculate values in Table 4 of the main report.

Worksite: WLOS - Monitoring Ref: WLOS-V1









Note: Missing data during the week were due to loss of power to the monitor caused by insufficient sunlight to charge ancillary batteries.




Note: Missing data during the week were due to loss of power to the monitor caused by insufficient sunlight to charge ancillary batteries.




Worksite: WLOS - Monitoring Ref: WLOS-V2





Note: Missing data between 07:00 on Sunday 12th December and 10:00 on Monday 13th December were due to power outage at the residential property.



Note: Missing data between 07:00 on Sunday 12^{th} December and 10:00 on Monday 13^{th} December were due to power outage at the residential property.



