Review of an Environmental Permit for an Installation subject to Chapter II of the Industrial Emissions Directive under the Environmental Permitting (England & Wales) Regulations 2016 (as amended)

# Decision document recording our decision-making process following review of a permit

The Permit number is:	EPR/NP3139RH
The Operator is:	AB Agri Limited
The Installation is:	ABN Langwathby
This Variation Notice number is:	EPR/NP3139RH/V002

## What this document is about

Article 21(3) of the Industrial Emissions Directive (IED) requires the Environment Agency to review conditions in permits that it has issued and to ensure that the permit delivers compliance with relevant standards, within four years of the publication by the European Commission of updated decisions on best available techniques (BAT) Conclusions.

We have reviewed the permit for this installation against the BAT Conclusions for the Food, Drink and Milk Industries published on 4<sup>th</sup> December 2019 in the Official Journal of the European Union. In this decision document, we set out the reasoning for the consolidated variation notice that we have issued.

It explains how we have reviewed and considered the techniques used by the Operator in the operation and control of the plant and activities of the installation. It is our record of our decision-making process and shows how we have taken into account all relevant factors in reaching our position.

As well as considering the review of the operating techniques used by the Operator for the operation of the plant and activities of the installation, the consolidated variation notice takes into account and brings together in a single document all previous variations that relate to the original permit issue. Where this has not already been done, it also modernises the entire permit to reflect the conditions contained in our current generic permit template.

The introduction of new template conditions makes the Permit consistent with our current general approach and with other permits issued to Installations in this sector. Although the wording of some conditions has changed, while others have been deleted because of the new regulatory approach, it does not reduce the level of environmental protection achieved by the Permit in any way. In this document, we therefore address only our determination of substantive issues relating to the new BAT Conclusions.

We try to explain our decision as accurately, comprehensively and plainly as possible. Achieving all three objectives is not always easy, and we would welcome any feedback as to how we might improve our decision documents in future.

## How this document is structured

- 1. Our decision
- 2. How we reached our decision
- 3. The legal framework
- 4. Annex 1 Review of operating techniques within the Installation against BAT Conclusions.
- 5. Annex 2 Review and assessment of changes that are not part of the BAT Conclusions derived permit review
- 6. Annex 3 Improvement Conditions

# 1 Our decision

We have decided to issue the Variation Notice to the Operator. This will allow the Operator to continue to operate the Installation, subject to the conditions in the Consolidated Variation Notice that updates the whole permit.

We consider that, in reaching our decision, we have taken into account all relevant considerations and legal requirements and that the varied permit will ensure that a high level of protection is provided for the environment and human health.

The Consolidated Variation Notice contains many conditions taken from our standard Environmental Permit template including the relevant annexes. We developed these conditions in consultation with industry, having regard to the legal requirements of the Environmental Permitting Regulations and other relevant legislation. This document does not therefore include an explanation for these standard conditions. Where they are included in the Notice, we have considered the techniques identified by the operator for the operation of their installation, and have accepted that the details are sufficient and satisfactory to make those standard conditions appropriate. This document does, however, provide an explanation of our use of "tailor-made" or installation-specific conditions, or where our Permit template provides two or more options.

# 2 How we reached our decision

### 2.1 <u>Requesting information to demonstrate compliance with BAT</u> <u>Conclusion techniques</u>

We issued a Notice under Regulation 61(1) of the Environmental Permitting (England and Wales) Regulations 2016 (a Regulation 61 Notice) on 04/05/2021 requiring the Operator to provide information to demonstrate where the operation of their installation currently meets, or how it will subsequently meet, the revised standards described in the relevant BAT Conclusions document.

The Notice required that where the revised standards are not currently met, the operator should provide information that:

- describes the techniques that will be implemented before 4 December 2023, which will then ensure that operations meet the revised standards, or
- justifies why standards will not be met by 4 December 2023, and confirmation of the date when the operation of those processes will cease within the Installation or an explanation of why the revised BAT standards are not applicable to those processes, or
- justifies why an alternative technique will achieve the same level of environmental protection equivalent to the revised BAT standards described in the BAT Conclusions.

Where the Operator proposed that they were not intending to meet a BAT standard that also included a BAT Associated Emission Level (BAT-AEL) described in the BAT Conclusions Document, the Regulation 61 Notice required that the Operator make a formal request for derogation from compliance with that BAT-AEL (as provisioned by Article 15(4) of IED). In this circumstance, the Notice identified that any such request for derogation must be supported and justified by sufficient technical and commercial information that would enable us to determine acceptability of the derogation request.

The Regulation 61 Notice response from the Operator was received on 26/07/2021.

We considered that the response did not contain sufficient information for us to commence determination of the permit review. We therefore issued a further information request to the Operator. Suitable further information was provided by the Operator on 15/09/2021.

We considered it was in the correct form and contained sufficient information for us to begin our determination of the permit review.

The Operator made no claim for commercial confidentiality. We have not received any information in relation to the Regulation 61 Notice response that appears to be confidential in relation to any party.

2.2 <u>Review of our own information in respect to the capability of the</u> <u>Installation to meet revised standards included in the BAT Conclusions</u> document

Based on our records and previous experience in the regulation of the installation we have no reason to consider that the Operator will not be able to comply with the techniques and standards described in the BAT Conclusions.

#### 2.3 <u>Requests for further information during determination</u>

Although we were able to consider the Regulation 61 Notice response generally satisfactory at receipt, we did in fact need more information in order to complete our permit review assessment, and issued a further information request on 22/10/2021. A copy of the further information request was placed on our public register.

The Operator provided a response on 12/11/2021 which included an updated site plan and risk assessments which include details of control measures in place to demonstrate compliance with BAT 8, this response was placed on our public register.

# 3 The legal framework

The Consolidated Variation Notice will be issued under Regulations 18 and 20 of the EPR. The Environmental Permitting regime is a legal vehicle which delivers most of the relevant legal requirements for activities falling within its scope. In particular, the regulated facility is:

- an *installation* as described by the IED;
- subject to aspects of other relevant legislation which also have to be addressed.

We consider that, in issuing the Consolidated Variation Notice, it will ensure that the operation of the Installation complies with all relevant legal requirements and that a high level of protection will be delivered for the environment and human health.

We explain how we have addressed specific statutory requirements more fully in the rest of this document.

## Annex 1: decision checklist regarding relevant BAT Conclusions

BAT Conclusions for the Food, Drink and Milk Industries, were published by the European Commission on 4 December 2019.

There are 37 BAT Conclusions.

BAT 1 – 15 are General BAT Conclusions (Narrative BAT) applicable to all relevant Food, Drink and Milk Installations in scope.

BAT 16 – 37 are sector-specific BAT Conclusions, including Best Available Techniques Associated Emissions Levels (BAT-AELs) and Associated Environmental Performance Levels (BAT-AEPLs):

BAT 16 & 17	BAT Conclusions for Animal Feed
BAT 18 – 20	BAT Conclusions for Brewing
BAT 21 – 23	BAT Conclusions for Dairies
BAT 24	BAT Conclusions for Ethanol Production
BAT 25 & 26	BAT Conclusions for Fish and Shellfish Processing
BAT 27	BAT Conclusions for Fruit and Vegetable Processing
BAT 28	BAT Conclusions for Grain Milling
BAT 29	BAT Conclusions for Meat Processing
BAT 30 – 32	BAT Conclusions for Oilseed Processing and Vegetable Oil Refining
BAT 33	BAT Conclusions for Soft Drinks and Nectar/Fruit Juice Processed from Fruit and Vegetables
BAT 34	BAT Conclusions for Starch Production
BAT 35 – 37	BAT Conclusions for Sugar Manufacturing

This annex provides a record of decisions made in relation to each relevant BAT Conclusion applicable to the installation. This annex should be read in conjunction with the Consolidated Variation Notice.

The overall status of compliance with the BAT conclusion is indicated in the table as:

#### NA – Not Applicable

**CC** – Currently Compliant

FC – Compliant in the future (within 4 years of publication of BAT Conclusions) NC – Not Compliant

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
1	Environmental Management System - Improve overall environmental performance. Implement an EMS that incorporates all the features as described within BATc 1.		The operator has provided information to support compliance with BATc 1. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 1. The operator has an environmental management system (EMS) which is externally accredited to ISO 14001 and ISO 50001.
2	EMS Inventory of inputs & outputs. Increase resource efficiency and reduce emissions. Establish, maintain and regularly review (including when a significant change occurs) an inventory of water, energy and raw materials consumption as well as of waste water and waste gas streams, as part of the environmental management system (see BAT 1), that incorporates all of the features as detailed within the BATcs.	CC	The operator has provided information to support compliance with BATc 2. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 2. The operator is externally accredited to ISO14001 and ISO50001. The Site holds Performance Indicator Monitoring Procedures for Water, Energy, Air Pollution; Waste Control and Disposal Procedures which form part of the National and Site EMS system. The EMS is under regular review.
3	Monitoring key process parameters at key locations for emissions to water. For relevant emissions to water as identified by the inventory of waste water streams (see BAT 2), BAT is to monitor key process parameters (e.g. continuous monitoring of waste water flow, pH and temperature) at key locations (e.g. at the inlet and/or outlet of the pre-treatment, at the inlet to the final treatment, at the point where the emission leaves the installation).	СС	The operator has provided information to support compliance with BATc 3. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 3. There are no discharges to surface water. Surface water runoff, boiler blowdown and vehicle wash discharge to sewer via a three stage interceptor.

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
			Annual sampling is undertaken to demonstrate compliance against the limits within the Trade Effluent Discharge Consent with sewerage undertaker (United Utilities).
4	Monitoring emissions to water to the required frequencies and standards. BAT is to monitor emissions to water with at least the frequency given and in accordance with EN standards. If EN standards are not available, BAT is to use ISO, national or other international standards that ensure the provision of data of an equivalent scientific quality.	NA	No direct discharges to surface water from the site. For the discharge to sewer; chloride is not a parameter of concern for this installation. No monitoring is required for compliance with the BATc.
5	Monitoring channelled emissions to air to the required frequencies and standards. BAT is to monitor channelled emissions to air with at least the frequency given and in accordance with EN standards.	CC	<ul> <li>The operator has provided information to support compliance with BATc 5. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 5.</li> <li>The site undertakes annual MCERTS testing of air emissions for total particulates from coolers and grinders using an approved contractor following EN 13284-1 standard.</li> <li>The requirement for annual monitoring of particulates has been included in the permit in order to ensure compliance with BATc 5.</li> </ul>
6	<b>Energy Efficiency</b> In order to increase energy efficiency, BAT is to use an energy efficiency plan (BAT 6a) and an appropriate combination of the	СС	The operator has provided information to support compliance with BATc 6. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 6.

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement		
	common techniques listed in technique 6b within the table in the BATc.		The operator is externally accredited to ISO50001.		
7	Water and wastewater minimisation         In order to reduce water consumption and the volume of waste water discharged, BAT is to use BAT 7a and one or a combination of the techniques b to k given below.         (a) water recycling and/or reuse         (b) Optimisation of water flow         (c) Optimisation of water nozzles and hoses         (d) Segregation of water streams         Techniques related to cleaning operations:         (e) Dry cleaning         (f) Pigging system for pipes         (g) High-pressure cleaning         (h) Optimisation of chemical dosing and water use in cleaning-in-place (CIP)         (i) Low-pressure foam and/or gel cleaning         (j) Optimised design and construction of equipment and process areas         (k) Cleaning of equipment as soon as possible		The operator has provided information to support compliance with BATc 7. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 7. Animal Feed Manufacture is essentially a dry process, with low water usage and limited potential for water saving and application of BAT techniques. The site uses a recirculation system to recycle boiler water, and utilises dry cleaning techniques such as vacuuming.		
8	<b>Prevent or reduce the use of harmful substances</b> In order to prevent or reduce the use of harmful substances, e.g. in cleaning and disinfection, BAT is to use one or a combination of the techniques given below.	СС	The operator has provided information to support compliance with BATc 8. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 8.		

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul> <li>(a) Proper selection of cleaning chemicals and/or disinfectants</li> <li>(b) Reuse of cleaning chemicals in cleaning-in-place (CIP)</li> <li>(c) Dry cleaning</li> <li>(d) Optimised design and construction of equipment and process areas</li> </ul>		Vehicle mats are used as a method to disinfect wheels at the site, when required for biosecurity reasons. The disinfectants used in this process are DEFRA approved. The Operator uses limited volumes of disinfectant; ensures the disinfectant is either absorbed or evaporated; and that no leaks or spills outside of the vehicle mat boundary occurs. Disinfectant Virkon S is stored as a concentrated powder and diluted on site. The dilution ratio is 1:100 which provides Virkon S at 1%, the powder is dissolved in an IBC with secondary containment/ bunded (110% capacity) and spill kit are made available in the vicinity. The Operator has a quality assurance document and risk assessments which include these control measures.
9	<b>Refrigerants</b> In order to prevent emissions of ozone-depleting substances and of substances with a high global warming potential from cooling and freezing, BAT is to use refrigerants without ozone depletion potential and with a low global warming potential.	NA	There is no refrigerants used on site.
10	Resource efficiencyIn order to increase resource efficiency, BAT is to use one or a combination of the techniques given below:(a) Anaerobic digestion(b) Use of residues(c) Separation of residues(d) Recovery and reuse of residues from the pasteuriser(e) Phosphorus recovery as struvite(f) Use of waste water for land spreading	CC	The operator has provided information to support compliance with BATc 10. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 10. Residues and by products from process manufacture are reworked into the process subject to quality assurance procedures for feed safety.

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
11	Waste water buffer storage In order to prevent uncontrolled emissions to water, BAT is to provide an appropriate buffer storage capacity for waste water.	NA	The discharge volumes from this installation are low, the minimal process effluent produced is discharged to sewer, additional buffer storage capacity is not applicable. However, the site has a 3 stage interceptor on the vehicle wash which routes to foul sewer.
12	Emissions to water – treatment In order to reduce emissions to water, BAT is to use an appropriate combination of the techniques given below. Preliminary, primary and general treatment (a) Equalisation (b) Neutralisation (c) Physical separate (eg screens, sieves, primary settlement tanks etc) Aerobic and/or anaerobic treatment (secondary treatment) (d) Aerobic and/or anaerobic treatment (eg activated sludge, aerobic lagoon etc) (e) Nitification and/or denitrification (f) Partial nitration - anaerobic ammonium oxidation Phosphorus recovery and/or removal (g) Phosphorus recovery as struvite (h) Precipitation (i) Enhanced biological phosphorus removal Final solids removal (j) Coagulation and flocculation	NA	No emission to water, as all process effluent and surface runoff are discharged to sewer. The site does use BAT techniques: b) Boiler blowdown water is diluted in a three part interceptor with the water from the vehicle wash which has sufficient flow rate to guarantee appropriate reduction in pH k) Suspended solids are gathered in the interceptor tank prior to discharge to the local sewerage system.

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries		Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	<ul><li>(k) Sedimentation</li><li>(I) Filtration (eg sand filtration, microfiltration, ultrafiltration)</li><li>(m) Flotation</li></ul>		
13	<ul> <li>Noise management plan</li> <li>In order to prevent or, where that is not practicable, to reduce noise emissions, BAT is to set up, implement and regularly review a noise management plan, as part of the environmental management system (see BAT 1), that includes all of the following elements: <ul> <li>a protocol containing actions and timelines;</li> <li>a protocol for conducting noise emissions monitoring;</li> <li>a protocol for response to identified noise events, eg complaints;</li> <li>a noise reduction programme designed to identify the source(s), to measure/estimate noise and vibration exposure, to characterise the contributions of the sources and to implement prevention and/or reduction measures.</li> </ul> </li> </ul>		BAT 13 is only applicable to cases where a noise nuisance at sensitive receptors is expected and/or has been substantiated, or if forms part of an existing permit requirement. There is no existing permit requirement and the site has no recent history of noise complaints therefore a noise management plan is not required.
14	Noise management         In order to prevent or, where that is not practicable, to reduce noise emissions, BAT is to use one or a combination of the techniques given below.         (a) Appropriate location of equipment and buildings         (b) Operational measures         (c) Low-noise equipment         (d) Noise control equipment		<ul> <li>The operator has provided information to support compliance with BATc 14. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 14.</li> <li>Operator uses a combination of relevant procedures: <ul> <li>Using inherently quieter machinery and processes;</li> <li>Enclosing noisy machinery and processes in buildings or acoustic enclosures;</li> <li>Cladding with acoustic panelling and impact deadening;</li> <li>Fitting attenuators on noisy airflows;</li> </ul> </li> </ul>

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	(e) Noise abatement		<ul> <li>Diffusing and slowing high speed and high pressure discharges, e.g. silencers on boiler pressure relief valves;</li> <li>Fitting vibration isolation mounts;</li> <li>Regularly maintaining the plant and machinery;</li> <li>Moving noisy plant further away from site boundaries and sensitive receptors;</li> <li>Restricting noisy activities to daytime hours; and</li> <li>Use of mounds or barriers to contain or deflect the noise.</li> </ul>
15	<ul> <li>Odour Management In order to prevent or, where that is not practicable, to reduce odour emissions, BAT is to set up, implement and regularly review an odour management plan, as part of the environmental management system (see BAT 1), that includes all of the following elements: <ul> <li>a protocol containing actions and timelines;</li> <li>a protocol for conducting odour monitoring.</li> <li>a protocol for response to identified odour incidents eg complaints;</li> <li>an odour prevention and reduction programme designed to identify the source(s); to measure/estimate odour exposure: to characterise the contributions of the sources; and to implement prevention and/or reduction measures. </li> </ul></li></ul>	NA	BAT 15 is only applicable to cases where an odour nuisance at sensitive receptors is expected and/or has been substantiated, or if forms part of an existing permit requirement. The original application EPR/NP3139RH/A001 had an odour management plan, however, the environment agency area regulator has confirmed there has been no reported odour nuisance from the site. The permit includes condition 3.3.1 which provides a mechanism to request an odour management plan should this be required.
	ANIMAL FEED MILL BAT CONLUSIONS (BAT 16-17)		
16	Energy Efficiency (green fodder only)	NA	Not applicable for this site.

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries				od, Drink and	Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	In order to increase energy efficiency is green fodder processing, BAT is to use an appropriate combination of the techniques specified in BAT 6 and of the techniques given below. (a) Use of predried fodder (b) Recycling of waste gas from the dryer (c) Use of waste heat for pre-drying			niques			
17	Emissions to air – particulates In order to reduce channelled dust emissions to air, BAT is to use one of the techniques given; a. bag filter, b. cyclone.					СС	The operator has provided information to support compliance with BATc 17. We have assessed the information provided and we are satisfied that the operator has demonstrated compliance with BATc 17.
	Parameter Specific process		Unit	(average	-AEL e over the g period)		Cooler The existing emission limit value (ELV) for the pellet cooler was 20mg/Nm <sup>3</sup> for particulate emissions. Monitoring data suggests the
		New	New plants	Existing plants		operator has complied with this ELV at the top of the BAT-AEL range. The limit of 20mg/m <sup>3</sup> will be retained in the permit.	
	Dust	Grinding	mg/Nm <sup>3</sup>	<2-5	<2-10		Grinder
		Pellet cooling		<2-20			The existing ELV for the grinder exhaust was 20 mg/Nm <sup>3</sup> for particulate emissions. As this is existing plant we believe it is appropriate to set the new ELV at the top of the range. A new ELV of 10mg/Nm <sup>3</sup> will be included in the varied permit to ensure compliance with the BAT-AEL. Monitoring data suggests the operator can comply with a tighter ELV of 10 mg/Nm <sup>3</sup> now, therefore we are including this limit within the permit from date of issue and we are choosing to not future date this BAT AEL.

BATC No.	Summary of BAT Conclusion requirement for Food, Drink and Milk Industries			Status NA/ CC / FC / NC	Assessment of the installation capability and any alternative techniques proposed by the operator to demonstrate compliance with the BAT Conclusion requirement
	Environmental Per Animal Feed	formance Level – Ener	gy Consumption for	СС	The operator has provided information to support compliance with the energy EPL. We have assessed the information provided and we are
	Product	Unit Specific energy consumption (yearly average)			satisfied that the operator has demonstrated compliance with the energy consumption for Animal Feed. The compound food figure of 0.01-0.10 is appropriate for this
	Compound food	MWh/tonne of	0.01-0.10 (1)(2)(3)		installation. The operators specific energy consumption average for 2020 – 2021 was 0.075 MWh/t, which is within the target, reflecting good energy management in place at this installation.
EPL	Dry pet food	products	0.39-0.50		
Ē	Wet pet food		0.33-0.85		
	<ol> <li>The lower end of the range can be achieved when pelleting is not applied.</li> <li>The specific energy consumption level may not apply when fish and other aquatic animals are used as raw material.</li> <li>The upper end of the range is 0.12 MWh/tonne of products for installations located in cold climates and/or when teat treatment is used for Salmonella decontamination.</li> </ol>				
	Environmental perf Animal Feed	formance level – Waste	e water discharge for	NA	Not applicable – dry process only.
EPL	Product	oduct Unit Specific waste water discharge (yearly average)			
	Wet pet food	m3/tonne of products	1.3-2.4		

## Annex 2: Review and assessment of changes that are not part of the BAT Conclusions derived permit review

#### Updating permit during permit review consolidation

We have made the following administrative change to the permit

- Activity name
- Introductory note (updated)
- Site plan (updated)
  - Table S1.1 overhaul
    - Activity Reference (AR) renumbering
    - Updated listed activities
    - o Addition of production capacity
    - Directly associated activities (DAAs) standardisation

We have updated permit conditions to those in the current generic permit template as a part of permit consolidation. The conditions will provide the same level of protection as those in the previous permit.

#### Capacity Threshold

The Environment Agency is looking to draw a "line in the sand" for permitted production capacity; a common understanding between the Operator and regulator for the emissions associated with a (maximum) level of production, whereby the maximum emissions have been demonstrated as causing no significant environmental impact.

We have included a permitted production level (capacity) within table S1.1 of the permit for the section 6.8 listed activity and we need to be confident that the level of emissions associated with this production level have been demonstrated to be acceptable.

The existing H1 assessment of particulate emissions to air remains valid for the capacity threshold now placed within table S1.1 of the permit.

#### Details of all emissions to Air

We asked the operator to list all emission points to air from the installation in the Regulation 61 notice. And to provide a site plan indicating the locations of all air emission points.

The operator has provided an up to date air emission plan.

The vents numbered A4 - A10 and A12 have been grouped as raw material storage tank vents in Table S3.1 as these vents are not monitored for any parameters and have no limits set in the permit.

#### Implementing the requirements of the Medium Combustion Plant Directive

We asked the Operator to provide information on all combustion plant on site in the Regulation 61 Notice as follows:

• Number of combustion plant (CHP engines, back-up generators, boilers);

- Size of combustion plant rated thermal input (MWth)
- Date each combustion plant came into operation

1. Rated thermal input (MW) of the	1.25
medium combustion plant.	
2. Type of the medium combustion plant (diesel engine, gas turbine, dual fuel engine, other engine or other medium combustion plant).	Boiler
3. Type and share of fuels used according to the fuel categories laid down in Annex II.	LPG
4. Date of the start of the operation of the medium combustion plant or, where the exact date of the start of the operation is unknown, proof of the fact that the operation started before 20 December 2018.	01/09/2015

The Operator provided the information in the table below:

We have reviewed the information provided and we consider that the declared combustion plant qualify as "existing" medium combustion plant.

For existing MCP with a rated thermal input of less than or equal to 5 MW, the emission limit values set out in tables 1 and 3 of Part 1 of Annex II MCPD shall apply from 1 January 2030.

We have included the appropriate emission limit values for existing medium combustion plant as part of this permit review. See Table S3.1 in the permit.

We have also included a new condition 3.1.4 within the permit which specifies the monitoring requirements for the combustion plant in accordance with the MCPD.

#### Particulate Emissions

BAT-AELs are derived for those substances identified as key environmental issues during the BREF review process.

If the operator has identified current compliance against BAT-AELs we will implement the relevant emission limit value (ELV) from the date of permit issue. This is relevant for emission points A1 and A3 against BAT 17 for particulate emissions from the coolers and grinders.

We have added an improvement condition (IC1) for size fractionation of particulate emissions because a BAT-AEL applies for dust emissions to air. The justification for this IC is that there are a number of activities within the FDM sector which may result in release of particulates to air e.g. drying, milling and grinding. Overall there is little available information on how much fine particulates are released. This IC is a one-off exercise requiring operators to monitor and report on the fractions of fine particulate ( $PM_{10}$  and  $PM_{2.5}$ ) emissions and increase our understanding of potential health effects. Where BAT-AELS apply to multiple emission points e.g. grain milling, we may accept limited representative monitoring rather than expecting them to monitor every single emission point.

#### **Emissions to Water and Water Framework Directive**

We asked the Operator to provide information on all emissions to water at the installation in the Regulation 61 Notice as follows;

- Identify any effluents which discharge directly to surface or groundwater;
- Provide an assessment of volume and quality, including results of any monitoring data available;
- and for any discharges to water / soakaway whether a recent assessment of the feasibility of connection to sewer has been carried out.

The operator has previously provided assessments for all emissions to water at the installation. The operator declares there has been no change to activities and subsequent effluents generated at the installation since this risk assessment was taken. Consequently, we agree that the original risk assessments remain valid at this time.

#### Soil & groundwater risk assessment (baseline report)

The IED requires that the operator of any IED installation using, producing or releasing "relevant hazardous substances" (RHS) shall, having regarded the possibility that they might cause pollution of soil and groundwater, submit a "baseline report" with its permit application. The baseline report is an important reference document in the assessment of contamination that might arise during the operational lifetime of the regulated facility and at cessation of activities. It must enable a quantified comparison to be made between the baseline and the state of the site at surrender.

At the definitive cessation of activities, the Operator has to satisfy us that the necessary measures have been taken so that the site ceases to pose a risk to soil or groundwater, taking into account both the baseline conditions and the site's current or approved future use. To do this, the Operator has to submit a surrender application to us, which we will not grant unless and until we are satisfied that these requirements have been met.

The Operator submitted a site condition report 'Site Condition Report – ABN Ltd Langwathby' during the original application received on 30/10/2015. The site condition report included a report on the baseline conditions as required by Article 22. We reviewed that report and considered that it adequately described the condition of the soil and groundwater at that time.

The Operator submitted a summary report which referenced the site condition report and baseline report. We have reviewed the information and we consider that it adequately describes the current condition of the soil and groundwater. Consequently, we are satisfied that the baseline conditions have not changed.

#### Hazardous Substances

Hazardous substances are those defined in Article 3 of Regulation (EC) No. 1272/2008 on classification, labelling and packaging of substances and mixtures

The operator has provided a short risk assessment on the hazardous substances stored and used at the installation. The risk assessment was a stage 1-3 assessment as detailed within EC Commission Guidance 2014/C 136/03.

The stage 1 assessment identified the hazardous substances used / stored on site. The stage 2 assessment identified if hazardous substances are capable of causing pollution. If they are capable of causing pollution they are then termed Relevant Hazardous Substances (RHS). The Stage 3 assessment identified if pollution prevention measures are fit for purpose in areas where hazardous substances are used / stored. This includes drains as well.

The outcomes of the three stage assessment identified that pollution of soil and/or ground water to be unlikely.

#### **Climate Change Adaptation**

The operator has considered if the site is at risk of impacts from adverse weather considering flooding, prolonged dry weather, high winds, extreme temperatures and lightning strikes.

The operator has submitted a climate change risk assessment, which demonstrates the severity and likelihood of the impact of potential changing climate variables results in majority are low to medium risk for the site. Power disruption had a moderate to high risk however, the site has mitigation in the form of a continuity supply agreement in place which decreases the residual risk resulting in a low to moderate risk.

We consider the climate change adaptation risk assessment to be appropriate for the installation.

#### Underground Structures

The operator has confirmed there are no underground structures at the installation.

## **Annex 3: Improvement Conditions**

Based on the information in the Operator's Regulation 61 Notice response and our own records of the capability and performance of the installation at this site, we consider that we need to set improvement conditions so that the outcome of the techniques detailed in the BAT Conclusions are achieved by the installation. These improvement conditions are set out below - justifications for them is provided at the relevant section of the decision document (Annex 1 or Annex 2).

If the consolidated permit contains existing improvement conditions that are not yet complete or the opportunity has been taken to delete completed improvement conditions then the numbering in the table below will not be consecutive as these are only the improvement conditions arising from this permit variation.

Improvement programme requirements V002		
Reference	Reason for inclusion	Justification of deadline
IC1	The Operator shall submit a written report to the Environment Agency of monitoring carried out to determine the size distribution of particulate matter in the exhaust gas emissions to air from emission points A1 and A3, identifying the fractions within the PM10 and PM2.5 ranges. The monitoring shall be carried out under representative operating conditions and shall be in accordance with EN ISO 23210 unless otherwise agreed with the Environment Agency.	12/01/2023 or other date as agreed in writing with the Environment Agency