

Construction Noise and Vibration Monthly Report – May 2022

West Northamptonshire District Council

© HS2 Ltd. gov.uk/hs2

Non-Te	echni	cal Summary	1			
Abbrev	/iatio	ns and Descriptions	2			
1	Intro	duction	3			
	1.2	Measurement Locations	5			
2	Sumr	mary of Results	6			
	2.1	Summary of Measured Noise Levels	6			
	2.2	Exceedances of the LOAEL and SOAEL	8			
	2.3	Exceedances of Trigger Level	9			
	2.4	Complaints	10			
Appen	dix A	Site Locations	11			
Appen	dix B	Monitoring Locations	17			
Appen	dix C	Data	22			
List of	table	S				
		e of Abbreviations	2			
		nitoring Locations	5 7			
Table 3: Summary of Measured dB L _{Aeq} Data over the Monitoring Period						
Table 4: Summary of Exceedances of LOAEL and SOAEL						
		lmary of Exceedances of Trigger Levels Imary of Complaints	9 10			
. 4510 0			10			

Non-Technical Summary

This Noise and Vibration Monitoring Report fulfils HS2 Limited's commitment detailed in the Environmental Minimum Requirements (EMRs), Annex 1, Code of Construction Practice, to present the results of noise and vibration monitoring carried out within West Northamptonshire District Council (WNDC) area during the month of May 2022.

Within this period monitoring was undertaken in the vicinity of the following worksites:

- Fir Tree Nursery Worksite (ref.:FTN) where Boddington Canal Feeder realignment, water management, topsoil stripping, material movement, stockpiling and establishment of site access road were underway.
- Lower Boddington Worksite (ref.:LB) where topsoil stripping, material movement, stockpiling and water management were underway.
- Chipping Warden Worksite (ref.: CW) where topsoil stripping, material movement, compound development, establishment of site access road, excavation of green tunnel, placement of green tunnel structure, temporary overbridge material movement preparation works, gate installation works, installation of waterproofing and concrete treatment were underway.
- Radstone worksite (ref.: RA) where topsoil stripping, bulk excavation, stockpiling, site access roadworks, compound maintenance, drainage and installation of temporary ponds were underway.
- A43 Brackley Worksite (ref.: A43) where main compound development works, drainage works and stockpiling were underway.

Further works, where monitoring did not take place, were undertaken at Greatworth South where access road works and top soil stripping were underway.

There were no exceedances of the HS2 threshold levels for significant noise impacts, which are defined in Information Paper E23 (https://www.gov.uk/government/publications/hs2-information-papers-environment), during the reporting period.

There were no exceedances of trigger levels as defined in section 61 consents during the reporting period at any monitoring position.

No complaints were received during the monitoring period.

Abbreviations and Descriptions

The abbreviations, descriptions and project terminology used within this report can be found in Table 1.

Table 1: Table of Abbreviations

Acronym/Term	Definition
L _{Aeq,T}	See equivalent continuous sound pressure level
Ambient sound	A description of the all-encompassing sound at a given location and time which will include sound from many sources near and far. Ambient sound can be quantified in terms of the equivalent continuous sound pressure level, $L_{pAeq,T}$
Decibel(s), or dB	Between the quietest audible sound and the loudest tolerable sound there is a million to one ratio in sound pressure (measured in Pascal (Pa)). Because of this wide range, a level scale called the decibel (dB) scale, based on a logarithmic ratio, is used in sound measurement. Audibility of sound covers a range of approximately 0-140dB.
Decibel(s) A- weighted, or dB(A)	The human ear system does not respond uniformly to sound across the detectable frequency range and consequently instrumentation used to measure sound is weighted to represent the performance of the ear. This is known as the 'A weighting' and is written as 'dB(A)'.
Equivalent continuous sound pressure level, or L _{Aeq,T}	An index used internationally for the assessment of environmental sound impacts. It is defined as the notional unchanging level that would, over a given period of time (T), deliver the same sound energy as the actual time-varying sound over the same period. Hence fluctuating sound levels can be described in terms of an equivalent single figure value, typically expressed as a decibel level.
Exclusion of data	Measurement of noise levels can be affected by weather conditions such as prolonged periods of rain, winds speeds higher than 5m/s and snow/ice ground cover. Noise levels measured during these periods are considered not representative of normal noise conditions at the site and, for the purposes of this report, are excluded from the assessment of exceedances and calculation of typical noise levels and are also greyed out in charts. Identifiable incongruous noise and vibration events not attributable to HS2 construction noise are also excluded.
Façade	A facade noise level is the noise level 1m in front of a large reflecting surface. The effect of reflection, is to produce a slightly higher (typically +3 dB) sound level than it would be if the reflecting surface was not there.
Free-field	A free-field noise level is the noise level measured at a location where no reflective surfaces, other than the ground, lies within 3.5 metres of the microphone position.
LOAEL	Lowest Observed Adverse Effect Level - the level above which adverse effects on health and quality of life can be detected.
Peak particle velocity, or PPV	Instantaneous maximum velocity reached by a vibrating element as it oscillates about its rest position. The PPV is a simple indicator of perceptibility and risk of damage to structures due to vibration. It is usually measured in mm/s.
SOAEL	Significant Observed Adverse Effect Level - the level above which significant adverse effects on health and quality of life occur.
Sound pressure level	The parameter by which sound levels are measured in air. It is measured in decibels. The threshold of hearing has been set at 0dB, while the threshold of pain is approximately 120dB. Normal speech is approximately 60dB at a distance of 1 metre and a change of 3dB in a time varying sound signal is commonly regarded as being just detectable. A change of 10dB is subjectively twice, or half, as loud.
Vibration dose value, or VDV	An index used to evaluate human exposure to vibration in buildings. While the PPV provides information regarding the magnitude of single vibration events, the VDV provides a measure of the total vibration experienced over a specified period of time (typically 16h daytime and 8h night-time). It takes into account the magnitude, the number and the duration of vibration events and can be used to quantify exposure to continuous, impulsive, occasional and intermittent vibration. The vibration dose value is measured in m/s ^{1.75} .

1 Introduction

- 1.1.1 HS2 is required to undertake noise (and vibration) monitoring as necessary to comply with the requirements of the High Speed Rail (London-West Midlands) Environmental Minimum Requirements, including specifically Annex 1: Code of Construction Practice, in addition to any monitoring requirements arising from conditions imposed through consents under Section 61 of the Control of Pollution Act, 1974 or through Undertakings & Assurances given to third parties. Such monitoring may be undertaken for the following purposes:
 - monitoring the impact of construction works;
 - to investigate complaints, incidents and exceedance of trigger levels; or
 - monitoring the effectiveness of noise and vibration control measures.
- 1.1.2 Monitoring data and interpretive reports are to be provided to each relevant local authority on a monthly basis and shall include a summary of the construction activities occurring, the data recorded over the monitoring period, any complaints received, any periods in exceedance of agreed trigger levels, the results of any investigations and any actions taken or mitigation measures implemented. This report provides noise data, and interpretation thereof, for monitoring carried out by HS2 within the West Northamptonshire District Council (WNDC) area for the period 1st to 31st May 2022.
- 1.1.3 Active construction sites in the local authority area where monitoring was undertaken during this period include:
 - Fir Tree Nursery- worksite, reference FTN (see Works Identification Plan 1 in Appendix A), where the following work activities were undertaken:
 - Boddington Canal Feeder realignment.
 - Water Management.
 - Topsoil stripping;
 - Material movement;
 - Stockpiling; and
 - Establishment of site access road.
 - Lower Boddington worksite, reference LB (see Works Identification Plan 1 in Appendix A), where the following work activities were undertaken:
 - Topsoil stripping;
 - Material movement;

- Stockpiling; and
- Water Management.
- Chipping Warden worksite, reference CW (see Works Identification Plan 2 in Appendix A), where the following work activities were undertaken:
 - Topsoil stripping;
 - Material movement;
 - Compound development;
 - Establishment of site access road;
 - Excavation of green tunnel;
 - Placement of green tunnel structure;
 - Temporary overbridge material movement preparation works;
 - Gate installation works; and
 - Installation of waterproofing and concrete treatment.
- Radstone worksite, reference RA (see Works Identification Plan 3 in Appendix A) where the following work activities were undertaken:
 - Topsoil stripping;
 - Bulk excavation;
 - Stockpiling;
 - Site access roadworks;
 - Compound maintenance;
 - Drainage works; and
 - Installation of temporary ponds.
- A43 Brackley worksite, reference A43 (see Works Identification Plan 4 in Appendix A), where the following work activities were undertaken:
 - Main compound development works.
 - Drainage works; and
 - Stockpiling.
- 1.1.4 Further works, where monitoring did not take place, were undertaken at the following locations:

- Greatworth South where the following work activities were undertaken:
 - Access road works; and
 - Topsoil stripping.
- 1.1.5 The applicable standards, guidance, and monitoring methodology are outlined in the construction noise and vibration monitoring methodology report which can be found at the following location

https://www.gov.uk/government/collections/monitoring-the-environmental-effects-of-hs2. Noise and vibration monitoring reports for previous months can also be found at this location.

1.2 Measurement Locations

- 1.2.1 Six (6) noise monitoring installations were active in May in the WNDC area. Table 2 summarises the position of noise monitoring installations within the WNDC area in May 2022.
- 1.2.2 Noise monitor location A43-N1, Whitfield, Brackley (worksite ref: A43) was relocated to monitoring location HF-N1, Hall Farm, Brackley (worksite ref: RA), on the 18th of May.
- 1.2.3 Maps showing the position of noise monitoring installations are presented in Appendix B.

Table 2: Monitoring Locations

Worksite Reference Measurement Reference		Address			
CW	CW-N1	Chipping Warden and Edgcote, Banbury			
LB	LB-N1	Lower Boddington, Daventry			
A43	A43-N1	A43, Whitfield, Brackley			
FTN FTN-N1		Fir Tree Nursery, Banbury Road, Lower Boddington			
RA RA-N1		Radstone Road, Brackley			
	HF-N1	Hall Farm, Brackley			

2 Summary of Results

2.1 Summary of Measured Noise Levels

2.1.1 Table 3 presents a summary of the measured noise levels at each monitoring location over the reporting period. The $L_{Aeq,T}$ is presented for each of the relevant time periods averaged over the calendar month, along with the highest single period $L_{Aeq,T}$ that was found to occur within the month.

Table 3: Summary of Measured dB L_{Aeq} Data over the Monitoring Period

Worksite Measurement Reference Reference		Site Address	Free-Field or Façade Measurement	Weekday Average L _{Aeq,T} (Highest Day L _{Aeq,T})			Saturday Average L _{Aeq,T} (Highest Day L _{Aeq,T})				Sunday / Public Holiday Average L _{Aeq,T} (Highest Day L _{Aeq,T})				
				0700 - 0800	0800 - 1800	1800 - 1900	1900 - 2200	2200 - 0700	0700 - 0800	0800 - 1300	1300 - 1400	1400 - 2200	2200 - 0700	0700 - 2200	2200 - 0700
CW	CW-N1	Chipping Warden and Edgcote, Banbury	Free-field	50.4 (53.6)	50.8 (53.2)	50.2 (52.9)	47.9 (58.3)	45.9 (54.8)	48.7 (49.3)	48.5 (50.3)	48.6 (53.3)	47.6 (50.7)	45.4 (55.4)	47.7 (54.6)	44.8 (49.4)
LB	LB-N1	Lower Boddington, West Northamptonshire	Free-field	51.2 (53.8)	54.1 (57.1)	50.0 (52.9)	48.9 (52.6)	48.9 (59.8)	49.9 (51.3)	49.8 (50.4)	49.9 (53.8)	49.5 (54.9)	48.8 (53.6)	49.1 (53.2)	48.9 (55.9)
A43	A43-N1	A43, Brackley, West Northamptonshire	Free field	54.6 (56.1)	54.3 (56.3)	53.8 (55.4)	52.0 (57.4)	50.3 (65.0)	51.6 (52.2)	52.7 (53.1)	52.8 (53.8)	52.8 (59.3)	46.0 (50.1)	53.6 (58.0)	48.8 (55.4)
FTN	FTN-N1	Fir Tree Nursery, Banbury Road, Lower Boddington	Free field	50.7 (62.2)	59.2 (68.3)	49.2 (53.6)	47.9 (52.9)	47.4 (59.3)	47.8 (49.3)	49.2 (53.7)	53.0 (66.3)	48.7 (56.8)	48.0 (57.8)	51.5 (67.9)	47.1 (53.3)
RA	RA-N1	Radstone Road, Brackley	Free-field	51.4 (54.6)	53.9 (56.6)	51.1 (54.5)	48.9 (52.4)	44.7 (51.8)	46.6 (47.2)	51.8 (53.4)	52.3 (53.1)	48.9 (52.7)	45.0 (50.1)	49.7 (54.1)	44.5 (50.2)
	HF-N1	Hall Farm, Brackley	Free field	54.1 (56.0)	56.9 (59.8)	52.9 (53.8)	49.9 (52.7)	47.8 (54.9)	51.5 (51.9)	54.4 (54.8)	53.8 (54.9)	51.4 (54.1)	47.4 (53.2)	52.2 (55.6)	47.3 (52.6)

2.1.2 Appendix C presents graphs of the noise monitoring data over the month for each of the measurement locations. Noise data presented consists of the hourly L_{Aeq} values and, where relevant, the L_{Aeq,T} values (where the time period T has been taken to be the averaging period as specified in Table 1 of HS2 Information Paper E23). The full data set for the monitoring equipment can be found at the following location: https://data.gov.uk/dataset/24542ae7-dd44-444f-b259-871c4cc43b5e/environmental-monitoring-data.

2.2 Exceedances of the LOAEL and SOAEL

- 2.2.1 The lowest observed adverse effect level (LOAEL) is defined in the Planning Practice Guidance Noise (PPG) as the level above which "noise starts to cause small changes in behaviour and/or attitude, e.g. turning up volume of television; speaking more loudly; where there is no alternative ventilation, having to close windows for some of the time because of the noise. Potential for some reported sleep disturbance. Affects the acoustic character of the area such that there is a perceived change in the quality of life".
- 2.2.2 The significant observed adverse effect level (SOAEL) is defined in the 'Planning Practice Guidance Noise' as the level above which "noise causes a material change in behaviour and/or attitude, e.g. avoiding certain activities during periods of intrusion; where there is no alternative ventilation, having to keep windows closed most of the time because of the noise. Potential for sleep disturbance resulting in difficulty in getting to sleep, premature awakening and difficulty in getting back to sleep. Quality of life diminished due to change in acoustic character of the area."
- 2.2.3 HS2 Phase One Information Paper E23: Control of Construction Noise and Vibration sets out the LOAELs and SOAELs for construction noise.
- 2.2.4 Where reported construction noise levels exceed the LOAEL and SOAEL, relevant periods will be identified. Summary statistics to evaluate ongoing qualification for noise insulation and temporary rehousing are also presented where relevant.
- 2.2.5 Table 4 presents a summary of recorded exceedances of the LOAEL and SOAEL at each measurement location over the reporting period, including the number of exceedances during each time period.

Table 4: Summary of Exceedances of LOAEL and SOAEL

Worksite Reference	Measurement Reference	Site Address	Day (Weekday, Saturday, Sunday, Night)	Time period	Number of exceedances of LOAEL	Number of exceedances of SOAEL
CW	CW-N1	Chipping Warden and Edgcote, Banbury	All days	All periods	No exceedances	No exceedances
LB	LB-N1	Lower Boddington, West Northamptonshire	Saturday	1400-2200	2	No exceedances
A43	A43-N1	A43, Brackley, West Northamptonshire	All days	All periods	No exceedances	No exceedances
FTN	FTN-N1	Fir Tree Nursery, Banbury Road, Lower Boddington	Weekday Saturday	0800-1800 1300-1400 1400-2200	5 1 3	No exceedances
RA	RA-N1	Radstone Road, Brackley	All days	All periods	No exceedances	No exceedances
	HF-N1	Hall Farm, Brackley	All days	All periods	No exceedances	No exceedances

- 2.2.6 Exceedances of the LOAEL were recorded at two (2) monitoring locations, where a total of eleven (11) LOAEL exceedances were observed during May 2022.
- 2.2.7 No exceedances of the SOAEL were recorded due to HS2 construction works at any of the monitoring locations during May 2022.

2.3 Exceedances of Trigger Level

2.3.1 Table 5 provides a summary of exceedances of the Section 61 trigger noise levels determined to be due to HS2 related construction noise measured during the reporting period, along with the findings of any investigation.

Table 5: Summary of Exceedances of Trigger Levels

Complaint Reference Number (if applicable)		Date and Time Period		Results of Investigation (including noise monitoring results)	Actions Taken
-	-	-	-	-	-

2.4 Complaints

2.4.1 Table 6 provides a summary of complaint information related to noise and vibration received during the reporting period, along with the findings of any investigation.


Table 6: Summary of Complaints

Complaint Reference Number	Worksite Reference	Description of Complaint	Results of Investigation	Actions Taken	
-	-	-	-	-	


Appendix A Site Locations

OFFICIAL


HS2 Worksite Identification Plan - Overview




HS2 Worksite Identification Plan - 1



Worksite Identification Plan - 2



HS2 Worksite Identification Plan - 3




Worksite Identification Plan - 4



LegendActive Worksites


Appendix B Monitoring Locations

Noise Monitoring Plan - 1




OFFICIAL

Noise Monitoring Plan - 2



Noise Monitoring Plan - 3



OFFICIAL

Noise Monitoring Plan - 4





Appendix C Data

Noise


The following graphs show the hourly measured ambient noise level $L_{Aeq,1h}$ and, where relevant, the averaged noise level $L_{Aeq,T}$ values, where the time period T is as specified in Table 1 of HS2 Information Paper E23. Periods with adversely weather affected noise levels are greyed out and have been excluded from the calculation of the $L_{Aeq,T}$ values in Table 3 of the main report.


Worksite: CW - Monitoring Ref: CW-N1







Note: Missing data on Monday 2nd May at 23:00 was due data period rounding cut-off after automatic system check.













Note: Missing data on Monday 30th May at 23:00 was due data period rounding cut-off after automatic system check.


Worksite: LB - Monitoring Ref: LB-N1


















OFFICIAL

Worksite: A43 - Monitoring Ref: A43-N1












Note: Missing data from Wednesday 18th May at 12:00 was due to relocation of monitor to Hall Farm (worksite ref: RA).

Worksite: RA - Monitoring Ref: HF-N1





Note: The monitor was installed on Wednesday 18th May at 15:00. Missing data between Wednesday 18th May at 20:00 and Thursday 19th May at 05:00 was due to a connectivity issue with the monitor. Missing data on Thursday 19th May at 23:00 was due data period rounding cut-off after automatic system check.







Worksite: FTN - Monitoring Ref: FTN-N1









Note: Missing data on Monday 9th May at 23:00 was due data period rounding cut-off after automatic system check.





Note: Missing data between Thursday 19th May at 13:00 and Friday 20th May at 16:00 was due to monitor maintenance. Missing data on Thursday 19th May at 23:00 was due data period rounding cut-off after automatic system check.







Worksite: RA - Monitoring Ref: RA-N1









Note: Missing data on Wednesday 18th May at 23:00 was due data period rounding cut-off after automatic system check.

