

EC Type Examination Certificate Number: UK/ 0120/ SGS0074

Sensus Metering Systems Ltd

No. 9 Ganluyuan Shillpu, Chaoyang District, Beijing, China 100025

Instrument Identification:

CubixRS 1.2L G4 credit diaphragm gas meter

Instrument Traceable Number UK/ 0120/ SGS0074

EC Directive 2004/22/EC

on Measuring Instruments Annex B

It is certified that the manufacturer's technical design and specimen for the above instrument has been examined and, based on the evidence submitted, it is considered that the instrument conforms to the requirements of MI-002 of EC Directive 2004/22/EC.

This certificate is to be used in conjunction with a certificate covering the product verification as required in Annex D or Annex F

This certificate is valid for 10 years from 7th November 2010 until 6th November 2020

Issue 2

Certification is based on report number(s) MID-B-135320-G4-Rb dated 7th December 2010

Notified Body Number 0120

Authorised Signature
Mr J Weaver

(€ 0120

Notified Body

SGS United Kingdom Ltd, 202B Worle Parkway, Weston-super-Mare, BS22 6WA UK t +44 (0)1934 522917 f +44 (0)1934 522137 www.sqs.com

7 www.sgs.com Contact Address

SGS United Kingdom Ltd, Unit 10, South Industrial Estate, Bowburn, Durham, DH6 5AD UK
t+44 (0)191 377 2000 f+44 (0)191 377 2020 www.sgs.com

EC Type Examination Cert.

Page 1 of 4 MID-B06E Rev 2



Approval Annex for EC Type Examination Cert. No. UK/ 0120/ SGS0074

| Manufacturer | : | Sensus Metering Systems Ltd. | | | | |
|----------------------|---|--|--|--|--|--|
| Type of Meter(s) | : | CubixRS 1.2L G4 credit diaphragm gas meter | | | | |
| Description of Meter | | G4 diaphragm gas meter. | | | | |
| Becompaint of motor | | On diaphiagin gas filetor. | | | | |
| Accuracy Class (es) | : | 1.5 | Software Version No : Not Applicable. | | | |
| Cyclic volume | | 1.2dm ³ | Bill Of Materials No | : 152.4mm 2217130403lss. 1 | | |
| Case material | : | Steel | | : 130mm 2217130402 lss. 1 : 110mm 2217130401 lss. 1 | | |
| Meter Location | : | Indoor, or in suitable enclosure. | Sealing Type Location | : Embossed plastic seal. : Fitted to top of index cover | | |
| Integrity of Meter | : | Inaccessible without breaking seal. | Temperature Range | : -25°C to +55°C | | |
| Range of Gases | : | First, second and third families | Maximum Operating Pressure: Up to 500mbar i.e. 75mbar, 100mbar, 200mbar, 300mbar, 400mbar, or 500mbar. | | | |
| Flow Range | : | Qmax 6.0m³/h Qmin 0.040m³/h | Orientation | : Connection ports vertical | | |

Photograph Showing Complete G4 1.2dm³ Meter with 152.4mm Boss Spacing





Photograph Showing Complete G4 1.2dm³ Meter with 130mm Boss Spacing




Photograph Showing Complete G4 1.2dm³ Meter with 110mm Boss Spacing






<u>Meter Index</u> (Showing blue security seal locations)



Sensus Seal Detail



The Sensus seal marking and date will be heat embossed on the Index seal, which is detailed in drawing 120070721-1 issue 02, after the meter has been certified.



Approved Product Variations:

Boss variants for the G4 CubixRS 1.2L Meter

| Product Code | Description | 3/4" BS 746 | 1" BS 746 | M30 x 2 (China Domestic Market) |
|--------------|--------------|-------------|-----------|--|
| 2217130401 | 110 ctr G4 | V | $\sqrt{}$ | V |
| 2217130402 | 130 ctr G4 | V | V | V |
| 2217130403 | 152.4 ctr G4 | | √ | |

Modifications to the meters described according to approval No.UK/ 0120/ SGS0074 must be notified to the issuing body before, being implemented, to confirm the meter's continuing compliance to the relevant pattern approval standard(s).