MERCHANT SHIPPING NOTICE



MSN 1669 (M) Amendment 1

The Merchant Shipping (Fire Protection) Regulations 2023: Special fire safety measures for ships carrying dangerous goods

Notice to all Shipowners, Shipbuilders, Masters, Certifying Authorities and Surveyors

Summary

This Notice advises all Shipowners, Shipbuilders, Masters, Certifying Authorities, and Surveyors of requirements imposed by the Merchant Shipping (Fire Protection) Regulations 2023 and the Merchant Shipping (Fire Protection: Small Ships) Regulations 1998 for ships constructed before 1st July 2002 in relation to special fire safety measures for ships carrying dangerous goods.

Key Points:-

- This Notice forms an integral part of the new Merchant Shipping (Fire Protection) Regulations 2023 ("the 2023 Regulations") as well as the Merchant Shipping (Fire Protection: Small Ships) Regulations 1998 ("the Small Ships Regulations").
- The requirements of this Notice are made mandatory by reference to it in the 2023 Regulations and the Small Ships Regulations and are statutory obligations.

This amendment updates the text of Merchant Shipping Notice 1669 (M) to reflect the 2023 Regulations and Merchant Shipping Notice 1900 (M) ("MSN 1900 (M)").

In this Merchant Shipping Notice, the following expressions have the following meanings - " "A" Class Division" means a bulkhead or part of a deck which is –

- (a) constructed of steel or other equivalent material;
- (b) suitably stiffened;
- (c) so constructed as to be capable of preventing the passage of smoke and flame to tile end of the 60 minute standard fire test; and
- (d) so insulated where necessary with suitable non-combustible materials that if the division is exposed to a standard fire test the average temperature on the unexposed side of the division shall not increase more than 139°C above the



initial temperature nor shall the temperature at any one point, including any joint, rise more than 180°C above the initial temperature within the time listed below -

"A-60" standard, 60 minutes; "A-30" standard, 30 minutes; "A-15" standard, 15 minutes; "A-0" standard, 0 minutes;

"cargo spaces" are all spaces used for cargo including cargo oil tanks, slop tanks and trunks to such spaces;

"closed ro-ro cargo space" means a ro-ro cargo space which is not an open ro-ro cargo space which is not a weather deck;

"dangerous goods" means goods as defined in the Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997;

"machinery spaces of Category A" means a machinery space which contains -

- (a) internal combustion type machinery used either for main propulsion purposes, or for other purposes where such machinery has in the aggregate a total power output of not less than 375 kilowatts, or
- (b) any oil-fired boiler or oil-fired unit; and any trunk to such a space;

"open ro-ro spaces" are ro-ro cargo spaces which are open at both ends, or open at one end and provided with adequate natural ventilation effective over the entire length through permanent openings in the side plating or deck head;

"ro-ro cargo spaces" means spaces not normally subdivided in any way and extending to either a substantial length or the entire length of the ship in which goods (packaged or in bulk), in or on rail or road cars, vehicles (including road or rail tankers), trailers, containers, pallets, demountable tanks or in or on similar stowage units or other receptacles can be loaded and unloaded normally in a horizontal direction;

"special category space" means any enclosed space above or below the bulkhead deck intended for the carriage of motor vehicles with fuel in their tanks for their own propulsion, into and from which such vehicles can be driven and to which passengers have access;

"weather deck" means a deck completely exposed to the weather from above and at least two sides.

- 1.1 The special protective requirements for passenger ships and cargo ships which are intended, or which contain cargo spaces which are intended for, the carriage of dangerous goods shall be determined by reference to Tables 1, 2 and 3.
- 1.2 In Table 1, ships and cargo spaces are divided into categories A-F as set out below -
 - 1.2.1 A ro-ro cargo spaces on the weather deck;
 - 1.2.2 B Ships and cargo spaces not specifically designed for the carriage of freight containers but intended for the carriage of dangerous goods in package form including goods in freight containers and portable tanks;



- 1.2.3 C Purpose built container ships and cargo spaces intended for the carriage of dangerous goods in freight containers and portable tanks;
- 1.2.4 D spaces intended for the carriage of dangerous goods which are -
- 1.2.4.1 closed ro-ro cargo spaces;
- 1.2.4.2 open ro-ro cargo spaces; or
- 1.2.5 E Ships and cargo spaces intended for the carriage of solid dangerous goods in bulk:
- 1.2.6 F Ships and cargo spaces intended for the carriage of dangerous goods other than liquids and gases in bulk in shipborne barges.

Such categories are listed in the top horizontal row of Table 1.

- 1.3 In Tables I, 2 and 3, the protective measures to be applied have the description set out below -
- 1.3.1 Arrangements shall be made to ensure immediate availability of a supply of water from the fire main at the required pressure either by a permanent pressurization of the firemain or by suitably placed remote starting arrangements for the fire pumps;
- 1.3.2 The quantity of water delivered shall be capable of supplying four nozzles of a size and at pressures specified in the 2023 Regulations or the Small Ships Regulations as applicable, capable of being trained on any part of the cargo space when empty. This amount of water may be applied by equivalent means to the satisfaction of the Secretary of State:
- 1.3.3 Means of effectively cooling the designated under deck cargo space by copious quantities of water, either by a fixed pressure water spraying system complying with Schedule 3 in Merchant Shipping Notice MSN 1666 (M) or flooding the cargo space with water, shall be provided. Hoses may be used for this purpose in small cargo spaces and in small areas of larger cargo spaces. The drainage and pumping arrangements shall be such as to prevent the build-up of free surfaces. If this is not possible, the adverse effect upon stability of the added weight and free surface of water shall be taken into account as necessary in calculating stability;
- 1.3.4 Provision to flood a designated under deck cargo space with suitable specified media may be substituted for the requirements in subparagraph 1.3.3 of this paragraph;
- 1.3.5 Electrical equipment and wiring where permitted for such spaces shall be in accordance with the Merchant Shipping (Passenger Ship Construction and Survey) Regulations 1984 or to the Merchant Shipping (Cargo Ship Construction and Survey) Regulations 1997, whichever is appropriate;
- 1.3.6 Closed ro-ro cargo spaces and special category spaces shall be fitted with a fixed fire detection and fire alarm system of an approved type complying with the requirements of Schedule 5 of Merchant Shipping Notice MSN 1666 (M). All other types of cargo spaces shall be fitted with either such a fixed fire detection and fire alarm system or a sample extraction smoke detection system complying with the requirements of Schedule 6 in Merchant Shipping Notice MSN 1666 (M). If a



sample extraction smoke detection system is fitted, particular attention shall be paid to paragraph 6.1.11 of Schedule 6 in Merchant Shipping Notice MSN 1666 (M) in order to prevent the leakage of toxic fumes into occupied areas;

- 1.3.7 Adequate power ventilation shall be provided in enclosed cargo spaces. The arrangement shall be such as to provide for at least six air changes per hour in the cargo space based on an empty cargo space and for removal of vapours from the upper or lower parts of the cargo space, as appropriate;
- 1.3.8 The fans shall be such as to avoid the possibility of ignition of flammable gas air mixture. Suitable wire mesh guards shall be fitted over inlet and outlet ventilation openings;
- 1.3.9 Natural ventilation shall be provided in enclosed cargo spaces intended for the carriage of solid dangerous goods in bulk, where there is no provision for mechanical ventilation;"
- 1.3.10 Where flammable or toxic liquids are to be carried in enclosed cargo spaces, the bilge pumping arrangements shall be to the requirements of the ,Merchant Shipping (Passenger Ship Construction: Ships of Classes I, II and II(A)) Regulations 1998,or of the Merchant Shipping (Passenger Ship Construction: Ships of Classes III to VI(A)) Regulations 1998, or of the Merchant Shipping (Cargo Ship Construction) Regulations 1997, whichever is appropriate;
- 1.3.11 Four sets of full protective clothing resistant to chemical attack shall be provided in addition to the firemen's outfits required by the Regulations. Protective clothing shall cover all skin so that no part of the body is unprotected;
- 1.3.12 At least two sets of self-contained breathing apparatus shall be provided in addition to the breathing apparatus otherwise required by the Regulations;
- 1.3.13 At least three portable fire extinguishers of the dry powder type or equivalent complying with Schedule 8 of Merchant Shipping Notice MSN 1665 (M) shall be provided for each cargo space. These extinguishers shall be in addition to any portable fire extinguishers required by the Regulations;
- 1.3.14 Bulkheads forming boundaries between cargo spaces and machinery spaces of Category A shall be insulated to "A-60" standard unless the dangerous goods are stowed at least 3 metres horizontally away from such bulkheads. Boundaries other than bulkheads between such spaces shall be insulated to "A-60" standard. Dangerous goods of Class 1 shall be stowed 3 metres horizontally away from machinery space bulkheads in all cases and the common bulkheads shall be insulated to "A-60" standard;
- 1.3.15 Each special category space, each open ro-ro cargo space having a deck over and each space deemed to be a closed ro-ro cargo space not capable of being sealed shall be fitted with a fixed pressure water spraying system complying with Schedule 3 in Merchant Shipping Notice MSN 1666 (M) for the protection of all parts of any deck and vehicle platform in such space, except that the Secretary of State may permit the use of any other fixed fire-extinguishing system that has been shown by full scale test to be no less effective.

The subparagraphs of this paragraph are listed in the left hand vertical columns of Tables 1, 2 and 3.



- 1.4 The classes of dangerous goods referred to in this Schedule are those specified in the Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Such classes are listed in the top horizontal rows of Tables 2 and 3.
- 1.5 Ships and cargo spaces in categories A, B, C or E shall comply with a particular subparagraph of paragraph 3 if –
- 1.5.1 An "X" appears in Table 1 where the vertical column for that Category crosses the horizontal row for that subparagraph; and
- 1.5.2 The dangerous goods (not being solid dangerous goods carried in bulk) which the ship or space as the case may be is intended to carry are of a class included in Table 3 and an "X" appears in that table where the vertical column for that class crosses the horizontal row for that subparagraph.
- 1.6 Ships and cargo spaces of Category D shall comply with the requirements of a particular subparagraph of paragraph 3 if the dangerous goods (being solid dangerous goods in bulk) are of a class included in Table 2 and an "X" appears where the vertical column for that class of goods crosses the horizontal row for that subparagraph.
- 1.7 Any requirement in this Schedule shall be applied subject to any exception or modification set out in the footnotes to the relevant Table or Tables which is applicable to that particular case.
- 1.8 Where in a ship or cargo space of Category D dangerous goods of class 4.3 are carried, the Secretary of State may, having regard to the hazards of the particular dangerous goods, impose such additional requirements as he may think necessary.
- 1.9 Any enclosed cargo space of Category D which is not provided with power ventilation shall be provided with natural ventilation.
- 1.10 In ships having ro-ro cargo spaces, a separation shall be provided between a closed ro-ro cargo space and an adjacent open ro-ro cargo space. The separation shall be such as to minimise the passage of dangerous vapours and liquids between such spaces. Alternatively, such separation need not be provided if the ro-ro cargo space is considered to be a closed cargo space over its entire length and shall fully comply with the relevant special requirements of this regulation
- 1.11 In ships having ro-ro cargo spaces, a separation shall be provided between a closed ro-ro cargo space and the adjacent weather deck. The separation shall be such as to minimise the passage of dangerous vapours and liquids between such spaces. Alternatively, a separation need not be provided if the arrangements of the closed ro-ro cargo spaces are in accordance with those required for the dangerous goods carried on the adjacent weather deck.



TABLE 1 - APPLICATION OF THE REQUIREMENTS TO DIFFERENT MODES OF CARRIAGE OF DANGEROUS GOODS IN SHIPS AND CARGO SPACES

Paragraph 2 \rightarrow	(A)	(B)	(C)	(D)		(E)	(F)		
Paragraph 3 ↓	Weather decks	Not specifically designed	Container cargo spaces	Closed ro-ro cargo spaces	Open ro-ro cargo spaces	Intended for solid dangerous goods in bulk	Shipborne barges		
(a) Immediate availability of supplies	Х	X	Х	X	X		Х		
(b) Quantity of water	Х	Х	Х	Х	Х	For	_		
(c) Water cooling	-	X	X	x	Х	application	Х		
(d) Cargo space flooding	-	X	X	Х	x	of	Х		
(e) Electrical equipment	-	X	X	х	x	-requirements of	Xq		
(f) Fire detection	-	X	X	x	+	these	Xq		
(g) Power ventilation	-	X	x ^a	X	+	-Regulations	x ^d		
(h) Fans	-	Х	x ^a	X	-	different	x ^d		
(i) Bilge pumping	- (X	X	x	+	classes of	-		
(j) Protective clothing	Х	x	X	x	x	dangerous	-		
(k) Breathing apparatus	X	X	X	Х	X	─goods – see	_		
(I) Fire extinguishers	Х	X	-	-	X	Table 2	-		
(m) Insulation of boundaries	Х	X	xp	x	x	1	-		
(n) Water spray	-	-	X	xc	Х	1	-		

Notes (Table 1)

- a For dangerous goods of classes 4 and 5.1 not applicable to closed freight containers. For dangerous goods of classes 2, 3, 6.1 and 8 when carried in closed freight containers the ventilation rate may be reduced to not less than two air changes. For the purpose of this requirement a portable tank is a closed freight container.
- ь Applicable to decks only.
- c Applies only to closed ro-ro cargo spaces, not capable of being sealed.
- d In the special case where the barges are capable of containing flammable vapours or alternatively if they are capable of discharging flammable vapours to a safe space outside the barge carrier compartment by means of ventilation ducts connected to the barges, these requirements may be reduced or waived to the satisfaction of the Secretary of State.
- e Special category spaces shall be treated as closed ro-ro spaces when dangerous goods are carried

TABLE 2 - APPLICATION OF THE REQUIREMENTS TO DIFFERENT CLASSES OF DANGEROUS GOODS FOR SHIPS AND CARGO SPACES CARRYING SOLID DANGEROUS GOODS IN BULK

f Dangerous Goods $ ightarrow$	4.1	4.2	4.3	5.1	6.1	8	9
ph 3 ↓	-						
Immediate availability of water supplies	Х	Х		Х	_	_	Х
Quantity of water	Х	Х	+	Х	-	_	Х
Electrical equipment	X	Xg	Х	X ^h	_	-	X ^h
Power ventilation		Xg	Х	-	-	-	-
Fans	X ¹	Xg	Х	X ^{g,1}	_	-	X ^{g,1}
Natural ventilation	x	X	Х	Х	X	x	Х
Personnel protection	X	X	x	X	X	x	X
Insulation of boundaries	x	X	x	Xg	-	_	Xi
	ph 3 ↓ Immediate availability of water supplies Quantity of water Electrical equipment Power ventilation Fans Natural ventilation Personnel protection	ph 3 ↓ Immediate availability of water supplies X Quantity of water X Electrical equipment X Power ventilation - Fans X ¹ Natural ventilation X Personnel protection X	ph 3 \downarrow Immediate availability of water suppliesXXQuantity of waterXXXQuantity of waterXXXElectrical equipmentXXXPower ventilation-XYFansX ¹ XYNatural ventilationXXPersonnel protectionXX	bcph 3 \downarrow Immediate availability of water suppliesXXQuantity of waterXX-Quantity of waterXX-Electrical equipmentXX ^g XPower ventilation-X ^g XFansX ¹ X ^g XNatural ventilationXXXPersonnel protectionXXX	bccph $3 \downarrow$ Immediate availability of water suppliesXX-XQuantity of waterXX-XX-XElectrical equipmentXXYXX-XPower ventilation-X ⁹ XFansX ¹ X ⁹ XXFansX ¹ X ⁹ XXXXXXXXPersonnel protectionXXXXXXX	ooooph 3 \downarrow Immediate availability of water suppliesXX-XQuantity of waterXX-X-Quantity of waterXX-X-Electrical equipmentXX ^g XX ^h -Power ventilation-X ^g XFansX ¹ X ^g XXXXNatural ventilationXXXXXPersonnel protectionXXXXX	JJImmediate availability of water suppliesXX-XQuantity of waterXX-XQuantity of waterXX-XElectrical equipmentXXggXXhPower ventilation-XggXFansX1XggXXgg.1Natural ventilationXXXXXXPersonnel protectionXXXXXX

Notes (Table 2)

- f The hazards of substances in this class which may be carried in bulk are such that special consideration must be given by the Secretary of State to the construction and equipment of the ship involved in addition to meeting the requirements enumerated in this table.
- g Only applicable to Seedcake containing solvent extractions, to Ammonium nitrate and to Ammonium nitrate fertilizers.
- h Only applicable to Ammonium nitrate and to Ammonium nitrate fertilizers. However, a degree of protection in accordance with standards contained in the International Electrotechnical Commission, publication 79 - Electrical Apparatus for Explosive Gas Atmospheres, is sufficient.
- i Only suitable wire mesh guards are required.
- j The requirements of the Code of Safe Practice for Solid Bulk Cargoes adopted by resolution A.434(XI), as amended, are sufficient.

TABLE 3 – APPLICATION OF THE REQUIREMENTS TO DIFFERENT CLASSES OF DANGEROUS GOODS EXCEPT SOLID DANGEROUS GOODS IN BULK

Class Goods	of Dangerous S →	1.1- 1.6	1.4S	2.1	2.2	2.3	3.1 3.2	3.3	4.1	4.2	4.3	5.1	5.2	6.1 liquid	6.1 Iiquid ≤23°C	6.1 liquid	6.1 solid	8 liquid	8 liquid ≤23°C		8 solid	9
Parag	raph 3 ↓														≤23 C	≥23 C ≤61°C			≥23 C	≥23 C ≤61°C		
(a)	Immediate availability of water supplies	Х	Х	х	х	Х	х	Х	Х	X	x	x	x	Х	Х	Х	Х	Х	Х	Х	Х	Х
(b)	Quantity of water	Х	Х	х	х	Х	х	х	Х	X	Х	х	x	x	Х	Х	Х	х	Х	Х	х	-
(c)	Water cooling	Х	_	-	_	-	-	_	-	-	_	-	-	-	-	_	-	-	-	_	-	-
(d)	Cargo space flooding	Х	-	-	_	-	-	-	_	-		-	-	-		-	_	-	-	_	-	-
(e)	Electrical equipment	Х	-	Х	_	_	x	-	-	-		-	-	-	х	_	_	-	х	_	_	-
(f)	Fire detection	Х	Х	Х	х	Х	Х	x	X	X	х	x	-	Х	х	х	х	Х	х	Х	х	-
(g)	Power ventilation	-	_	Х	-	Х	х	-	x	X	x	x		-	х	х	X ^k	-	х	Х	_	x
(h)	Fans	-	-	x	-	-	x	-	-	-	-		-	-	х	х	_	-	х	Х	_	-
(i)	Bilge pumping	-	-	-	T	-	х	-	-	-	-	_	-	X	х	х	_	-	х	-	-	-
(j) & (k	x) Personnel protection	-	-	Х	x	x	X	X	X	х	Х	Х	Х	Х	х	х	х	Х	х	Х	х	x
(I)	Fire extinguishers	-	-	-		-	x	х	X	x	Х	Х	-	-	Х	Х	_	_	Х	Х	_	-
(m)	Insulation of boundaries	X	-	Х	х	Х	x	X	Х	Х	Х	m X	-	_	Х	Х	-	-	х	х	-	-
(n)	Water spray	Х	X	Х	Х	X	х	x	Х	Х	Х	Х	Х	Х	х	Х	Х	х	х	Х	Х	Х

Notes (Table 3)

k When "mechanically-ventilated spaces" are required by the International Maritime Dangerous Goods (IMCG) Code, as amended.

1 Stow 3 m horizontally away from the machinery space boundaries in all cases.

m Refer to the International Maritime Dangerous Goods Code.

n As appropriate to the goods being carried.

More Information

Ship Standards Maritime and Coastgua Bay 2/23 Spring Place 105 Commercial Road Southampton SO15 1EG	rd Agency
Tel: e-mail:	+44 (0) 203 81 8172000 marine.technology@mcga.gov.uk
Website Address:	www.gov.uk/government/organisations/maritime-and-coastguard-agency
General Enquiries:	infoline@mcga.gov.uk
Published:	[] 2023 Please note that all addresses and telephone numbers are correct at time of publishing

© Crown Copyright 2022

Safer Lives, Safer Ships, Cleaner Seas