

Notice of variation and consolidation with introductory note

The Environmental Permitting (England & Wales) Regulations 2016

Viridor South London Limited

Beddington ERF and WTS

Beddington Lane

Croydon

CR0 4TD

Variation application number

EPR/GP3305LN/C003

Consolidated permit number

EPR/GP3305LN

Beddington ERF and WTS

Permit number EPR/GP3305LN

Introductory note

This introductory note does not form a part of the notice.

The following notice gives notice of the variation of environmental permits EPR/GP3305LN and EPR/JB3902FZ referred to in the status logs below and the replacement of those permits with a consolidated environmental permit.

The following changes have been made as a result of this Operator requested variation:

- The throughput of the energy from waste (ERF) plant has been increased from 347,422 tonnes per year to 382,286 tonnes per year
- The thermal input of the ERF at the 110% Maximum Continuous Rating or 'MCR' point is 105.4MWth for both lines, whilst the electrical generating capacity is expected to increase to approximately 29.5 MWe
- Amended the locations of emission points S1, W1 and W2 to show their correct locations on the site plan
- Added an emission point (A4) for the shredder associated with the waste transfer station activities
- Amended the waste transfer station from a standard rules permit (SR2015 No10) to a bespoke permit including hazardous waste transfer station & non-hazardous waste transfer and treatment station activities under the newly consolidated permit
- Added waste codes to the waste transfer station activity
- Added a single waste code to the incineration activity EWC 20 01 99 'municipal waste not otherwise specified'. The plant is already allowed to accept 18 01 04 'wastes whose collection and disposal is not subject to special requirements in order to prevent infection(for example dressings, plaster casts, linen, disposable clothing, diapers)'. EWC 18 01 04 refers to waste which is collected from healthcare facilities such as hospitals. Where the same sort of waste is collected from municipal sources (e.g. hygiene and sanitary waste, nappies and incontinence pads) it should instead be coded as EWC 20 01 99. The addition of this waste code is administrative only and does not expand the types of waste permitted to be accepted at the facility.
- Amended improvement conditions 2, 6, 10, 11 and 12 to mark them as complete.
- The waste transfer station permit EPR/JB3902FZ has been consolidated into the ERF plant permit EPR/GP3305LN
- Permit EPR/GP3305LN will be the consolidated permit and permit EPR/JB3902FZ will cease to exist
- The site has been renamed as "Beddington ERF and WTS" to better reflect the activities undertaken onsite and the registered office address has been updated

Brief description of the process

This permit controls the operation of a waste incineration plant (the ERF) and a waste transfer station. The relevant listed Installation activity for the ERF is S5.1 A1(b). The permit implements the requirements of the EU Directives on Industrial Emissions and Waste.

The main features of the permit for the waste incineration plant are as follows:

Furnace technology	Moving Grate
Number of lines	2
Principal waste type	Municipal and commercial & industrial

Stack height	95 m
Permitted plant capacity	382,286 tonnes per year
Electrical generation capacity	29.5 MWe

The ERF plant is designed to recover energy from residual municipal waste, and from commercial and industrial waste of a similar nature to residual municipal waste, by incineration. Energy is recovered from the ERF plant in the form of electricity, which is exported to the National Grid.

The installation is located within the London Borough of Sutton at Beddington Farmlands, which is south of Mitcham Common and north of Beddington Park. The site is bounded by an industrial unit to the east and the west. The remaining surroundings are open land/wetlands, which form Beddington Farmlands Local Wildlife Site. The nearest residential receptor is 0.3km to the north-east of the Installation boundary.

The ERF plant processes up to maximum 382,286 tonnes of waste per year (21.82 tonnes per hour of waste per line) in two incineration lines of a mass burn moving grate design. Waste is delivered to the facility by road in covered vehicles or containers and tipped within the main building in the waste reception hall directly into the waste bunker. The waste is stored and mixed in the waste bunker prior to being burnt in the moving grate incinerators. The waste reception hall is equipped with rapid action roller shutter doors for vehicle access and egress and operates under slight negative pressure relative to the external environment as a result of the extraction of combustion air for the incineration process.

Heat from the combustion process is used to generate high pressure steam in a multi stage boiler plant which is integral to the combustion process. The high pressure steam is fed to a steam turbine to generate electricity. The ERF has a total capacity of around 105.4MWth (thermal input) at the 110% MCR point and is capable of generating up to approximately 29.5 MWe of electrical power, of which approximately 26.5 MW is exported to the National Grid. Provision has been made in the design for the plant to be capable of supplying heat in the form of steam or hot water, once a viable heat user becomes available to take the heat as an output.

The furnace design ensures that a temperature of at least 850°C for a period of at least two seconds is achieved in the combustion chamber. To ensure that the temperature does not fall below 850°C, auxiliary burners firing low sulphur fuel oil are automatically triggered by online process monitoring equipment. The auxiliary burners are also used to achieve and maintain the minimum furnace temperature during start up and shutdown periods.

Combustion gases are cleaned before they are released to atmosphere. There are four components to the flue gas cleaning and abatement technique:

- Selective Non-Catalytic Reduction (SNCR), involving the injection of urea into the combustion chamber, provides for the abatement of nitrogen oxides;
- hydrated lime reagent, injected to neutralise acid gas compounds;
- activated carbon, injected to absorb mercury, dioxins and furans; and
- bag filtration to remove fine particulates. The residues which are collected on the bag filters are directed to a residues silo. Part of the residues are recycled to the reagent injection points to ensure maximum usage of the lime content.

Cleaned flue gases exiting the abatement system of each incinerator line are discharged through two 95m tall stacks each with a windshield. Exhaust flue gases are continuously monitored for particulate matter, oxides of nitrogen, nitrous oxide, sulphur dioxide, carbon monoxide, total organic carbon, hydrogen chloride and ammonia. Monitoring for heavy metals, dioxins, dioxin-like PCBs, PAHs, brominated dioxins and hydrogen fluoride is carried out periodically.

Under normal circumstances there are no liquid effluent emissions from the installation. Although some rainwater is harvested for use in the process, the site has a net consumption of water. Waste water arising from boiler blowdown and water treatment backwash are recycled to the Incinerator Bottom Ash (IBA) quench system. Sludge from the IBA waste water pit is periodically tankered off-site for appropriate treatment.

The incineration process results in solid residues of IBA and air pollution control (APC) residues. The quenched IBA from the combustion process is transferred by conveyor to the bottom ash storage bunker then periodically transferred to an appropriately authorised facility for treatment.

APC residues are collected and temporarily stored on site in a silo prior to being removed from the site in enclosed tankers for subsequent treatment or disposal at an appropriately authorised facility.

The permit sets conditions controlling the management, operation and the control of emissions from the installation, including the monitoring and reporting of emissions to all environmental media.

Waste Transfer and Treatment Station

The waste transfer station accepts hazardous, clinical and non-hazardous waste. The hazardous and clinical wastes are not treated, but only temporarily stored prior to onward transport to appropriately permitted facilities. Clinical wastes are stored in sealed containers. Waste electrical and electronic equipment (WEEE) is stored in skips on impermeable surfaces with sealed drainage. Asbestos waste is double bagged and stored within clearly identified, segregated, secure, lockable containers on an impermeable surface with sealed drainage system. Liquid wastes are stored in drums/other sealed containers on appropriately constructed and sized bunding. Non-hazardous waste can be treated via; manual sorting, separation, screening, baling, crushing, compaction or shredding in preparation for the waste to be transferred to the waste incineration plant. All wastes are stored undercover, either within the building, or for large WEEE, within a shipping container, unless it is a specified waste. The shredding takes place inside the building and its exhaust vents through emission point A4. All process drainage feeds into the site combined drainage system, which discharges to the sewer.

The schedules specify the changes made to the permit.

The status log of a permit sets out the permitting history, including any changes to the permit reference number.

Status log of permit A: EPR/GP3305LN		
Description	Date	Comments
Application EPR/TP3836CT/A001	Duly made 17/08/2012	Application for Incineration Plant.
Schedule 5 - Additional information received	12/10/2012	Clarification on a number of waste codes, and details of shutdown procedure.
Schedule 5 - Additional information received	Document dated 31/10/2012 received on 4/11/2012	Revised Noise Impact Assessment & Air Quality assessment on the impact of NO ₂ at sensitive receptors, greenhouse gas assessment, and confirmation of site boundary.
Additional information received	10/12/2012	Air Quality assessment on the impact of NO ₂ at sensitive receptors - A Case Specific Calculation of the Additional NO ₂ Concentration for a Receptor at the Beddington Lane/Brookmead Road Junction.
Additional information received	31/01/2013	Revised noise risk assessment; revised Air Quality Assessment on the Impact of NO ₂ at Sensitive Receptors.
Additional information received	01/03/2013	Revised noise risk assessment; revised Air Quality Assessment on the Impact of NO ₂ at Sensitive Receptors.
Additional information received	14/03/2013	Short term assessment of metals & abnormal emissions.

Status log of permit A: EPR/GP3305LN		
Description	Date	Comments
Additional information received	20/03/2013	Final - revised Air Quality & BAT Assessment on the Impact of NO2 at Sensitive Receptors – supersedes all previous submissions.
Additional information received	08/04/2013	Clarification on Abnormal emission.
Permit determined EPR/TP3836CT/A001	23/07/2013	Permit issued to Viridor Waste Management Limited.
Variation application EPR/TP3836CT/V002	Duly made 17/08/2018	Application to vary the CO emission limit and monitoring reference period. Agency initiated variation to add FPP conditions.
Variation determined EPR/TP3836CT	18/01/2019	Variation notice issued.
Notified of change of Company Registered Office Address	23/07/2020	Registered office address changed to Viridor House, Priory Bridge Road, Taunton, Somerset, TA1 1AP.
Variation issued EPR/TP3836CT/V003	09/10/2020	Varied permit issued to Viridor Waste Management Limited.
Variation application EPR/TP3836CT/V004	Duly made 14/10/2020	Application to increase the throughput of waste to the incinerator.
Variation determined EPR/TP3836CT	09/12/2020	Variation notice issued.
Application EPR/GP3305LN/T001 (full transfer of permit EPR/TP3836CT)	Duly made 28/10/2020	Application to transfer the permit in full to Viridor South London Limited.
Transfer determined EPR/GP3305LN	18/12/2020	Full transfer of permit complete.
Regulation 61 notice issued	05/04/2022	Regulation 61 Notice requiring information for Statutory review of permit. BAT Conclusions published 03 December 2019.
Regulation 61 notice response	23/06/2022	--
Variation issued EPR/GP3305LN/V002	29/09/2022	--
Application EPR/GP3305LN/C003 (variation and consolidation with EPR/JB3902FZ)	Duly made 19/10/2022	Application to increase the throughput of waste to the ERF plant and consolidate with the waste transfer station permit.
Additional information received	25/05/2023	Updated Fire Prevention Plan, Site Condition Report, Greenhouse Gas Assessment, shredder operating technique and design capacities.
Additional information received	21/06/2023	Updated Waste Acceptance Procedures
Additional information received	10/12/2025	Updated registered office address
Variation determined and consolidation issued. EPR/GP3305LN/C003	03/06/2026	Varied and consolidated permit issued in modern format.

Status log of permit B: EPR/JB3902FZ		
Description	Date	Comments
Application received EPR/JB3136RD/A001	Duly made 17/09/2012	Application for SR2008No5.
Permit determined EPR/JB3136RD	17/03/2014	Permit issued to Viridor Waste Management Limited
Application Variation EPR/JB3136RD/V002	Duly made 14/12/2017	Application to vary the permit to SR2015No10
Additional Information received	18/06/2018	Updated Fire Prevention Plan
Variation determined EPR/JB3136RD	20/06/2018	Varied permit issued.
Notified of change of Company Registered office Address	23/07/2020	Registered office address changed to Viridor House, Priory Bridge Road, Taunton, Somerset, TA1 1AP
Variation issued EPR/JB3136RD/V003	09/10/2020	Varied permit issued to Viridor Waste Management Limited.
Application EPR/JB3902FZ/T001 (full transfer of permit EPR/JB3136RD)	Duly made 28/10/2020	Application to transfer the permit in full to Viridor South London Limited.
Transfer determined EPR/JB3902FZ Billing reference: EAWML 104442	18/12/2020	Full transfer of permit complete.
Application EPR/JB3136RD/V004 (variation and consolidation with EPR/GP3305LN)	Duly made 21/03/2023	Application to vary the SR2015No10 permit into a bespoke hazardous/clinical waste transfer station permit and consolidate with permit EPR/GP3305LN.
Additional information received	25/05/2023	Updated Fire Prevention Plan, Site Condition Report, Greenhouse Gas Assessment, shredder operating technique and design capacities.
Additional information received	21/06/2023	Updated Waste Acceptance Procedures
Application EPR/JB3902FZ/V005 Notified of change of Registered office	02/04/2024	Registered office changed to Ardley ERF Middleton Stoney Road Ardley Bicester OX27 7AA.
Variation issued EPR/JB3902FZ/V005	25/04/2024	Varied permit issued to Viridor South London Limited.
Variation determined and consolidation issued. EPR/GP3305LN/C003	03/06/2026	Varied and consolidated permit issued in modern format.

End of introductory note

Notice of variation and consolidation

The Environmental Permitting (England and Wales) Regulations 2016

The Environment Agency in exercise of its powers under regulations 18 and 20 of the Environmental Permitting (England and Wales) Regulations 2016 varies and consolidates environmental permits

Permit numbers

EPR/GP3305LN

EPR/JB3902FZ

Issued to

Viridor South London Limited (“the operator”)

whose registered office is

Ardley ERF

Middleton Stoney Road

Ardley

OX27 7AA

company registration number **08106962**

to operate regulated facilities at

Beddington ERF and WTS

Beddington Lane

Croydon

CR0 4TD

to the extent set out in the schedules.

The notice shall take effect from 03/06/2026.

The number of the consolidated permit is EPR/GP3305LN.

Name	Date
Principal Permitting Team Leader	03/06/2026

Authorised on behalf of the Environment Agency

Schedule 1 – changes in the permit

Note: The conditions numbers used in this schedule refer to those in the consolidated permit.

The following conditions were varied as a result of the application made by the operator:

- Table S1.1, as referenced in conditions 1.1.1, 2.1.1, 2.5.2, has been amended to add two new activities for the waste transfer station (AR4 - hazardous waste transfer and AR5 - non-hazardous waste transfer) and to amend the generation capacity in AR2 to 29.5MWe.
- Table S1.2, as referenced in conditions 2.3.1 and 2.3.2 has been amended to add the updated Fire Prevention Plan, Waste Acceptance Criteria and operation of the shredder.
- Table S1.3, as referenced in condition 2.4.1 has been amended to mark IC2 and IC6 as complete.
- Condition 2.3.4 was amended to reference the newly added waste tables S2.3 and S2.4, which detail the wastes permitted to be accepted at the waste transfer station.
- Table S2.2, as referenced in condition 2.3.3, has been amended to add EWC 20 01 99.
- Table S3.1, as referenced in conditions 2.4.9, 2.3.12, 3.1.1, 3.2.1, 3.2.2, 3.6.1, 3.6.3 and 3.6.4, has been amended to add emission point A4 – for the waste transfer station shredder and to remove references to 2023 dates.
- Table S3.2, as referenced in conditions 3.1.1, 3.6.1 and 3.6.4, has been amended to separate the emission points and add a more appropriate source description and monitoring requirements for emission point W2.
- Table S3.5 as referenced in conditions 3.1.3 and 3.6.1, has been amended to change the monitoring standard to align with the updated method from 2025.
- Conditions 1.1.3, 1.2.1, 1.2.2, 1.2.3, 1.3.1, 2.1.2, 2.3.5, 2.3.6, 2.3.7, 2.3.8, 2.3.9, 2.3.10, 2.3.11, 2.3.12, 2.3.13, 2.3.14, 2.3.15, 3.1.3, 3.2.1, 3.2.2, 3.3.4, 4.2.2 and 4.2.4 have had the following wording included to distinguish that these conditions are only applicable to those activities listed in table S1.1: “For the following activities referenced in schedule 1, table S1.1...”.
- Condition 3.1.1 has been amended to include table S3.3, which was an administrative error in the previous permit.
- Condition 3.6.1 has been amended to include S3.3, which was an administrative error in the previous permit.
- Schedule 6 interpretation has been amended to include applicable references for the waste transfer station activities.
- Site plan in Schedule 7, as referenced in condition 2.2.1 has been amended to include all emission points at their correct locations.

The following conditions were added as a result of the application made by the operator:

- Conditions 1.1.5, 2.5.1, 2.5.2, 2.6.1 and 2.6.2 were added for the waste activities AR4 and AR5.
- Condition 3.2.3 has been added.

The following conditions were removed as a result of the application made by the operator:

- Condition 3.8.2 was removed as a Fire Prevention Plan was submitted and included in Table S1.2.

Schedule 2 – consolidated permit

Consolidated permit issued as a separate document.

Permit

The Environmental Permitting (England and Wales) Regulations 2016

Permit number

EPR/GP3305LN

This is the consolidated permit referred to in the variation and consolidation notice for application EPR/GP3305LN/C003 authorising,

Viridor South London Limited (“the operator”),

whose registered office is

**Ardley ERF
Middleton Stoney Road
Ardley
OX27 7AA**

company registration number **08106962**

to operate an installation and waste operations at

**Beddington ERF and WTS
Beddington Lane
Croydon
CR0 4TD**

to the extent authorised by and subject to the conditions of this permit.

Name	Date
Principal Permitting Team Leader	03/06/2026

Authorised on behalf of the Environment Agency

Conditions

1 Management

1.1 General management

- 1.1.1 The operator shall manage and operate the activities:
- (a) in accordance with a written management system that identifies and minimises risks of pollution, including those arising from operations, maintenance, accidents, incidents, non-conformances, closure and those drawn to the attention of the operator as a result of complaints; and
 - (b) using sufficient competent persons and resources.
 - (c) referenced in schedule 1, table S1.1 (AR1), , in accordance with a written other than normal operating conditions (OTNOC) management plan.
- 1.1.2 Records demonstrating compliance with condition 1.1.1 shall be maintained.
- 1.1.3 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall review the written management system at least every 3 years or otherwise as requested by the Environment Agency.
- 1.1.4 Any person having duties that are or may be affected by the matters set out in this permit shall have convenient access to a copy of it kept at or near the place where those duties are carried out.
- 1.1.5 For the following activities referenced in schedule 1, table S1.1 AR4 to AR5 the operator shall comply with the requirements of an approved competence scheme.

1.2 Energy efficiency

- 1.2.1 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall:
- (a) take appropriate measures to ensure that energy is recovered with a high level of energy efficiency and energy is used efficiently in the activities.
 - (b) review and record at least every four years whether there are suitable opportunities to improve the energy efficiency of the activities; and
 - (c) take any further appropriate measures identified by a review.
- 1.2.2 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall provide and maintain steam and/or hot water pass-outs such that opportunities for the further use of waste heat may be capitalised upon should they become practicable.
- 1.2.3 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall review the viability of Combined Heat and Power (CHP) implementation at least every 4 years, or in response to any of the following factors, whichever comes sooner:
- (a) new plans for significant developments within 15 km of the installation;
 - (b) changes to the Local Plan;
 - (c) changes to the UK CHP Development Map or similar; and
 - (d) new financial or fiscal incentives for CHP.

The results shall be reported to the Agency within 2 months of each review, including where there has been no change to the original assessment in respect of the above factors.

1.3 Efficient use of raw materials

- 1.3.1 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 The operator shall:
- (a) take appropriate measures to ensure that raw materials and water are used efficiently in the activities;
 - (b) maintain records of raw materials and water used in the activities;
 - (c) review and record at least every four years whether there are suitable alternative materials that could reduce environmental impact or opportunities to improve the efficiency of raw material and water use; and
 - (d) take any further appropriate measures identified by a review.

1.4 Avoidance, recovery and disposal of wastes produced by the activities

- 1.4.1 The operator shall take appropriate measures to ensure that:
- (a) the waste hierarchy referred to in Article 4 of the Waste Framework Directive is applied to the generation of waste by the activities; and
 - (b) any waste generated by the activities is treated in accordance with the waste hierarchy referred to in Article 4 of the Waste Framework Directive; and
 - (c) where disposal is necessary, this is undertaken in a manner which minimises its impact on the environment.
- 1.4.2 The operator shall review and record at least every four years whether changes to those measures should be made and take any further appropriate measures identified by a review.

2 Operations

2.1 Permitted activities

- 2.1.1 The operator is only authorised to carry out the activities specified in schedule 1 table S1.1 (the “activities”).
- 2.1.2 For the following activities referenced in schedule 1, table S1.1 (AR1 to AR3) waste authorised by this permit shall be clearly distinguished from any other waste on the site.

2.2 The site

- 2.2.1 The activities shall not extend beyond the site, being the land shown edged in green on the site plan at schedule 7 to this permit.

2.3 Operating techniques

- 2.3.1 The activities shall, subject to the conditions of this permit, be operated using the techniques and in the manner described in the documentation specified in schedule 1, table S1.2, unless otherwise agreed in writing by the Environment Agency.
- 2.3.2 If notified by the Environment Agency that the activities are giving rise to pollution, the operator shall submit to the Environment Agency for approval within the period specified, a revision of any plan specified in schedule 1, table S1.2 or otherwise required under this permit which identifies and minimises the risks of pollution relevant to that plan, and shall implement the approved revised plan

in place of the original from the date of approval, unless otherwise agreed in writing by the Environment Agency.

- 2.3.3 Any raw materials or fuels listed in schedule 2 table S2.1 shall conform to the specifications set out in that table.
- 2.3.4 Waste shall only be accepted if:
- (a) it is of a type and quantity listed in schedule 2 table(s) S2.2, S2.3, S2.4; and
 - (b) it conforms to the description in the documentation supplied by the producer or holder.
- 2.3.5 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 waste paper, metal, plastic or glass that has been separately collected for the purpose of preparing for re-use or recycling shall not be accepted. Waste from the treatment of these separately collected wastes shall only be accepted if incineration delivers the best environmental outcome in accordance with regulation 12 of the Waste (England and Wales) Regulations 2011.
- 2.3.6 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 separately collected fractions other than those listed in condition 2.3.5 shall not be accepted unless they are unsuitable for recovery by recycling.
- 2.3.7 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall ensure that where waste produced by the activities is sent to a relevant waste operation, that operation is provided with the following information, prior to the receipt of the waste:
- (a) the nature of the process producing the waste;
 - (b) the composition of the waste;
 - (c) the handling requirements of the waste;
 - (d) the hazardous property associated with the waste, if applicable; and
 - (e) the waste code of the waste.
- 2.3.8 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall ensure that where waste produced by the activities is sent to a landfill site, it meets the waste acceptance criteria for that landfill.
- 2.3.9 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 waste shall not be charged if:
- (a) the combustion chamber temperature is below 850 °C,
 - (b) any continuous emission limit value in schedule 3 table S3.1(a) is exceeded during abnormal operation; or
 - (c) any continuous emission limit value in schedule 3 table S3.1 is exceeded, other than during abnormal operation; or
 - (d) continuous emission monitors to demonstrate compliance with any continuous emission limit value in schedule 3 table S3.1 are unavailable other than during abnormal operation; or
 - (e) there is a stoppage, disturbance or failure of the activated carbon abatement system, other than during abnormal operation.
 - (f) continuous emission monitors to demonstrate compliance with the emission limit values for particulates, TOC or CO in schedule 3 are unavailable unless alternative techniques, as agreed in writing with the Environment Agency, are used to demonstrate compliance with those emission limit values.
- 2.3.10 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall record the beginning and end of each period of “abnormal operation”.

- 2.3.11 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 during a period of “abnormal operation”, the operator shall restore normal operation of the failed equipment or replace the failed equipment as soon as possible.
- 2.3.12 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall interpret the start of the period of “abnormal operation” as the earliest of the following:
- (a) a technically unavoidable stoppage, disturbance, or failure of continuous emission monitors.
 - (b) a technically unavoidable stoppage, disturbance, or failure of the activated carbon abatement system
 - (c) Any other technically unavoidable stoppage, disturbance, or failure of the plant which is causing or could lead to an exceedance of an emission limit value in table S3.1.
- 2.3.13 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall interpret the end of the period of “abnormal operation” as the earliest of the following:
- (a) when the failed equipment is repaired and brought back into normal operation;
 - (b) when the operator initiates a shut down of the waste combustion activity, as described in the application or as agreed in writing with the Environment Agency;
 - (c) The failed equipment has not been repaired and brought back into normal operation and a single period of abnormal operation reaches a duration of 4 hours after the start of abnormal operation on an incineration line
 - (d) Abnormal operation occurs on an incineration line and the cumulative duration of abnormal operation periods over 1 calendar year has reached 60 hours on that incineration line;
- 2.3.14 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall have at least one auxiliary burner in each line which shall be operated at start up, shut down and as required during operation to ensure that the operating temperature specified in condition 2.3.9 is maintained as long as incompletely burned waste is present in the combustion chamber. Unless the temperature specified in condition 2.3.9 is maintained in the combustion chamber, such burner(s) shall be fed only with fuels which result in emissions no higher than those arising from the use of gas oil, liquefied gas or natural gas.
- 2.3.15 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 bottom ash and APC residues shall not be mixed.

2.4 Improvement programme

- 2.4.1 The operator shall complete the improvements specified in schedule 1 table S1.3 by the date specified in that table unless otherwise agreed in writing by the Environment Agency.
- 2.4.2 Except in the case of an improvement which consists only of a submission to the Environment Agency, the operator shall notify the Environment Agency within 14 days of completion of each improvement.

2.5 Technical requirements

Waste battery and accumulator treatment

- 2.5.1 Treatment of waste batteries and accumulators must meet the minimum requirements set out in Annex III, Part A of the Batteries Directive.

Hazardous waste storage and treatment

- 2.5.2 For the following activities referenced in schedule 1, table S1.1 AR4 and AR5 hazardous waste shall not be mixed, either with a different category of hazardous waste or with other waste, substances or materials, unless it is authorised by schedule 1 table S1.1 and appropriate measures are taken.

2.6 WEEE storage

- 2.6.1 Spillage collection facilities and, where appropriate, decanters and cleanser-degreasers shall be provided and used as necessary.
- 2.6.2 WEEE shall be stored in areas provided with a weatherproof covering where appropriate or in containers providing a weatherproof covering where appropriate.

3 Emissions and monitoring

3.1 Emissions to water, air or land

- 3.1.1 There shall be no point source emissions to water, air or land except from the sources and emission points listed in schedule 3 tables S3.1, S3.2 and S3.3.
- 3.1.2 The limits given in schedule 3, subject to condition 3.2.1, shall not be exceeded.
- 3.1.3 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 wastes produced at the site shall, as a minimum, be sampled and analysed in accordance with schedule 3 table S3.5 Additional samples shall be taken and tested and appropriate action taken, whenever:
- (a) disposal or recovery routes change; or
 - (b) it is suspected that the nature or composition of the waste has changed such that the route currently selected may no longer be appropriate.

3.2 Emissions limits and monitoring for emission to air for incineration plant

- 3.2.1 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the limits for emissions to air apply as follows:
- (a) The limits in table S3.1 shall not be exceeded except during periods of abnormal operation.
 - (b) The limits in table S3.1 (a) shall not be exceeded.
- 3.2.2 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 where Continuous Emission Monitors are installed to comply with the monitoring requirements in schedule 3 table S3.1 and S3.1(a); the Continuous Emission Monitors shall be used such that;
- (a) the values of the 95% confidence intervals of a single measured result at the daily emission limit value shall not exceed the following percentages of the emission limit values:

• Carbon monoxide	10%
• Sulphur dioxide	20%
• Oxides of nitrogen (NO & NO ₂ expressed as NO ₂)	20%
• Particulate matter	30%
• Total organic carbon (TOC)	30%
• Hydrogen chloride	40%
• Ammonia	40%
• Mercury	40%
 - (b) valid half-hourly average values or 10-minute averages shall be determined within the effective operating time (excluding the start-up and shut-down periods) from the measured values after having subtracted the value of the confidence intervals in condition 3.2.2 (a).

- (c) where it is necessary to calibrate or maintain the monitor and this means that data are not available for a complete half-hour or 10 minute period, the half-hourly average or 10-minute average shall in any case be considered valid if measurements are available for a minimum of 20 minutes or 7 minutes during the half-hour or 10-minute period respectively. The number of half-hourly or 10-minute averages so validated shall not exceed 5 or 15 respectively per day;
- (d) daily average values shall be calculated as follows:
 - (i) the average of valid half hourly averages or 10 minute averages over calendar day excluding half hourly averages or 10 minute averages during periods of abnormal operation. The daily average value shall be considered valid if no more than five half-hourly average or fifteen 10-minute average values in any day have been determined not to be valid;
- (e) no more than ten daily average values per year shall be determined not to be valid.

3.2.3 Emissions of periodically monitored substances shall be determined within the effective operating time (excluding the start-up and shut-down periods).

3.3 Emissions of substances not controlled by emission limits

- 3.3.1 Emissions of substances not controlled by emission limits (excluding odour) shall not cause pollution. The operator shall not be taken to have breached this condition if appropriate measures, including, but not limited to, those specified in any approved emissions management plan, have been taken to prevent or where that is not practicable, to minimise, those emissions.
- 3.3.2 The operator shall:
 - (a) if notified by the Environment Agency that the activities are giving rise to pollution, submit to the Environment Agency for approval within the period specified, an emissions management plan which identifies and minimises the risks of pollution from emissions of substances not controlled by emission limits;
 - (b) implement the approved emissions management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.
- 3.3.3 All liquids in containers, whose emission to water or land could cause pollution, shall be provided with secondary containment, unless the operator has used other appropriate measures to prevent or where that is not practicable, to minimise, leakage and spillage from the primary container.
- 3.3.4 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 periodic monitoring shall be carried out at least once every 5 years for groundwater and 10 years for soil, unless such monitoring is based on a systematic appraisal of the risk of contamination

3.4 Odour

- 3.4.1 Emissions from the activities shall be free from odour at levels likely to cause pollution outside the site, as perceived by an authorised officer of the Environment Agency, unless the operator has used appropriate measures, including, but not limited to, those specified in any approved odour management plan, to prevent or where that is not practicable to minimise the odour.
- 3.4.2 The operator shall:
 - (a) if notified by the Environment Agency that the activities are giving rise to pollution outside the site due to odour, submit to the Environment Agency for approval within the period specified, an odour management plan which identifies and minimises the risks of pollution from odour;
 - (b) implement the approved odour management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.

3.5 Noise and vibration

- 3.5.1 Emissions from the activities shall be free from noise and vibration at levels likely to cause pollution outside the site, as perceived by an authorised officer of the Environment Agency, unless the operator has used appropriate measures, including, but not limited to, those specified in any approved noise and vibration management plan to prevent or where that is not practicable to minimise the noise and vibration.
- 3.5.2 The operator shall:
- (a) if notified by the Environment Agency that the activities are giving rise to pollution outside the site due to noise and vibration, submit to the Environment Agency for approval within the period specified, a noise and vibration management plan which identifies and minimises the risks of pollution from noise and vibration;
 - (b) implement the approved noise and vibration management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.

3.6 Monitoring

- 3.6.1 The operator shall, unless otherwise agreed in writing by the Environment Agency, undertake the monitoring specified in the following tables in schedule 3 to this permit:
- (a) point source emissions specified in tables S3.1, S3.1(a), S3.2 and S3.3;
 - (b) process monitoring specified in table S3.4;
 - (c) residue quality in table S3.5
- 3.6.2 The operator shall maintain records of all monitoring required by this permit including records of the taking and analysis of samples, instrument measurements (periodic and continual), calibrations, examinations, tests and surveys and any assessment or evaluation made on the basis of such data.
- 3.6.3 Monitoring equipment, techniques, personnel and organisations employed for the emissions monitoring programme and the environmental or other monitoring specified in condition 3.6.1 shall have either MCERTS certification or MCERTS accreditation (as appropriate) unless otherwise agreed in writing by the Environment Agency. Newly installed CEMs, or CEMs replacing existing CEMs, shall have MCERTS certification and unless otherwise agreed in writing by the Environment Agency have an MCERTS certified range which is not greater than 1.5 times the daily emission limit value (ELV) specified in schedule 3 table S3.1. The CEM shall also be able to measure instantaneous values over the ranges which are to be expected during all operating conditions. If it is necessary to use more than one range setting of the CEM to achieve this requirement, the CEM shall be verified for monitoring supplementary, higher ranges. Newly installed Data handling and acquisition systems (DAHS), or DAHS replacing existing DAHS, shall have MCERTS certification.
- 3.6.4 Permanent means of access shall be provided to enable sampling/monitoring to be carried out in relation to the emission points specified in schedule 3 tables S3.1, S3.1(a), S3.2, S3.3 unless otherwise agreed in writing by the Environment Agency.

3.7 Pests

- 3.7.1 The activities shall not give rise to the presence of pests which are likely to cause pollution, hazard or annoyance outside the boundary of the site. The operator shall not be taken to have breached this condition if appropriate measures, including, but not limited to, those specified in any approved pests management plan, have been taken to prevent or where that is not practicable, to minimise the presence of pests on the site.
- 3.7.2 The operator shall:
- (a) if notified by the Environment Agency, submit to the Environment Agency for approval within the period specified, a pests management plan which identifies and minimises risks of pollution from pests;

- (b) implement the pests management plan, from the date of approval, unless otherwise agreed in writing by the Environment Agency.

3.8 Fire prevention

- 3.8.1 The operator shall take all appropriate measures to prevent fires on site and minimise the risk of pollution from them including, but not limited to, those specified in any approved fire prevention plan.

4 Information

4.1 Records

- 4.1.1 All records required to be made by this permit shall:
 - (a) be legible;
 - (b) be made as soon as reasonably practicable;
 - (c) if amended, be amended in such a way that the original and any subsequent amendments remain legible, or are capable of retrieval; and
 - (d) be retained, unless otherwise agreed in writing by the Environment Agency, for at least 6 years from the date when the records were made, or in the case of the following records until permit surrender:
 - (i) off-site environmental effects; and
 - (ii) matters which affect the condition of the land and groundwater.
- 4.1.2 The operator shall keep on site all records, plans and the management system required to be maintained by this permit, unless otherwise agreed in writing by the Environment Agency.

4.2 Reporting

- 4.2.1 The operator shall send all reports and notifications required by the permit to the Environment Agency using the contact details supplied in writing by the Environment Agency.
- 4.2.2 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 a report or reports on the performance of the activities over the previous year shall be submitted to the Environment Agency by 31 January (or other date agreed in writing by the Environment Agency) each year using the annual report form specified in schedule 4, table S4.4 or otherwise in a format agreed with the Environment Agency. The report(s) shall include as a minimum:
 - (a) a review of the results of the monitoring and assessment carried out in accordance with the permit including an interpretive review of that data;
 - (b) the annual production /treatment data set out in schedule 4 table S4.2;
 - (c) the performance parameters set out in schedule 4 table S4.3
 - (d) the functioning and monitoring of the incineration plant in a format agreed with the Environment Agency. The report shall, as a minimum requirement (as required by Chapter IV of the Industrial Emissions Directive) give an account of the running of the process and the emissions into air and water compared with the emission standards in the IED.
- 4.2.3 Within 28 days of the end of the reporting period the operator shall, unless otherwise agreed in writing by the Environment Agency, submit reports of the monitoring and assessment carried out in accordance with the conditions of this permit, as follows:
 - (a) in respect of the parameters and emission points specified in schedule 4 table S4.1;

- (b) for the reporting periods specified in schedule 4 table S4.1 and using the forms specified in schedule 4 table S4.4 ; and
 - (c) giving the information from such results and assessments as may be required by the forms specified in those tables.
- 4.2.4 For the following activities referenced in schedule 1, table S1.1 AR1 to AR3 the operator shall, unless notice under this condition has been served within the preceding four years, submit to the Environment Agency, within six months of receipt of a written notice, a report assessing whether there are other appropriate measures that could be taken to prevent, or where that is not practicable, to minimise pollution.
- 4.2.5 Within 1 month of the end of each quarter, the operator shall submit to the Environment Agency using the form made available for the purpose, the information specified on the form relating to the site and the waste accepted and removed from it during the previous quarter.

4.3 Notifications

- 4.3.1 In the event:
- (a) that the operation of the activities gives rise to an incident or accident which significantly affects or may significantly affect the environment, the operator must immediately—
 - (i) inform the Environment Agency,
 - (ii) take the measures necessary to limit the environmental consequences of such an incident or accident, and
 - (iii) take the measures necessary to prevent further possible incidents or accidents;
 - (b) of a breach of any permit condition the operator must immediately—
 - (i) inform the Environment Agency, and
 - (ii) take the measures necessary to ensure that compliance is restored within the shortest possible time;
 - (c) of a breach of permit condition which poses an immediate danger to human health or threatens to cause an immediate significant adverse effect on the environment, the operator must immediately suspend the operation of the activities or the relevant part of it until compliance with the permit conditions has been restored.
- 4.3.2 Any information provided under condition 4.3.1 (a), (b) or (c), shall be confirmed by sending the information listed in schedule 5 to this permit within the time period specified in that schedule
- 4.3.3 Where the Environment Agency has requested in writing that it shall be notified when the operator is to undertake monitoring and/or spot sampling, the operator shall inform the Environment Agency when the relevant monitoring and/or spot sampling is to take place. The operator shall provide this information to the Environment Agency at least 14 days before the date the monitoring is to be undertaken.
- 4.3.4 The Environment Agency shall be notified within 14 days of the occurrence of the following matters, except where such disclosure is prohibited by Stock Exchange rules:
- Where the operator is a registered company:
- (a) any change in the operator's trading name, registered name or registered office address; and
 - (b) any steps taken with a view to the operator going into administration, entering into a company voluntary arrangement or being wound up.
- Where the operator is a corporate body other than a registered company:
- (a) any change in the operator's name or address; and
 - (b) any steps taken with a view to the dissolution of the operator.

In any other case:

- (a) the death of any of the named operators (where the operator consists of more than one named individual);
- (b) any change in the operator's name(s) or address(es); and
- (c) any steps taken with a view to the operator, or any one of them, going into bankruptcy, entering into a composition or arrangement with creditors, or, in the case of them being in a partnership, dissolving the partnership.

4.3.5 Where the operator proposes to make a change in the nature or functioning, or an extension of the activities, which may have consequences for the environment and the change is not otherwise the subject of an application for approval under the Regulations or this permit:

- (a) the Environment Agency shall be notified at least 14 days before making the change; and
- (b) the notification shall contain a description of the proposed change in operation.

4.3.6 The Environment Agency shall be given at least 14 days notice before implementation of any part of the site closure plan.

4.4 Interpretation

4.4.1 In this permit the expressions listed in schedule 6 shall have the meaning given in that schedule.

4.4.2 In this permit references to reports and notifications mean written reports and notifications, except where reference is made to notification being made "immediately", in which case it may be provided by telephone

Schedule 1 – Operations

Table S1.1 activities			
Activity reference	Activity listed in Schedule 1 of the EP Regulations	Description of specified activity	Limits of specified activity
AR1	S5.1 A1 (b)	The incineration of non-hazardous waste in a waste incineration plant with a capacity of 3 tonnes per hour or more.	From receipt of waste to emission of exhaust gas and removal from site of waste arising. Waste types and quantities as specified in Table S2.2 of this permit.
Directly Associated Activities			
AR2	Electricity generation	Generation of 29.5MWe electrical power using a steam turbine from energy recovered from the flue gases.	--
AR3	Back up electrical generator	1.3MWth generator for providing emergency electrical power to the plant in the event of supply interruption.	Emergency use to a maximum of 500 hours operation per year. Maximum of 50 hours testing per year.
Activity reference	Description of activities for waste operations		Limits of activities
AR4	Hazardous waste transfer station	<p>D15: Storage pending any of the operations numbered D1 to D14 (excluding temporary storage, pending collection, on the site where it is produced)</p> <p>R13: Storage of wastes pending any of the operations numbered R1 to R12 (excluding temporary storage, pending collection, on the site where it is produced)</p>	<p>From receipt of waste to despatch or recovered materials and disposal of waste arising. Waste types and quantities as specified in Table S2.3 of this permit.</p> <p>Temporary storage of hazardous waste shall not exceed 50 tonnes pending any of the activities listed in Part A (1) Section 5.1, 5.2, 5.3 of the EP Regulations.</p> <p>Subject to any other requirements of this permit wastes shall be stored for no longer than 1 year prior to disposal or 3 years prior to recovery.</p> <p>Asbestos waste shall be double bagged and stored within clearly identified, segregated, secure, lockable containers on an impermeable surface with sealed drainage system.</p>
AR5	Non-hazardous waste transfer and treatment station	D15: Storage pending any of the operations numbered D1 to D14 (excluding temporary storage, pending	<p>From receipt of waste to despatch or recovered materials and disposal of waste arising.</p> <p>Treatment consisting only of manual sorting, separation,</p>

		<p>collection, on the site where it is produced)</p> <p>R13: Storage of wastes pending any of the operations numbered R1 to R12 (excluding temporary storage, pending collection, on the site where it is produced)</p> <p>D14: Repackaging prior to submission to any of the operations numbered D1 to 13</p> <p>D9: Physico-chemical treatment not specified elsewhere in Annex IIA which results in final compounds or mixtures which are discarded by means of any of the operations numbered D1 to D8 and D10 to D12</p> <p>R3: Recycling/reclamation of organic substances which are not used as solvents</p> <p>R4: Recycling/reclamation of metals and metal compounds</p> <p>R5: Recycling/reclamation of other inorganic materials</p>	<p>screening, baling, shredding, crushing or compaction of non-hazardous waste into different components for disposal, (no more than 50 tonnes per day) or recovery.</p> <p>No shredding, crushing or compaction of WEEE, batteries or healthcare waste is permitted.</p> <p>Unless stored or treated outside as specified waste:</p> <p>a) all bulking, transfer or treatment of non-hazardous waste shall be carried out inside a building;</p> <p>b) all non-hazardous waste shall be stored in a building or within a secure container.</p> <p>c) all non-hazardous waste shall be stored and treated on an impermeable surface with sealed drainage system.</p> <p>Specified waste shall be stored and treated on hard standing or on an impermeable surface with sealed drainage system.</p> <p>No more than a total of 50 tonnes of intact and shredded waste vehicle tyres (waste codes 16 01 03 and 19 12 04) shall be stored at the site.</p> <p>Waste types and quantities as specified in Table S2.4 of this permit.</p> <p>Subject to any other requirements of this permit wastes shall be stored for no longer than 1 year prior to disposal or 3 years prior to recovery.</p>
--	--	--	---

Description	Parts	Date Received
Application EPR/TP3836CT	Parts B2 and B3 of the Application Form. The Supporting Information Document including associated Annex sections. Responses to questions 1, 4 and 5 of the Not Duly Made letter.	Duly made 17/08/2012
Response to Schedule 5 Information Request Notice issued 05/10/2012	Responses to questions 2, 3, 4 and 5.	12/10/2012

Table S1.2 Operating techniques		
Description	Parts	Date Received
Response to Schedule 5 Notice dated 08/11/2012	Response to question 1 – noise impact assessment	21/11/2012
Additional information	Noise Impact Assessment	04/03/2013
Additional Information	Short term assessment of metals & abnormal emissions revised assessment	14/03/2013
Additional Information	Report S1190-0900-0014JRS – Final - revised Air Quality Assessment on the Impact of NO2 at Sensitive Receptors – supersedes all previous submissions.	30/03/2013
Additional Information	Clarification on abnormal emission for short term assessment of metals	08/04/2013
Variation application EPR/TP3836CT/V004	Parts C2 and C3 of the Application Form and document 'Supporting Information - EP Variation', dated 08/10/2020.	14/10/2020
Response to regulation 61 notice	Operating techniques as set out in the response to the regulation 61 notice.	23/06/2022 & 17/08/2022
Additional Information	Beddington ERF Waste Treatment Facility Fire Prevention Plan (Version 1.4), issue date 18/06/2018 Operation of the shredder – Schedule 5 Notice response – question 5	25/05/2023
Additional Information	Waste Acceptance Procedure, document ref ERF-BED-OPS-LMI-ENV-022, version 3, dated 23/05/2023	21/06/2023

Table S1.3 Improvement programme requirements		
Reference	Requirement	Date
IC1	The Operator shall submit a written report to the Environment Agency on the implementation of its Environmental Management System and the progress made in the certification of the system by an external body or if appropriate submit a schedule by which the EMS will be certified.	Complete
IC2	The Operator shall submit a written proposal to the Environment Agency to carry out tests to determine the size distribution of the particulate matter in the exhaust gas emissions to air from emission point A1& A2, identifying the fractions within the PM10 and PM2.5 ranges. The proposal shall include a timetable for approval by the Environment Agency to carry out such tests and produce a report on the results. On receipt of written agreement by the Environment Agency to the proposal and the timetable, the Operator shall carry out the tests and submit to the Environment Agency a report on the results.	Complete
IC3	The Operator shall submit a written report to the Environment Agency on the commissioning of the installation. The report shall summarise the environmental performance of the plant as installed against the design parameters set out in the Application. The report shall also include a review of the performance of the facility against the conditions of this permit and details of procedures developed during commissioning for achieving and demonstrating compliance with permit conditions.	Complete
IC4	The Operator shall carry out checks to verify the residence time, minimum temperature and oxygen content of the exhaust gases in the furnace	Complete

Table S1.3 Improvement programme requirements		
Reference	Requirement	Date
	whilst operating under the anticipated most unfavourable operating conditions. The results shall be submitted in writing to the Environment Agency.	
IC5	<p>The Operator shall submit a written report to the Environment Agency describing the performance and optimisation of the Selective Non Catalytic Reduction (SNCR) system and combustion settings to minimise oxides of nitrogen (NOx) emissions within the emission limit values described in this permit with the minimisation of nitrous oxide (N2O) and ammonia (NH3) emissions. The report shall include an assessment of the level of NOx, N2O and NH3 emissions that can be achieved under optimum operating conditions.</p> <p>The report shall also provide details of the optimisation (including dosing rates) for the control of acid gases and dioxins.</p>	Complete
IC6	The Operator shall submit a written summary report to the Environment Agency to confirm by the results of calibration and verification testing that the performance of Continuous Emission Monitors for parameters as specified in Table S3.1 and Table S3.1(a) complies with the requirements of BS EN 14181, specifically the requirements of QAL1, QAL2 and QAL3.	Complete
IC7	The Operator shall carry out monitoring of NO2 and NO to determine the primary proportion of NO2 in the emissions to air and to monitor the performance of SNCR on the flue gas. Emissions monitoring data shall be collected over a representative period of operation to be agreed in writing with the Environment Agency. A written report on the monitoring shall be made to the Environment Agency.	Complete
IC8	<p>The Operator shall carry out an assessment of the impact of emissions to air of the following component metals subject to emission limit values, Manganese (Mn), Lead (Pb) and Nickel (Ni). A report on the assessment shall be made to the Environment Agency.</p> <p>Emissions monitoring data obtained during the first year of operation shall be used to compare the actual emissions with those assumed in the impact assessment submitted with the Application. An assessment shall be made of the impact of each metal against the relevant EQS/EAL. In the event that the assessment shows that an EQS/EAL can be exceeded, the report shall include proposals for further investigative work.</p>	Complete
IC9	The Operator shall provide notification to the Environment Agency of reprogramming of the CEMs to the 10-minute average ELV for CO. Following acknowledgement receipt from the Environment Agency, the ELV and reference period for CO emission point reference locations A1 and A2 shall be as per Note (2) in Tables S3.1 and S3.1(a).	Complete

Table S1.3 Improvement programme requirements		
Reference	Requirement	Date
	The notification requirements of condition 2.4.2 shall be deemed to have been complied with on submission of the information above.	
IC10	<p>The operator shall perform a study to determine the extent to which the operation of the current systems in place at the plant to minimise NOx emissions can be further optimised such that emissions are reduced as far as possible below, 165 mg/Nm³ as a daily average, without significantly increasing emissions of other pollutants or having a significant negative effect on plant operation, reliability or bottom ash quality. The study shall be based on the results of trials carried out at the installation and shall have regard to the recommendations for test conditions set out in Section 5.4.3 of report titled 'Establishing factors that influence NOx reduction at waste incineration plant to levels below the upper end of the BAT-AELs' (dated 14/01/2022), or other methodology agreed in writing with the Environment Agency. A written report of the study shall be submitted to the Environment Agency which shall include but not necessarily be limited to the following:</p> <ul style="list-style-type: none"> • A brief description of the currently installed measures at the installation to minimise NOx emissions, including details of how the reagent dosing system responds to emissions monitoring data and historic data which illustrates the current achievable level of daily NOx emissions. • The results of trials conducted to further reduce daily average NOx emissions using currently installed measures, including: <ul style="list-style-type: none"> ○ a description of the parameters that were varied during the trial e.g. ammonia or urea feed rates, physical form of urea injected, air flows, and the range over which they were varied ○ the levels of NOx achieved and associated levels of ammonia and nitrous oxide emissions and reagent consumption ○ observed effects and predicted long-term impacts on plant operation, reliability and maintenance regime ○ any changes to the composition of the bottom ash and boiler ash and the implications of those changes for the ability to process and use the ash, as well as for the pollution potential of the ash both during processing and its subsequent use as a secondary aggregate ○ any other relevant cross-media effects <p>The report shall also include a description of the extent to which current systems in place at the plant to minimise NOx emissions can be optimised on a permanent basis, including justification and an implementation plan where relevant.</p>	Complete
IC11	The operator shall submit a report to the Environment Agency on whether waste feed to the plant can be proven to have a low and stable mercury content. The report shall have regard to BAT 4 of the BAT conclusions, be based on historic mercury emissions monitoring data and have regard to the Environment Agency Mercury Monitoring Protocol.	Complete
IC12	The operator shall submit a report to the Environment Agency on whether dioxin emissions to air are stable. The report shall have regard to BAT 4	Complete

Table S1.3 Improvement programme requirements		
Reference	Requirement	Date
	of the BAT conclusions, be based on historic dioxin emissions monitoring data and have regard to the Environment Agency Dioxins Monitoring Protocol.	

Schedule 2 – Waste types, raw materials and fuels

Table S2.1 Raw materials and fuels	
Raw materials and fuel description	Specification
Fuel Oil	< 0.1% sulphur content

Table S2.2 Permitted waste types and quantities for activity reference AR1 – incineration plant	
Maximum quantity	Maximum quantity 382,286 tonnes per year in total and 21.82 tonnes per line per hour.
Waste code	Description
02	Wastes from Agriculture, Horticulture, Aquaculture, Forestry, Hunting and Fishing, Food Preparation and Processing
02 01	wastes from agriculture, horticulture, aquaculture, forestry, hunting and fishing.
02 01 03	plant tissue waste
02 01 04	waste plastic (except packaging)
02 01 07	wastes from forestry
02 01 09	agrochemical waste other than those mentioned in 02 01 08*
02 03	wastes from fruit, vegetable, cereal or other vegetable origin material preparation and processing
02 03 04	materials unsuitable for consumption or processing
02 05	wastes from the dairy products industry
02 05 01	materials unsuitable for consumption or processing
02 06	wastes from the baking and confectionery industry
02 06 01	materials unsuitable for consumption or processing
02 06 02	wastes from preserving agents
03	Wastes from Wood Processing and the Production of Panels and Furniture, Pulp, paper and Cardboard.
03 01	wastes from wood processing and the production of panels and furniture.
03 01 01	waste bark and cork
03 01 05	sawdust, shavings, cuttings, wood, particle board and veneer other than those mentioned in 03 01 04*.
03 03	wastes from pulp, paper and cardboard production and processing
03 03 01	waste bark wood

Table S2.2 Permitted waste types and quantities for activity reference AR1 – incineration plant	
Maximum quantity	Maximum quantity 382,286 tonnes per year in total and 21.82 tonnes per line per hour.
Waste code	Description
03 03 07	mechanically separated rejects from pulping of waste paper and cardboard
03 03 08	wastes from sorting of paper and cardboard destined for recycling
04	Wastes from the Leather, Fur and Textile Industries
04 02	wastes from the textile industry
04 02 09	wastes from composite materials (impregnated textile, elastomer, plastomer)
04 02 10	organic matter from natural products (eg. grease, wax)
04 02 21	wastes from unprocessed textile fibres
04 02 22	wastes from processed textile fibres
07	Wastes from Organic Chemical Processes
07 02	wastes from the MFSU of plastics, synthetic rubber and man-made fibres
07 02 13	waste plastic
09	Wastes from the Photographic Industry
09 01	wastes from the photographic industry
09 01 07	photographic film and paper containing silver or silver compounds
09 01 08	photographic film and paper free of silver or silver compounds
09 01 10	single-use cameras without batteries
12	Wastes from Shaping and Physical and Mechanical Surface Treatment of Metals and Plastics
12 01	wastes from shaping and physical and mechanical surface treatment of metals and plastics
12 01 05	plastics shavings and turnings
15	Waste Packaging, Absorbants, Wiping Cloths, Filter Materials and Protective Clothing not otherwise specified
15 01	packaging (including separately collected municipal packaging waste)
15 01 01	paper and cardboard packaging
15 01 02	plastic packaging
15 01 03	wooden packaging
15 01 05	composite packaging
15 01 06	mixed packaging
15 01 09	textile packaging
15 02	absorbants, filter materials, wiping cloths and protective clothing
15 02 03	absorbents, filter materials, wiping cloths and protective clothing other than those mentioned in 15 02 02*
16	Wastes Not Otherwise Specified in the List
16 01	end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08)
16 01 19	plastic

Table S2.2 Permitted waste types and quantities for activity reference AR1 – incineration plant	
Maximum quantity	Maximum quantity 382,286 tonnes per year in total and 21.82 tonnes per line per hour.
Waste code	Description
17	Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 02	wood, glass and plastic
17 02 01	wood
17 02 03	plastic
17 09	other construction and demolition wastes
17 09 04	mixed construction and demolition wastes other than those mentioned in 17 09 01*, 17 09 02* and 17 09 03*
18	Wastes from Human or Animal Health Care and/or Related Research (except kitchen and restaurant wastes not arising from immediate health care)
18 01	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 04	wastes whose collection and disposal is not subject to special requirements in order to prevent infection(for example dressings, plaster casts, linen, disposable clothing, diapers)
18 01 07	chemicals other than those mentioned in 18 01 06
18 01 09	medicines other than those mentioned in 18 01 08
18 02	wastes from research, diagnosis, treatment or prevention of disease involving animals
18 02 03	wastes whose collection and disposal is not subject to special requirements in order to prevent infection
18 02 06	chemicals other than those mentioned in 18 02 05
18 02 08	medicines other than those mentioned in 18 02 07
19	Wastes from Waste Management Facilities, Off-Site Waste Water Treatment Plants and the Preparation of Water for Human Consumption and Water for Industrial Use
19 02	wastes from the physiochemical treatments of waste (including dechromatation, decyanidation, neutralization)
19 02 03	premixed wastes composed only of non-hazardous wastes
19 02 10	combustible wastes other than those mentioned in 19 02 08* and 19 02 09*
19 03	stabilised/solidified wastes
19 03 05	stabilised wastes other than those mentioned in 19 03 04
19 03 07	solidified wastes other than those mentioned in 19 03 06
19 05	wastes from aerobic treatment of solid wastes
19 05 01	non-composted fraction of municipal and similar wastes
19 05 02	non-composted fraction of animal and vegetable waste
19 05 03	off-specification compost
19 06	wastes from anaerobic treatment of waste
19 06 04	digestate from anaerobic treatment of municipal waste
19 06 06	digestate from anaerobic treatment of animal and vegetable waste

Table S2.2 Permitted waste types and quantities for activity reference AR1 – incineration plant	
Maximum quantity	Maximum quantity 382,286 tonnes per year in total and 21.82 tonnes per line per hour.
Waste code	Description
19 08	wastes from waste water treatment plants not otherwise specified
19 08 01	screenings
19 08 14	sludges from other treatment of industrial waste water other than those mentioned in 19 08 13
19 10	wastes from shredding of metal-containing wastes
19 10 04	fluff-light fraction and dust other than those mentioned in 19 10 03
19 12	wastes from the mechanical treatment of waste (eg. sorting, crushing, compacting, pelletising) not otherwise specified
19 12 01	paper and cardboard
19 12 04	plastic and rubber
19 12 07	wood other than that mentioned in 19 12 06*
19 12 08	textiles
19 12 10	combustible waste (refuse derived fuel)
19 12 12	other wastes (including mixtures of materials) from mechanical treatment of wastes other than those mentioned in 19 12 11*
20	Municipal Wastes (Household Waste and Similar Commercial, Industrial and Institutional Wastes)
20 01	separately collected fractions (except 15 01)
20 01 01	paper and cardboard
20 01 08	bio-degradable kitchen and canteen waste
20 01 10	clothes
20 01 11	textiles
20 01 25	edible oil and fat
20 01 28	paint, inks, adhesives and resins other than those mentioned in 20 01 27*
20 01 30	detergents other than those mentioned in 20 01 29*
20 01 32	medicines other than those mentioned in 20 01 31*
20 01 36	discarded electrical and electronic equipment other than those mentioned in 20 01 21*, 20 01 23* and 20 01 35*
20 01 38	wood other than that mentioned in 20 01 37* (i.e. other than that containing dangerous substances)
20 01 39	plastics
20 01 99	other fractions not otherwise specified
20 02	garden and park wastes (including cemetery waste)
20 02 01	bio-degradable wastes
20 03	other municipal wastes
20 03 01	mixed municipal wastes
20 03 02	wastes from markets
20 03 03	street cleaning residues

Table S2.2 Permitted waste types and quantities for activity reference AR1 – incineration plant	
Maximum quantity	Maximum quantity 382,286 tonnes per year in total and 21.82 tonnes per line per hour.
Waste code	Description
20 03 06	waste from sewage cleaning
20 03 07	bulky waste

Table S2.3 Permitted waste types and quantities for activity reference AR4 – hazardous waste transfer station	
Maximum quantity	The maximum quantity of all waste accepted at the site under activities AR4 – AR5 shall be less than 75,000 tonnes per year.
Waste code	Description
16	Wastes not otherwise specified in the list
16 02	wastes from electrical and electronic equipment
16 02 13*	discarded equipment containing hazardous components other than those mentioned in 16 02 09 to 16 02 12
16 05	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
17	Construction and demolition wastes (including excavated soil from contaminated sites)
17 06	insulation materials and asbestos-containing construction materials
17 06 01*	insulation materials containing asbestos
17 06 05*	construction materials containing asbestos
18	Wastes from human or animal health care and/or related research (except kitchen and restaurant wastes not arising from immediate health care)
18 01	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 03*	wastes whose collection and disposal is subject to special requirements in order to prevent infection
18 02	wastes from research, diagnosis, treatment or prevention of disease involving animals
18 02 02*	wastes whose collection and disposal is subject to special requirements in order to prevent infection
20	Municipal wastes (household waste and similar commercial, industrial and institutional wastes) including separately collected fractions
20 01	separately collected fractions (except 15 01)
20 01 13*	solvents
20 01 14*	acids
20 01 15*	alkalines
20 01 17*	photochemicals
20 01 19*	pesticides
20 01 21*	fluorescent tubes and other mercury-containing waste
20 01 23*	discarded equipment containing chlorofluorocarbons

Table S2.3 Permitted waste types and quantities for activity reference AR4 – hazardous waste transfer station	
Maximum quantity	The maximum quantity of all waste accepted at the site under activities AR4 – AR5 shall be less than 75,000 tonnes per year.
Waste code	Description
20 01 33*	batteries and accumulators included in 16 06 01, 16 06 02 or 16 06 03 and unsorted batteries and accumulators containing these batteries
20 01 35*	discarded electrical and electronic equipment other than those mentioned in 20 01 21 and 20 01 23 containing hazardous components

Table S2.4 Permitted waste types and quantities for activity reference AR5 – non-hazardous waste transfer and treatment station	
Maximum quantity	The maximum combined quantity of waste accepted at the site under activities AR4 and AR5 shall be less than 75,000 tonnes per year.
Exclusions	Wastes having any of the following characteristics shall not be accepted: <ul style="list-style-type: none"> • Consisting solely or mainly of dusts, powders or loose fibres • Wastes that are in a form which is either sludge or liquid
Waste code	Description
02	Wastes from agriculture, horticulture, aquaculture, forestry, hunting and fishing, food preparation and processing
02 01	wastes from agriculture, horticulture, aquaculture, forestry, hunting and fishing
02 01 03	plant-tissue waste
02 01 04	waste plastics (except packaging)
02 01 07	wastes from forestry
02 01 09	agrochemical waste other than those mentioned in 02 01 08
02 01 10	waste metal
02 02	wastes from the preparation and processing of meat, fish and other foods of animal origin
02 02 03	materials unsuitable for consumption or processing
02 03	wastes from fruit, vegetables, cereals, edible oils, cocoa, coffee, tea and tobacco preparation and processing; conserve production; yeast and yeast extract production, molasses preparation and fermentation
02 03 04	materials unsuitable for consumption or processing
02 05	wastes from the dairy products industry
02 05 01	materials unsuitable for consumption or processing
02 06	wastes from the baking and confectionery industry
02 06 01	materials unsuitable for consumption or processing
02 06 02	wastes from preserving agents
02 07	wastes from the production of alcoholic and non-alcoholic beverages (except coffee, tea and cocoa)
02 07 01	wastes from washing, cleaning and mechanical reduction of raw materials
02 07 02	wastes from spirits distillation

Table S2.4 Permitted waste types and quantities for activity reference AR5 – non-hazardous waste transfer and treatment station

Maximum quantity	The maximum combined quantity of waste accepted at the site under activities AR4 and AR5 shall be less than 75,000 tonnes per year.
Exclusions	Wastes having any of the following characteristics shall not be accepted: <ul style="list-style-type: none"> • Consisting solely or mainly of dusts, powders or loose fibres • Wastes that are in a form which is either sludge or liquid
Waste code	Description
02 07 04	materials unsuitable for consumption or processing
03	Wastes from wood processing and the production of panels and furniture, pulp, paper and cardboard
03 01	wastes from wood processing and the production of panels and furniture
03 01 01	waste bark and cork
03 01 05	sawdust, shavings, cuttings, wood, particle board and veneer other than those mentioned in 03 01 04
03 03	wastes from pulp, paper and cardboard production and processing
03 03 01	waste bark and wood
03 03 07	mechanically separated rejects from pulping of waste paper and cardboard
03 03 08	wastes from sorting of paper and cardboard destined for recycling
03 03 10	fibre rejects, fibre-, filler- and coating-sludges from mechanical separation
04	Wastes from the leather, fur and textile industries
04 01	wastes from the leather and fur industry
04 01 08	waste tanned leather (blue sheetings, shavings, cuttings, buffing dust) containing chromium
04 01 09	wastes from dressing and finishing
04 02	wastes from the textile industry
04 02 09	wastes from composite materials (impregnated textile, elastomer, plastomer)
04 02 10	organic matter from natural products (for example grease, wax)
04 02 21	wastes from unprocessed textile fibres
04 02 22	wastes from processed textile fibres
07	Wastes from organic chemical processes
07 02	wastes from the MFSU of plastics, synthetic rubber and man-made fibres
07 02 13	waste plastic
09	Wastes from the photographic industry
09 01	wastes from the photographic industry
09 01 07	photographic film and paper containing silver or silver compounds
09 01 08	photographic film and paper free of silver or silver compounds
09 01 10	single-use cameras without batteries
09 01 12	single-use cameras containing batteries other than those mentioned in 09 01 11
10	Wastes from thermal processes
10 01	wastes from power stations and other combustion plants (except 19)
10 01 01	bottom ash, slag and boiler dust (excluding boiler dust mentioned in 10 01 04)

Table S2.4 Permitted waste types and quantities for activity reference AR5 – non-hazardous waste transfer and treatment station

Maximum quantity	The maximum combined quantity of waste accepted at the site under activities AR4 and AR5 shall be less than 75,000 tonnes per year.
Exclusions	Wastes having any of the following characteristics shall not be accepted: <ul style="list-style-type: none"> • Consisting solely or mainly of dusts, powders or loose fibres • Wastes that are in a form which is either sludge or liquid
Waste code	Description
12	Wastes from shaping and physical and mechanical surface treatment of metals and plastics
12 01	wastes from shaping and physical and mechanical surface treatment of metals and plastics
12 01 05	plastics shavings and turnings
15	Waste packaging, absorbents, wiping cloths, filter materials and protective clothing not otherwise specified
15 01	packaging (including separately collected municipal packaging waste)
15 01 01	paper and cardboard packaging
15 01 02	plastic packaging
15 01 03	wooden packaging
15 01 04	metallic packaging
15 01 05	composite packaging
15 01 06	mixed packaging
15 01 07	glass packaging
15 01 09	textile packaging
15 02	absorbents, filter materials, wiping cloths and protective clothing
15 02 03	absorbents, filter materials, wiping cloths and protective clothing other than those mentioned in 15 02 02
16	Wastes not otherwise specified in the list
16 01	end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08)
16 01 03	end-of-life tyres
16 01 19	plastic
16 02	wastes from electrical and electronic equipment
16 02 14	discarded equipment other than those mentioned in 16 02 09 to 16 02 13
16 02 16	components removed from discarded equipment other than those mentioned in 16 02 15
16 03	off-specification batches and unused products
16 03 04	inorganic wastes other than those mentioned in 16 03 03
16 03 06	organic wastes other than those mentioned in 16 03 05
16 05	gases in pressure containers and discarded chemicals
16 05 05	gases in pressure containers other than those mentioned in 16 05 04
16 06	batteries and accumulators
16 06 04	alkaline batteries (except 16 06 03)

Table S2.4 Permitted waste types and quantities for activity reference AR5 – non-hazardous waste transfer and treatment station

Maximum quantity	The maximum combined quantity of waste accepted at the site under activities AR4 and AR5 shall be less than 75,000 tonnes per year.
Exclusions	Wastes having any of the following characteristics shall not be accepted: <ul style="list-style-type: none"> • Consisting solely or mainly of dusts, powders or loose fibres • Wastes that are in a form which is either sludge or liquid
Waste code	Description
16 06 05	other batteries and accumulators
16 11	waste linings and refractories
16 11 02	carbon-based linings and refractories from metallurgical processes others than those mentioned in 16 11 01
16 11 04	other linings and refractories from metallurgical processes other than those mentioned in 16 11 03
16 11 06	linings and refractories from non-metallurgical processes others than those mentioned in 16 11 05
17	Construction and demolition wastes (including excavated soil from contaminated sites)
17 01	concrete, bricks, tiles and ceramics
17 01 01	concrete
17 01 02	bricks
17 01 03	tiles and ceramics
17 01 07	mixtures of concrete, bricks, tiles and ceramics other than those mentioned in 17 01 06
17 02	wood, glass and plastic
17 02 01	wood
17 02 02	glass
17 02 03	plastic
17 03	bituminous mixtures, coal tar and tarred products
17 03 02	bituminous mixtures other than those mentioned in 17 03 01
17 04	metals (including their alloys)
17 04 01	copper, bronze, brass
17 04 02	aluminium
17 04 03	lead
17 04 04	zinc
17 04 05	iron and steel
17 04 06	tin
17 04 07	mixed metals
17 04 11	cables other than those mentioned in 17 04 10
17 05	soil (including excavated soil from contaminated sites), stones and dredging spoil
17 05 04	soil and stones other than those mentioned in 17 05 03
17 06	insulation materials and asbestos-containing construction materials

Table S2.4 Permitted waste types and quantities for activity reference AR5 – non-hazardous waste transfer and treatment station

Maximum quantity	The maximum combined quantity of waste accepted at the site under activities AR4 and AR5 shall be less than 75,000 tonnes per year.
Exclusions	Wastes having any of the following characteristics shall not be accepted: <ul style="list-style-type: none"> • Consisting solely or mainly of dusts, powders or loose fibres • Wastes that are in a form which is either sludge or liquid
Waste code	Description
17 06 04	insulation materials other than those mentioned in 17 06 01 and 17 06 03
17 08	gypsum-based construction material
17 08 02	gypsum-based construction materials other than those mentioned in 17 08 01
17 09	other construction and demolition wastes
17 09 04	mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03
18	Wastes from human or animal health care and/or related research (except kitchen and restaurant wastes not arising from immediate health care)
18 01	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 01	sharps (except 18 01 03)
18 01 04	wastes whose collection and disposal is not subject to special requirements in order to prevent infection (for example dressings, plaster casts, linen, disposable clothing, diapers)
18 01 09	medicines other than those mentioned in 18 01 08
19	Wastes from waste management facilities, off-site waste water treatment plants and the preparation of water intended for human consumption and water for industrial use
19 01	wastes from incineration or pyrolysis of waste
19 01 02	ferrous materials removed from bottom ash
19 01 12	bottom ash and slag other than those mentioned in 19 01 11
19 02	wastes from physico/chemical treatments of waste (including dechromatation, decyanidation, neutralisation)
19 02 03	premixed wastes composed only of non-hazardous wastes
19 02 10	combustible wastes other than those mentioned in 19 02 08 and 19 02 09
19 03	stabilised/solidified wastes
19 03 05	stabilised wastes other than those mentioned in 19 03 04
19 03 07	solidified wastes other than those mentioned in 19 03 06
19 05	wastes from aerobic treatment of solid wastes
19 05 01	non-composted fraction of municipal and similar wastes
19 05 02	non-composted fraction of animal and vegetable waste
19 05 03	off-specification compost
19 12	wastes from the mechanical treatment of waste (for example sorting, crushing, compacting, pelletising) not otherwise specified
19 12 01	paper and cardboard
19 12 02	ferrous metal

Table S2.4 Permitted waste types and quantities for activity reference AR5 – non-hazardous waste transfer and treatment station

Maximum quantity	The maximum combined quantity of waste accepted at the site under activities AR4 and AR5 shall be less than 75,000 tonnes per year.
Exclusions	Wastes having any of the following characteristics shall not be accepted: <ul style="list-style-type: none"> • Consisting solely or mainly of dusts, powders or loose fibres • Wastes that are in a form which is either sludge or liquid
Waste code	Description
19 12 03	non-ferrous metal
19 12 04	plastic and rubber
19 12 05	glass
19 12 07	wood other than that mentioned in 19 12 06
19 12 08	textiles
19 12 09	minerals (for example sand, stones)
19 12 10	combustible waste (refuse derived fuel)
19 12 12	other wastes (including mixtures of materials) from mechanical treatment of wastes other than those mentioned in 19 12 11
20	Municipal wastes (household waste and similar commercial, industrial and institutional wastes) including separately collected fractions
20 01	separately collected fractions (except 15 01)
20 01 01	paper and cardboard
20 01 02	glass
20 01 08	biodegradable kitchen and canteen waste
20 01 10	clothes
20 01 11	textiles
20 01 34	batteries and accumulators other than those mentioned in 20 01 33
20 01 36	discarded electrical and electronic equipment other than those mentioned in 20 01 21, 20 01 23 and 20 01 35
20 01 38	wood other than that mentioned in 20 01 37
20 01 39	plastics
20 01 40	metals
20 01 41	wastes from chimney sweeping
20 01 99	other fractions not otherwise specified; comprising separately collected fractions of municipal clinical waste (not arising from healthcare and /or related research i.e. not including natal care, diagnosis, treatment or prevention of disease) which is subject to special requirements in order to prevent infection. other fractions not otherwise specified comprising only non-clinical human and animal offensive/hygiene waste (not arising from healthcare and /or related research i.e. not including natal care, diagnosis, treatment or prevention of disease) which is subject to special requirements in order to prevent infection.
20 02	garden and park wastes (including cemetery waste)
20 02 01	biodegradable waste
20 02 02	soil and stones

Table S2.4 Permitted waste types and quantities for activity reference AR5 – non-hazardous waste transfer and treatment station	
Maximum quantity	The maximum combined quantity of waste accepted at the site under activities AR4 and AR5 shall be less than 75,000 tonnes per year.
Exclusions	Wastes having any of the following characteristics shall not be accepted: <ul style="list-style-type: none"> • Consisting solely or mainly of dusts, powders or loose fibres • Wastes that are in a form which is either sludge or liquid
Waste code	Description
20 03	other municipal wastes
20 03 01	mixed municipal waste
20 03 02	waste from markets
20 03 03	street-cleaning residues
20 03 07	bulky waste
20 03 99	other municipal waste not otherwise specified - sanitary waste from schools and offices only

Schedule 3 – Emissions and monitoring

Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
A1 & A2 - as shown on the Site Plan in Schedule 7	Particulate matter	Incineration exhausts gases	30 mg/m ³	½-hr average	Continuous	EN 14181
	Particulate matter		5 mg/m ³	daily average	Continuous	EN 14181
	Total Organic Carbon (TOC)		20 mg/m ³	½-hr average	Continuous	EN 14181
	Total Organic Carbon (TOC)		10 mg/m ³	daily average	Continuous	EN 14181
	Hydrogen chloride		60 mg/m ³	½-hr average	Continuous	EN 14181
	Hydrogen chloride		8 mg/m ³	daily average	Continuous	EN 14181
	Carbon monoxide		150 mg/m ³	95% of all 10-minute averages in any 24-hour period	Continuous	EN 14181
	Carbon monoxide		50 mg/m ³	daily average	Continuous	EN 14181
	Sulphur dioxide		200 mg/m ³	½-hr average	Continuous	EN 14181
	Sulphur dioxide		40 mg/m ³	daily average	Continuous	EN 14181
	Oxides of nitrogen (NO and NO ₂ expressed as NO ₂)		400 mg/m ³	½-hr average	Continuous	EN 14181
Oxides of nitrogen (NO and NO ₂ expressed as NO ₂)	165 mg/m ³	daily average	Continuous	EN 14181		

Table S3.1 Point source emissions to air – emission limits and monitoring requirements.						
Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
	Hydrogen fluoride		1 mg/m ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually	CEN TS 17340
	Cadmium & thallium and their compounds (total)		0.02 mg/m ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually	BS EN 14385
	Mercury and its compounds		0.02 mg/m ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually Not required if continuous monitoring has been specified by the Environment Agency	BS EN 13211
	Mercury and its compounds		0.02 mg/m ³	Daily average	Continuous Not required unless continuous monitoring has been specified by the Environment Agency in line with sampling protocol	EN 14181
	Sb, As, Pb, Cr, Co, Cu, Mn, Ni and V and their compounds (total)		0.3 mg/m ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually	BS EN 14385
	Exhaust gas temperature		No limit set	-	Continuous	Traceable to national standards
	Exhaust gas pressure		No limit set	-	Continuous	Traceable to national standards
	Exhaust gas flow		No limit set	-	Continuous	BS EN 16911-2

Table S3.1 Point source emissions to air – emission limits and monitoring requirements.						
Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
	Exhaust gas oxygen content		No limit set	-	Continuous	EN 14181
	Exhaust gas water vapour content		No limit set	-	Continuous	EN 14181
	Ammonia (NH ₃)		12 mg/m ³	Daily average	Continuous	BS EN 14181
	Nitrous oxide (N ₂ O)		No limit set	½-hr average and daily average	Continuous	EN 14181
	Carbon dioxide		No limit set	Continuous	Continuous	EN 14181
	Dioxins / furans (I-TEQ)		0.06 ng/m ³ and 0.08 ng/m ³ if long term limit is specified by the Environment Agency in line with sampling protocol	periodic over minimum 6 hours, maximum 8 hour period and value over sampling period of 2 to 4 weeks for long term sampling	Bi-annually and long term sampling if specified by the Environment Agency in line with sampling protocol	EN 1948 Parts 1, 2 and 3 and CEN TS 1948-5 if specified by the Environment Agency in line with sampling protocol
	Dioxin-like PCBs (WHO-TEQ Humans / Mammals, Fish, Birds)		No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	EN 1948 Parts 1, 2 and 4

Table S3.1 Point source emissions to air – emission limits and monitoring requirements.						
Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard(s) or method(s)
	Dioxins / furans (WHO-TEQ Humans / Mammals, Fish, Birds)		No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	BS EN 1948 Parts 1, 2 and 3
	Polybrominated dibenzodioxins and furans		No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	Method based on procedural requirements of EN 1948
	Specific individual polycyclic aromatic hydrocarbons (PAHs), as specified in Schedule 6.		No limit set	periodic over minimum 6 hours, maximum 8 hour period	Annually	BS ISO 11338 Parts 1 and 2.
A3 - as shown on the Site Plan in Schedule 7	Carbon monoxide	Back-up electrical generator	No limit set	In line with web guide 'Monitoring stack emissions: low risk MCPs and specified generators' Published 20 January 2026 (formerly known as TGN M5)	Every 1500 hours of operation or once every five years (whichever comes first) from 01/01/2030	In line with web guide 'Monitoring stack emissions: low risk MCPs and specified generators' Published 20 January 2026 (formerly known as TGN M5)
A4 – as shown on the Site Plan in Schedule 7	Oxides of nitrogen	Shredder in waste transfer station	No limit set	--	--	--
	Particulate matter		No limit set	--	--	--
	Sulphur dioxide		No limit set	--	--	--

Table S3.1(a) Point source emissions to air during abnormal operation of incineration plant – emission limits and monitoring requirements						
Emission point ref. & location	Parameter	Source	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard or method
A1 & A2 - as shown on the Site Plan in Schedule 7	Particulate matter	Incineration exhausts gases	150 mg/m ³	½-hr average	Continuous	EN 14181 or alternative surrogate as agreed in writing with the environment agency during failure of the continuous emission monitor
	Total Organic Carbon (TOC)		20 mg/m ³	½-hr average	Continuous	EN 14181 or alternative surrogate as agreed in writing with the environment agency during failure of the continuous emission monitor
	Carbon monoxide		150 mg/m ³	95% of all 10-minute averages in any 24-hour period	Continuous	EN 14181 or alternative surrogate as agreed in writing with the environment agency during failure of the continuous emission monitor

Table S3.2 Point Source emissions to water (other than sewer) and land – emission limits and monitoring requirements						
Emission point ref. & location	Source	Parameter	Limit (incl. unit)	Reference Period	Monitoring frequency	Monitoring standard or method
W1 as shown on site plan in Schedule 7.	Uncontaminated surface water run-off	None set	None set	--	--	--
W2 as shown on site plan in Schedule 7.	Uncontaminated car park surface water run-off	Visual oil and grease	None visible	Instantaneous	Monthly	--

Table S3.3 Point source emissions to sewer, effluent treatment plant or other transfers off-site– emission limits and monitoring requirements						
Emission point ref. & location	Source	Parameter	Limit (incl. Unit)	Reference period	Monitoring frequency	Monitoring standard or method
S1 – as shown on site plan in Schedule 7.	Water, including boiler blow-down, air compressor condensate, drainage from storage areas, water from dewatering gully waste and wash-down water	None set	None set	--	--	Permanent sampling access not required.

Table S3.4 Process monitoring requirements				
Emission point reference or source or description of point of measurement	Parameter	Monitoring frequency	Monitoring standard or method	Other specifications
As identified in the Application	Wind Speed and Direction	Continuous	Anemometer	--
Location close to the Combustion Chamber inner wall or as identified and justified in Application.	Temperature (° C)	Continuous	Traceable to national standards	As agreed in writing with the Agency.
Incineration plant	Gross electrical efficiency	within 6 months of any modification that significantly affects energy efficiency	Performance test at full load or other method as agreed in writing with the Environment Agency	--

Table S3.5 Residue quality					
Emission point reference or source or description of point of measurement	Parameter	Limit	Monitoring frequency	Monitoring standard or method *	Other specifications
Bottom Ash	TOC	3%	Quarterly	EN 14899 and either EN 13137 or EN 15936	Environment Agency web guidance 'Guidelines for ash sampling and analysis 16 th September 2025'
Bottom Ash	Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs.	-	Quarterly	Environment Agency web guidance 'Guidelines for ash sampling and analysis 16 th September 2025'	
Bottom Ash	Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions	-	Before use of a new disposal or recycling route	Environment Agency web guidance 'Guidelines for ash sampling and analysis 16 th September 2025'	
APC Residues	Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs.	-	Quarterly	Environment Agency web guidance 'Guidelines for ash sampling and analysis 16 th September 2025'	

Table S3.5 Residue quality					
Emission point reference or source or description of point of measurement	Parameter	Limit	Monitoring frequency	Monitoring standard or method *	Other specifications
APC Residues	Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions	-	Before use of a new disposal or recycling route	Environment Agency web guidance 'Guidelines for ash sampling and analysis 16th September 2025'	

*Or other equivalent standard as agreed in writing with the Environment Agency.

Schedule 4 – Reporting

Parameters, for which reports shall be made, in accordance with conditions of this permit, are listed below.

Table S4.1 Reporting of monitoring data			
Parameter	Emission or monitoring point/reference	Reporting period	Period begins
Emissions to air Parameters as required by condition 3.6.1.	A1 & A2	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct
TOC Parameters as required by condition 3.6.1	Bottom Ash	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct
Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs Parameters as required by condition 3.6.1	Bottom Ash	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct
Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions Parameters as required by condition 3.6.1	Bottom Ash	Before use of a new disposal or recycling route	
Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs Parameters as required by condition 3.6.1	APC Residues	Quarterly	1 Jan, 1 Apr, 1 Jul and 1 Oct
Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions Parameters as required by condition 3.6.1	APC Residues	Before use of a new disposal or recycling route	

Table S4.2: Annual production/treatment	
Parameter	Units
Total Municipal Waste Incinerated	tonnes
Total Commercial Waste Incinerated	tonnes
Electrical energy produced	kWh

Parameter	Units
Thermal energy produced e.g. steam for export	kWh
Electrical energy exported	kWh
Electrical energy used on installation	kWh
Waste heat utilised by the installation	kWh

Parameter	Frequency of assessment	Units
Annual Report as required by condition 4.2.2	Annually	-
Electrical energy exported, imported and used at the installation	Annually	kWh / tonne of waste incinerated
Fuel oil consumption	Annually	kg / tonne of waste incinerated
Bottom Ash residue	Annually	Route, tonnes and tonnes / tonne of waste incinerated
APC residue	Annually	Route, tonnes and tonnes / tonne of waste incinerated
Urea consumption	Annually	kg / tonne of waste incinerated
Activated Carbon consumption	Annually	kg / tonne of waste incinerated
Hydrated Lime consumption	Annually	kg / tonne of waste incinerated
Water consumption	Annually	kg / tonne of waste incinerated
Periods of abnormal operation	Annually	No of occasions and cumulative hours for current calendar year for each line.

Media/parameter	Reporting format	Date of form
Annual report required by condition 4.2.2	Annual performance report template	-
Emissions to air until 02/12/2023	Form Air 1-7 or other form as agreed in writing by the Environment Agency	23/07/13
Emissions to air from 03/12/2023	Forms air 1-9 or other forms as agreed in writing by the Environment Agency	29/09/22
Residue quality	Form residue 1 and 2 or other form as agreed in writing by the Environment Agency	29/09/22
Other performance indicators	Form performance 1 or other form as agreed in writing by the Environment Agency	29/09/22

Schedule 5 – Notification

These pages outline the information that the operator must provide.

Units of measurement used in information supplied under Part A and B requirements shall be appropriate to the circumstances of the emission. Where appropriate, a comparison should be made of actual emissions and authorised emission limits.

If any information is considered commercially confidential, it should be separated from non-confidential information, supplied on a separate sheet and accompanied by an application for commercial confidentiality under the provisions of the EP Regulations.

Part A

Permit Number	
Name of operator	
Location of Facility	
Time and date of the detection	

(a) Notification requirements for any malfunction, breakdown or failure of equipment or techniques, accident, or emission of a substance not controlled by an emission limit which has caused, is causing or may cause significant pollution	
To be notified within 24 hours of detection	
Date and time of the event	
Reference or description of the location of the event	
Description of where any release into the environment took place	
Substances(s) potentially released	
Best estimate of the quantity or rate of release of substances	
Measures taken, or intended to be taken, to stop any emission	
Description of the failure or accident.	

(b) Notification requirements for the breach of a limit	
To be notified within 24 hours of detection unless otherwise specified below	
Emission point reference/ source	
Parameter(s)	
Limit	
Measured value and uncertainty	
Date and time of monitoring	

(b) Notification requirements for the breach of a limit	
To be notified within 24 hours of detection unless otherwise specified below	
Measures taken, or intended to be taken, to stop the emission	

Time periods for notification following detection of a breach of a limit	
Parameter	Notification period

(c) Notification requirements for the breach of permit conditions not related to limits	
To be notified within 24 hours of detection	
Condition breached	
Date, time and duration of breach	
Details of the permit breach i.e. what happened including impacts observed.	
Measures taken, or intended to be taken, to restore permit compliance.	

(d) Notification requirements for the detection of any significant adverse environmental effect	
To be notified within 24 hours of detection	
Description of where the effect on the environment was detected	
Substances(s) detected	
Concentrations of substances detected	
Date of monitoring/sampling	

Part B – to be submitted as soon as practicable

Any more accurate information on the matters for notification under Part A.	
Measures taken, or intended to be taken, to prevent a recurrence of the incident	

Measures taken, or intended to be taken, to rectify, limit or prevent any pollution of the environment which has been or may be caused by the emission	
The dates of any unauthorised emissions from the facility in the preceding 24 months.	

Name*	
Post	
Signature	
Date	

* authorised to sign on behalf of the operator

Schedule 6 – Interpretation

“abatement equipment” means that equipment dedicated to the removal of polluting substances from releases from the installation to air or water media.

“abnormal operation” means: any technically unavoidable stoppages, disturbances, or failures of the plant or the measurement devices. Abnormal operation starts as defined in condition 2.3.12 and ends as defined in condition 2.3.13. Abnormal operation is limited to 4 hours for a single occurrence and a total of 60 hours per year per line.

“accident” means an accident that may result in pollution.

“APC residues” means air pollution control residues

“application” means the application for this permit, together with any additional information supplied by the operator as part of the application and any response to a notice served under Schedule 5 to the EP Regulations.

“Annex I” means Annex I to the Waste Framework Directive.

“Annex II” means Annex II to the Waste Framework Directive.

“authorised officer” means any person authorised by the Environment Agency under section 108(1) of The Environment Act 1995 to exercise, in accordance with the terms of any such authorisation, any power specified in section 108(4) of that Act.

“BAT conclusions” means Commission Implementing Decision (EU) 2019/2010 of 12 November 2019 establishing the best available techniques (BAT) conclusions, under Directive 2010/75/EU of the European Parliament and of the Council, for Waste Incineration

“bottom ash” means ash falling through the grate and transported by the grate;

“CEM” Continuous emission monitor

“CEN” means Comité Européen de Normalisation

“bi-annually” means twice per year with at least five months between tests;

“Commissioning” means testing of the new incineration plant that involves any operation of the furnace.

Daily average emissions value means ‘the average of at least 43 valid half hourly averages or for CO the average of at least 43 valid half hourly averages or 129 valid 10 min averages’

“dioxin and furans” means polychlorinated dibenzo-p-dioxins and polychlorinated dibenzofurans.

“disposal”. Means any of the operations provided for in Annex I to Directive 2008/98/EC of the European Parliament and of the Council on waste.

“emissions to land” includes emissions to groundwater.

“EP Regulations” means The Environmental Permitting (England and Wales) Regulations SI 2016 No.1154 and words and expressions used in this permit which are also used in the Regulations have the same meanings as in those Regulations.

“emissions of substances not controlled by emission limits” means emissions of substances to air, water or land from the activities, either from the emission points specified in schedule 3 or from other localised or diffuse sources, which are not controlled by an emission limit.

“groundwater” means all water, which is below the surface of the ground in the saturation zone and in direct contact with the ground or subsoil.

“Hazardous property” has the meaning in Annex III of the Waste Framework Directive

“Hazardous waste” has the meaning given in the Hazardous Waste (England and Wales) Regulations 2005.

“incineration line” means all of the incineration equipment related to a common discharge to air location.

“Industrial Emissions Directive” means DIRECTIVE 2010/75/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 24 November 2010 on industrial emissions

“ISO” means International Standards Organisation.

‘*List of Wastes*’ means the list of wastes established by Commission Decision 2000/532/EC replacing Decision 94/3/EC establishing a list of wastes pursuant to Article 1(a) of Council Directive 75/442/EEC on waste and Council Decision 94/904/EC establishing a list of hazardous waste pursuant to Article 1(4) of Council Directive 91/689/EEC on hazardous waste, as amended from time to time

“LOI” means loss on ignition a technique used to determine the combustible material by heating the ash residue to a high temperature

“MCERTS” means the Environment Agency’s Monitoring Certification Scheme.

“PAH” means Poly-cyclic aromatic hydrocarbon, and comprises Anthanthrene, Benzo[a]anthracene, Benzo[b]fluoranthene, Benzo[k]fluoranthene, Benzo[b]naph(2,1-d)thiophene, Benzo[c]phenanthrene, Benzo[ghi]perylene, Benzo[a]pyrene, Cholanthrene, Chrysene, Cyclopenta[c,d]pyrene, Dibenzo[ah]anthracene, Dibenzo[a,i]pyrene Fluoranthene, Indo[1,2,3-cd]pyrene, Naphthalene

“PCB” means Polychlorinated Biphenyl. Dioxin-like PCBs are the non-ortho and mono-ortho PCBs listed in the table below.

“Pests” means Birds, Vermin and Insects.

“quarter” means a calendar year quarter commencing on 1 January, 1 April, 1 July or 1 October.

“R” means a recovery operation provided for in Annex II to the Waste Framework Directive.

“recovery” means any of the operations provided for in Annex II to Directive 2008/98/EC of the European Parliament and of the Council on waste.

“start up” is any period, where the plant has been non-operational, until waste has been fed to the plant in a sufficient quantity to initiate steady-state conditions as described in the application or agreed in writing with the Environment Agency.

“shut down” is any period where the plant is being returned to a non-operational state as described in the application or agreed in writing with the Environment Agency.

“specified waste” means the following waste codes: 01 01 01, 01 01 02, 01 04 08, 01 04 09, 01 04 13, 02 04 01, 10 11 12, 10 12 08, 10 13 14, 15 01 07, 17 01 01, 17 01 02, 17 01 03, 17 01 07, 17 02 02, 17 03 02, 17 05 04, 17 05 08, 19 12 05, 19 12 09 and 20 02 02.

“TOC” means Total Organic Carbon. In respect of releases to air, this means the gaseous and vaporous organic substances, expressed as TOC. In respect of Bottom Ash, this means the total carbon content of all organic species present in the ash (excluding carbon in elemental form).

“Waste code” means the six digit code referable to a type of waste in accordance with the List of Wastes and in relation to hazardous waste, includes the asterisk

“Waste Framework Directive” or “WFD” means Waste Framework Directive 2008/98/EC of the European Parliament and of the Council on waste

“year” means calendar year ending 31 December.

Where a minimum limit is set for any emission parameter, for example pH, reference to exceeding the limit shall mean that the parameter shall not be less than that limit.

Unless otherwise stated, any references in this permit to concentrations of substances in emissions into air means:

- (a) in relation to emissions from combustion processes, the concentration in dry air at a temperature of 273K, at a pressure of 101.3 kPa and with an oxygen content of 3% dry for liquid and gaseous fuels, 6% dry for solid fuels; and/or

- (b) in relation to emissions from non-combustion sources, the concentration at a temperature of 273K and at a pressure of 101.3 kPa, with no correction for water vapour content
- (c) in relation to gases from incineration plants other than those burning waste oil, the concentration in dry air at a temperature of 273K, at a pressure of 101.3 kPa and with an oxygen content of 11% dry.

For dioxins/furans and dioxin-like PCBs the determination of the toxic equivalence concentration (I-TEQ, & WHO-TEQ for dioxins/furans, WHO-TEQ for dioxin-like PCBs) stated as a release limit and/ or reporting requirement, the mass concentrations of the following congeners have to be multiplied with their respective toxic equivalence factors before summing. When reporting on measurements of dioxins/furans and dioxin-like PCBs, the toxic equivalence concentrations should be reported as a range based on: all congeners less than the detection limit assumed to be zero as a minimum, and all congeners less than the detection limit assumed to be at the detection limit as a maximum. However the minimum value should be used when assessing compliance with the emission limit value in table S3.1.

TEF schemes for dioxins and furans				
Congener	I-TEF	WHO-TEF		
	1990	2005	1997/8	
		Humans / Mammals	Fish	Birds
Dioxins				
2,3,7,8-TCDD	1	1	1	1
1,2,3,7,8-PeCDD	0.5	1	1	1
1,2,3,4,7,8-HxCDD	0.1	0.1	0.5	0.05
1,2,3,6,7,8-HxCDD	0.1	0.1	0.01	0.01
1,2,3,7,8,9-HxCDD	0.1	0.1	0.01	0.1
1,2,3,4,6,7,8-HpCDD	0.01	0.01	0.001	<0.001
OCDD	0.001	0.0003	-	-
Furans				
2,3,7,8-TCDF	0.1	0.1	0.05	1
1,2,3,7,8-PeCDF	0.05	0.03	0.05	0.1
2,3,4,7,8-PeCDF	0.5	0.3	0.5	1
1,2,3,4,7,8-HxCDF	0.1	0.1	0.1	0.1
1,2,3,7,8,9-HxCDF	0.1	0.1	0.1	0.1
1,2,3,6,7,8-HxCDF	0.1	0.1	0.1	0.1
2,3,4,6,7,8-HxCDF	0.1	0.1	0.1	0.1
1,2,3,4,6,7,8_HpCDF	0.01	0.01	0.01	0.01
1,2,3,4,7,8,9-HpCDF	0.01	0.01	0.01	0.01
OCDF	0.001	0.0003	0.0001	0.0001

TEF schemes for dioxin-like PCBs			
Congener	WHO-TEF		
	2005	1997/8	
	Humans / mammals	Fish	Birds
Non-ortho PCBs			
3,4,4',5-TCB (81)	0.0001	0.0005	0.1
3,3',4,4'-TCB (77)	0.0003	0.0001	0.05
3,3',4,4',5 - PeCB (126)	0.1	0.005	0.1
3,3',4,4',5,5'-HxCB(169)	0.03	0.00005	0.001
Mono-ortho PCBs			
2,3,3',4,4'-PeCB (105)	0.00003	<0.000005	0.0001
2,3,4,4',5-PeCB (114)	0.00003	<0.000005	0.0001
2,3',4,4',5-PeCB (118)	0.00003	<0.000005	0.00001
2',3,4,4',5-PeCB (123)	0.00003	<0.000005	0.00001
2,3,3',4,4',5-HxCB (156)	0.00003	<0.000005	0.0001
2,3,3',4,4',5'-HxCB (157)	0.00003	<0.000005	0.0001
2,3',4,4',5,5'-HxCB (167)	0.00003	<0.000005	0.00001
2,3,3',4,4',5,5'-HpCB (189)	0.00003	<0.000005	0.00001

When the following terms appear in the waste code list in Schedule 2, table 2.2, for that table, they have the meaning given below:

'hazardous substance' means a substance classified as hazardous as a consequence of fulfilling the criteria laid down in parts 2 to 5 of Annex I to Regulation (EC) No 1272/2008

'heavy metal' means any compound of antimony, arsenic, cadmium, chromium (VI), copper, lead, mercury, nickel, selenium, tellurium, thallium and tin, as well as these materials in metallic form, as far as these are classified as hazardous substances

'PCBs' means

- polychlorinated biphenyls
- polychlorinated terphenyls
- monomethyl-tetrachlorodiphenyl methane, Monomethyl-dichloro-diphenyl methane, Monomethyldibromo-diphenyl methane
- any mixture containing any of the above mentioned substances in a total of more than 0,005 %by weight


'transition metals' means any of the following metals: any compound of scandium, vanadium, manganese, cobalt, copper, yttrium, niobium, hafnium, tungsten, titanium, chromium, iron, nickel, zinc, zirconium, molybdenum and tantalum, as well as these materials in metallic form, as far as these are classified as hazardous substances

'stabilisation' means processes which change the hazardousness of the constituents in the waste and transform hazardous waste into non-hazardous waste

'solidification' means processes which only change the physical state of the waste by using additives without changing the chemical properties of the waste

'partly stabilised wastes' means wastes containing, after the stabilisation process, hazardous constituents which have not been changed completely into non-hazardous constituents and could be released into the environment in the short, middle or long term.

Schedule 7 – Site plan



END OF PERMIT